# Contract|अनुबंध



Contract No | अनुबंध क्रमांक: GEMC-511687771839154 Generated Date | अनुबंध तिथि: 08-Jan-2024

Organisation Details | संगठन विवरण

Type|प्ररूप : State Autonomous

Ministry|मंत्रालय :

Department|विभाग : Department of Panchayati Raj Organisation Name|संगठन का नाम : SOLAPUR District Panchayats

Office Zone|कार्यालय क्षेत्र: Pandhrewadi Buyer Details | खरीदार विवरण

Designation | पद : Gramsevak Contact No.|संपर्क नंबर : 02186-297326-

Email ID|ईमेल आईडी : gppandharewadi03-mh@panchayat.gov.in

GSTIN|जीएसटीआईएन:

At post Pandharewadi tal pandharpur Dist Solapur, Address|पता:

SOLAPUR, MAHARASHTRA-413301, India

Financial Approval Detail|वित्तीय स्वीकृति विवरण

IFD Concurrence।आईएफडी सहमति:

Designation of Administrative Approval प्रशासनिक अनुमोदन का पदनाम:

Designation of Financial Approval|

वित्तीय अनुमोदन का पदनाम :

Sarpanch/Gramsevak Sarpanch/Gramsevak

Payment Mode|

Role:

MOPR भुगतान का तरीका: Designation | पद : Gramsevak

Email ID|ईमेल आईडी : gppandharewadi03-mh@panchayat.gov.in

Paying Authority Details | भुगतान प्राधिकरण विवरण

BUYER

GSTIN|जीएसटीआईएन:

At post Pandharewadi tal pandharpur Dist Solapur, Address|पता:

Solapur, MAHARASHTRA-413301, India

Seller Details|विक्रैता विवरण

GeM Seller ID|जेम विक्रैता आईडी : RG3D230009936554 Company Name|कंपनी का नाम : AYUSH SALES AND SERVICES

Contact No.|संपर्क नंबर : 07744083737

galavepriyanka35@gmail.com Email ID|ईमेल आईडी :

GAT NO-412,Gram Panchayat Village, Galavewadi,SAN MD 71,Galavewadi, Address|पता:

Sangli, MAHARASHTRA-415315, -

MSME Registration number|एमएसएमई पंजीकरण संख्या : UDYAM-MH-29-0069902

MSE Social Category|एमएसई सामाजिक श्रेणी : General MSE Gender। एमएसई लिंग श्रेणी : Female

GSTIN|जीएसटीआईएन: 27DMHPG4360M1ZQ

\*GST / Tax invoice to be raised in the name of | जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा - Buyer

Delivery Instructions | वितरण निर्देश : NA

## Product Details|उत्पाद विवरण

#	Item Description आइटम विवेरण	Ordered Quantity  आइटम विवरण	Unit   इकाई	Unit Price (INR)  इकाई मूल्य (INR)	Tax Bifurcation (INR)  कर विभाजन (INR)	Price (Inclusive of all Duties and Taxes in INR)  मूल्य (INR में सभी शुल्क और कर सहित)
1	Product Name उत्पाद का नाम : ELITE 36 W LED Luminaire For Flood Light Brand ब्रांड : ELITE Brand Type ब्रांड प्रकार : Registered Brand Catalogue Status कैटलॉग की स्थिति: Catalogue not verified by OEM Selling As कैसे बेचा जा रहा है : Reseller not verified by OEM Category Name & Quadrant श्रेणी का नाम और चतुर्थीश : LED Luminaire (for Flood Light) as per IS 10322, IS 16107 (Q3) Model मॅडल: Elite Led Flood Light 36W (Picture Light) HSN Code एचएसएन कोड: HSN not specified by seller	32	pieces	2,910	NA	93,120
Total Order Value   कुल ऑर्डर मूल्य (in INR)						93,120

Consignee Detail|परेषिती विवरण

S.No क्र.सं.	Consignee   परेषिती	Item वस्तु	Lot No.  लॉट नंबर	Quantity मात्रा	Delivery Start After  दिनांक के बाद डिलीवरी शुरू करना है	Delivery To Be Completed By  वितरण पूरा कब तक करना है
1	Designation पद : Gramsevak Email ID ईमेल आईडी : gppandharewadi03-mh@panchayat.gov.in Contact संपर्क : 02186-297326- GSTIN जीएसटीआईएन : -	ELITE 36 W LED Luminaire For Flood	-	32	08-Jan-2024	23-Jan-2024

Droduct Cooc.	fication for ELITE 36 W LED Luminaire For Flood Light				
Product Specification for ELITE 36 W LED Luminaire For Flood Light					
Specification  विनर्देश	Sub-Spec उप-विनिर्देश	Value मूल्य			
	LED Luminaire conformity to IS:10322/Part 5/Section 5/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest	Yes			
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes			
STANDARDS	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec1)/2012	Туре В			
	Types of LED Modules as per the IS: 16103(Part-2)/2012	Type 3			
	LED Rating/System Wattage/Rated Power	36 W			
	Luminaire System Efficacy (Lumen/watt)	>/= 100 Lm/Watt			
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP65			
	Mounting brackets (included)	Adjustable			
	Warranty for free replacement (in Years)	2			
	Input operating Voltage range and frequency	140 to 270 V olts AC at 50 Hz+/-2 Hz with auto cu off at below 120V			
	Automatic Higher Cut off voltage above 300 volt	Yes			
ELECTRICAL	Rated voltage	230 V AC 50 Hz			
EFFICIENCY	AC Power Factor at full load	≥ 0.95			
	Driver Efficiency (in %age)	≥85			
	Total Harmonics Distortion (in %age)	≤ 10			
	"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer"	Yes			
	LED chip Efficacy	≥130 Lm/Watt			
	Colour temperature (+/-500K)	6000K			
OPTICAL	Working life for LED (Minimum 50,000 burning hours as per LM-80 report)	Yes			
	Colour Rendering Index(CRI)	≥70			
	Beam Angle	≥120			
	Optic lense materal (UV stabilised) (Write NA for without optic lense supply)	Poly carbonate lense			
	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes			
T. (50.44)	Capacitor shall be rated for a temperature of 105 deg. celsius or better	Yes			
THERMAL MANAGEMENT	Junction temperature	< 85 degC			
	Operating temperature range	-10 deg C to +50 deg C			
	Operating Humidity Range	10 % to 95% RH			
	Short circuit Protection	Yes			
	Over load protecton	Yes			
	Over Voltage protection	Yes			
PROTECTION	Reverse polarity	Yes			
	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes			
	Insulation resistance between earth and current carrying part	>100 M ohm			
	The luminaire shall be protected against surges and transients ( Internal)	>/=4KV			
	The luminaire shall be protected against surges and transients of >/=10KV (External)	Yes			
	The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity	Yes			
	The luminaire body must be corrosion resistant epoxy powder coated	Yes			
	All fastners must be of stainless steel	Yes			
	The entire housing (both LED section and driver section) shall be dust and water proof having IP 66 protection as per IS:10322 (Part 1):1982 latest	Yes			
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes			

CONSTRUCTIONAL	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degration due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	1 No.
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	40 cm
	Light Source	SMD LED Chip as per LM 80/IS16106
	"Manufactures Name and and brand on the aluminium die cast body	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
MARKING	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
	LED Make	OSRAM / NICHIA/CREE / SAMSUNG / SEOUL / LUMILED / PHILIPS / EDISON / SYSKA / LUMENMAX / EVERLIGHT / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish on demand by buyer/consignee)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government lab/NABL/ILAC accrediated lab. Reports shall be furnish on demany by buyer (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,)	Yes
REPORTS AND CERTIFICATIONS	LM 80 & TM 21 (Part of LM 80) (Ref. IS:16105:2012) Reports and Photo biological report for LED report from Central Government lab /NABL/ILAC accrediated lab. Reports shall be furnish on demany by buyer (LM-80 report shall haveand the Pohoto Biological report of the LED Chip being used in the luminaire)	Yes
	Availability of test Report from Central Government lab/NABL/ILAC accrediated lab to Indian Standrad IS:10322/part 5/sec-5/2012 and IS 16107 (Part 2/Sec 1): 2012	Yes
	Seller has to furnish Type test report on demand by buyer/consignee	Yes
	DC or AC supplied electronic control gear for LED Module shall comlpy as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for Flood Light shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 5): 2012 as applicable on the date	Yes

Note | टिपणी:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

### ePBG Detail | ईपीबीजी विवरण

#### NA

# Terms and Conditions|नियम और शर्तें

- 1. General Terms and Conditions-
- 1.1 This contract is governed by the General Terms and Conditions, conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।