

Contract | अनुबंध



Contract No | अनुबंध क्रमांक: GEMC-511687702397131

Generated Date | अनुबंध तिथि: 10-Jan-2024

Organisation Details | संगठन विवरण

Type | प्ररूप : Central Government
Ministry | मंत्रालय : Ministry of Railways
Department | विभाग : Indian Railways
Organisation Name | संगठन का नाम : North Eastern Railway
Office Zone | कार्यालय क्षेत्र : Office Of The Principal Chief Material Manager NER

Buyer Details | खरीदार विवरण

Designation | पद : Assistant Material Manager
Contact No. | संपर्क नंबर : -
Email ID | ईमेल आईडी : ammdepot@ner.railnet.gov.in
GSTIN | जीएसटीआईएन : N
Address | पता : Office of the Deputy Chief Materials Manager, North Eastern Railway,
GORAKHPUR, UTTAR PRADESH-273012, India

Financial Approval Detail | वित्तीय स्वीकृति विवरण

IFD Concurrence | आईएफडी सहमति : No
Designation of Administrative Approval | Dy.CEE/WS/GKP
प्रशासनिक अनुमोदन का पदनाम :
Designation of Financial Approval | Dy.CEE/WS/GKP
वित्तीय अनुमोदन का पदनाम :

Paying Authority Details | भुगतान प्राधिकरण विवरण

Role : BUYER
Payment Mode | Railways
भुगतान का तरीका :
Designation | पद : Assistant Material Manager
Email ID | ईमेल आईडी : ammdepot@ner.railnet.gov.in
GSTIN | जीएसटीआईएन : N
Address | पता : Office of the Deputy Chief Materials Manager, North Eastern Railway,
GORAKHPUR, UTTAR PRADESH-273012, India

Seller Details | विक्रेता विवरण

GeM Seller ID | जेम विक्रेता आईडी : B676180000550263
Company Name | कंपनी का नाम : M/S SHREE BAJRANGI ENTERPRISES
Contact No. | संपर्क नंबर : 09984103741
Email ID | ईमेल आईडी : shreebajrangi2018@gmail.com
Address | पता : NILL, GURDWARA PUNJABI COLONI, UNIVERSITY ROAD, PADLEYGANJ,
Gorakhpur, UTTAR PRADESH-273009, -
MSME Registration number | एमएसएमई पंजीकरण संख्या : -
GSTIN | जीएसटीआईएन : 09AKRPA9112A1ZG

*GST / Tax invoice to be raised in the name of | जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा - Consignee

Delivery Instructions | वितरण निर्देश : NA

Product Details | उत्पाद विवरण

#	Item Description आइटम विवरण	Ordered Quantity आइटम विवरण	Unit इकाई	Unit Price (INR) इकाई मूल्य (INR)	Tax Bifurcation (INR) कर विभाजन (INR)	Price (Inclusive of all Duties and Taxes in INR) मूल्य (INR) में सभी शुल्क और कर सहित
1	Product Name उत्पाद का नाम : HALONIX Yes WLed Luminaire Light Brand ब्रांड : HALONIX Brand Type ब्रांड प्रकार : Registered Brand Catalogue Status कैटलॉग की स्थिति : OEM verified catalogue Selling As कैसे बेचा जा रहा है : OEM verified Reseller Category Name & Quadrant श्रेणी का नाम और चतुर्थांश : LED Luminaire (for Road and Street Lights) as per IS 10322, IS 16107, IS 16108, IS 16103, IS 10322 (Q3) Model मॉडल : LED 60W STREET LIGHT as per TDS HSN Code एचएसएन कोड : HSN not specified by seller	75	pieces	6,200	NA	465,000
Total Order Value कुल ऑर्डर मूल्य (in INR)						465,000

Consignee Detail | परेषिती विवरण

S.No क्र.सं.	Consignee परेषिती	Item वस्तु	Lot No. लॉट नंबर	Quantity मात्रा	Delivery Start After दिनांक के बाद डिलीवरी शुरू करना है	Delivery To Be Completed By वितरण पूरा कब तक करना है
1	Designation पद : Dy Chief Electrical Engineer Workshop GKP Email ID ईमेल आईडी : singh.mkner66@gov.in Contact संपर्क : 9794-840305- GSTIN जीएसटीआईएन : 09AAAGM0289C1ZH	HALONIX Yes WLed	-	75	10-Jan-2024	25-Jan-2024

	Address पत्ता : Chief Work Shop Manager, Mechanical Workshop, North Eastern Railway, Gorakhpur, GORAKHPUR, UTTAR PRADESH-273012, India	Luminaire Light				
Product Specification for HALONIX Yes WLed Luminaire Light						
Specification विनिर्देश	Sub-Spec उप-विनिर्देश	Value मूल्य				
STANDARDS	LED Luminaire conformity to IS:10322/Part 5/Section 3/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest	Yes				
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes				
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec.-1)/2012	Type B				
	Types of LED Modules as per the IS:IS: 16103(Part-2)/2012	Type 3				
	LED Rating (in Watts)/System Wattage/Rated Power	60W				
	Luminaire System Efficacy (Lumen/watt)	>/= 100 Lm/Watt				
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP66				
	Warranty for free replacement (in years)	2				
ELECTRICAL EFFICIENCY	Input operating Voltage range and frequency	140 to 270 V olts AC at 50 Hz+/-2 with auto cutt off at below 120V				
	Automatic Higher Cut off voltage above 300 volt	Yes				
	Rated voltage	240 V AC 50 Hz				
	AC Power Factor at full load	≥ 0.95				
	Driver Efficiency (in %age) Upto 100W: ≥85%, Above 100W: >/=90%	Yes				
	Total Harmonics Distortion	≤ 10				
	"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer (as per Cl. 8 of IS:16104:2012 lates)"	Yes				
OPTICAL	LED chip Efficacy	≥130 Lm/Watt				
	Colour temperature	6500K				
	Working life for LED (Minimum 50,000 burning hours as per LM-80 and LM 21 reports)	Yes				
	Colour Rendering Index(CRI)	≥70				
	LED Beam Angle	≥120				
	Optic lense materal (UV stabilised)	Poly carbonate lense				
THERMAL MANAGEMENT	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes				
	Junctiojn / Soldering point temperature shall not exceed 85 deg.c as per LM 80 report	Yes				
	Capacitor shall be rated for a temperature of 105 deg. celsius or better	Yes				
	Operating temperature range	-10 deg C to +50 deg C				
	Operating Humidity Range	10 % to 95% RH				
PROTECTION	Short circuit Protection	Yes				
	Over load protecton	Yes				
	Over Voltage protection	Yes				
	Reverse polarity	Yes				
	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes				
	Insulation resistance between earth and current carrying part	>100 M Ohm				
	The luminaire shall be protected against surges and transients (Internal)	>/=5KV				
	The luminaire shall be protected against surges and transients of >/=10KV (External)	Yes				
	The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity	Yes				
	The luminaire body must be corrosion resistant powder coated	Yes				
	All fastnrs must be of stainless steel	Yes				
	Protection of the entire housing (both LED section and driver section) as per IS:10322 (Part 1):1982 latest	IP66				
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes				

CONSTRUCTIONAL	Luminaries light transparency should be of Toughened glass	Yes
	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degradation due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	1 No.
	Light Source	SMD LED Chip as per LM 80/IS16106
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	50 cm
MARKING	"Manufactures Name and and brand on the aluminium die cast body "	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
	Diameter of pole Luminari suitable for: (upto 45W Pole OD: shall be 40mm), (>45W<120W Pole OD: Shall be 50 mm), (above 120W: OD shall be 60 mm for which luminari is suitable	Yes
Reports And Certifications	LED Make	OSRAM / NICHIA / CREE / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish to the buyer / consignee on demand)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer / consignee on demand (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,	Yes
	LM 80 & TM 21 (Ref. IS:16105:2012) Report and Photo biological report for LED report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer / consignee on demand (LM-80 report shall have the Pohoto Biological re	Yes
	Availability of test Report from Central Government Lab /NABL/ILAC accredited lab to Indian Standrad IS:10322/part 5/sec-3/2012 and IS 16107 (Part 2/Sec 1) : 2012	Yes
	Seller shall furnish the Type test reports to the buyer / consignee on demand	Yes
	DC or AC supplied electronic control gear for LED Module shall complpy as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for road and street lighting shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 3): 2012 as applicable on date	Yes
BIS license of the product उत्पाद का बीआईएस लाइसेंस: 83005100		
ePBG Detail ईपीबीजी विवरण		
NA		
Terms and Conditions नियम और शर्तें		
1. General Terms and Conditions-		
1.1 This contract is governed by the General Terms and Conditions , conditions stipulated to this Product/Service as provided in the Marketplace.		
1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable		
Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.		
नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।		