

Contract | अनुबंध



Contract No | अनुबंध क्रमांक: GEMC-511687778180578

Generated Date | अनुबंध तिथि: 11-Jan-2024

Organisation Details | संगठन विवरण

Type | प्ररूप : Central Autonomous
Ministry | मंत्रालय : Ministry of Education
Department | विभाग : Department of School Education and Literacy
Organisation Name | संगठन का नाम : KENDRIYA VIDYALAYA SANGATHAN
Office Zone | कार्यालय क्षेत्र : KENDRIYA VIDYALAYA JAJPUR

Buyer Details | खरीदार विवरण

Designation | पद : SAMARESH MAJHI
Contact No. | संपर्क नंबर : -
Email ID | ईमेल आईडी : buycon328.kvs.or@gembuyer.in
GSTIN | जीएसटीआईएन : -
Address | पता : AT-AKARPADA, PO:- SRIDHARPUR , VIA- CHITALO, DIST-JAJPUR, ODISHA, PIN-755062, JAJAPUR, ODISHA-755001, India

Financial Approval Detail | वित्तीय स्वीकृति विवरण

IFD Concurrence | आईएफडी सहमति : No
Designation of Administrative Approval | PRINCIPAL
प्रशासनिक अनुमोदन का पदनाम : PRINCIPAL
Designation of Financial Approval | PRINCIPAL
वित्तीय अनुमोदन का पदनाम : PRINCIPAL

Paying Authority Details | भुगतान प्राधिकरण विवरण

Role : PAO
Payment Mode | Offline
भुगतान का तरीका : Offline
Designation | पद : PUSPANJALI SAHOO
Email ID | ईमेल आईडी : buycon483.kvsk.or@gembuyer.in
GSTIN | जीएसटीआईएन : -
Address | पता : AT-AKARPADA, PO:- SRIDHARPUR , VIA- CHITALO, DIST-JAJPUR, ODISHA, PIN-755062, Jajapur, ODISHA-755001, India

Seller Details | विक्रेता विवरण

GeM Seller ID | जेम विक्रेता आईडी : RGD200001805667
Company Name | कंपनी का नाम : BRIGHT SOLUTION
Contact No. | संपर्क नंबर : 07977237223
Email ID | ईमेल आईडी : brightsolution1012@gmail.com
Address | पता : 1 New Sate Chawl, Nr Sivaji Medan Kajupada Pipe Line, K A Road, Sakinaka, MUMBAI, MAHARASHTRA-400072, -
MSME Registration number | एमएसएमई पंजीकरण संख्या : UDYAM-MH-18-0069003
MSE Social Category | एमएसई सामाजिक श्रेणी : General
MSE Gender | एमएसई लिंग श्रेणी : Male
GSTIN | जीएसटीआईएन : 27BVYPP3837L1ZI

*GST / Tax invoice to be raised in the name of | जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा - Buyer

Delivery Instructions | वितरण निर्देश : NA

Product Details | उत्पाद विवरण

#	Item Description आइटम विवरण	Ordered Quantity आइटम विवरण	Unit इकाई	Unit Price (INR) इकाई मूल्य (INR)	Tax Bifurcation (INR) कर विभाजन (INR)	Price (Inclusive of all Duties and Taxes in INR) मूल्य (INR में सभी शुल्क और कर सहित)
1	<p>Product Name उत्पाद का नाम : Unbranded Led Flood Light, Power 30 Watt</p> <p>Brand ब्रांड : NA</p> <p>Brand Type ब्रांड प्रकार : Unbranded</p> <p>Catalogue Status कैटलॉग की स्थिति : Catalogue not verified by OEM</p> <p>Selling As कैसे बेचा जा रहा है : Reseller not verified by OEM</p> <p>Category Name & Quadrant श्रेणी का नाम और चतुर्थांश : Led Flood Light (Q3)</p> <p>Model मॉडल : LED Flood Light 30 Watt</p> <p>HSN Code एचएसएन कोड : HSN not specified by seller</p>	3	pieces	706	NA	2,118
Total Order Value कुल ऑर्डर मूल्य (in INR)						2,118

Consignee Detail | परेषिती विवरण

S.No क्र.सं.	Consignee परेषिती	Item वस्तु	Lot No. लॉट नंबर	Quantity मात्रा	Delivery Start After दिनांक के बाद डिलीवरी शुरू करना है	Delivery To Be Completed By वितरण पूरा कब तक करना है
	<p>Designation पद : SAMARESH MAJHI</p> <p>Email ID ईमेल आईडी : buycon328.kvs.or@gembuyer.in</p> <p>Contact संपर्क : -</p>					

1	GSTIN जीएसटीआईएन : - Address पता : AT-AKARPADA, PO:- SRIDHARPUR , VIA- CHITALO, DIST-JAJPUR, ODISHA, PIN-755062, JAJAPUR, ODISHA-755001, India	Unbranded Led Flood Light, Power 30 Watt	-	3	11-Jan-2024	26-Jan-2024
Product Specification for Unbranded Led Flood Light, Power 30 Watt						
Specification विनिर्देश	Sub-Spec उप-विनिर्देश	Value मूल्य				
Constructional	LED Rating (in Watts)/System Wattage/Rated Power	30 Watt				
	Mounting Plate size	(430mm x 340mm)+/-10mm				
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes				
	The luminaire body must be corrosion resistant powder coated	Yes				
	Protection of the entire housing as per IS:10322 (Part 1):1982 latest	IP66				
	Suitable connector shall be provided for LED connection between driver output and LED	Yes				
	Length of ISI marked three core wire (shall be provided along with supply of material)	100 centimeter				
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes				
	The Luminaires casing/housing shall be Spun Aluminium/Die Cast Aluminium with higher thermal conductivity	Yes				
	Light Source	SMD LED Chip as per LM 80/IS16106				
	Toughened Glass shall not get discoloured shall not suffer degraation due to heat and ageing within warranty period	Yes				
	Luminaries light transparency should be of Toughened glass	Yes				
	Toughned transparent glass cover thickness	>/=4 mm				
	Mounting Pipe size	75 millimeter				
	Thickness IK rating	3mm, IK-08				
	Driver components shall be industrial grade or above	Yes				
	Diffuser Material	UV stabilized injection Moulded Poly Carbonate with Prismatic Cut				
	Adjustable Mounting Bracket	Yes				
Electrical Efficiency	AC Power Factor at full load	>/=0.95				
	Rated voltage	230 V AC 50 Hz				
	Input operating Voltage range and frequency	90 to 300 Volts AC at 50 Hz+/-2				
	Total Harmonics Distortion (as per IS: 16102)	</=10				
	Impact Protection	IK-08				
	Automatic Higher Cut off voltage above 300 volt	Yes				
	Driver Efficiency (in %age)	Upto 100W: >/=85%				
Optical	Working lile for LED (as per LM-80 and LM 21 reports)	>/=50000				
	LED Beam Angle (degree)	>/=120				
	Colour temperature	6000 +/- 500K				
	LED chip Efficacy	>/=135 Lm/Watt				
	Colour Rendering Index(CRI)	>/=70				
	Junction Temperature	<85 deg C				
	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes				
Protection	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes				
	Over Voltage Protection	Yes				
	The luminaire shall be protected against surges and transients of >/=10KV (External)	Yes				
	Short Circuit Protection	Yes				
	Over Load Protection	Yes				

	The luminaire shall be protected against surges and transients (Internal)	>/=5KV
	Insulation resistance between earth and current carrying part	>100 M Ohm
	Reverse Polarity	Yes
Thermal Management	Operating Humidity Range (RH)	10 % to 95%
	Operating Temperature Range	-10 deg C to +50 deg C
Marking	Manufacturer's Name, Model Number, Serial Number on the aluminium die cast body Engraved/Embossed	Yes
	Date of Manufacture (month-year), and lot number as Identification Mark inside each unit and the outside of each packaging box	Yes
	Manufactures Name and and brand on the aluminium die cast body	Engraved/Embossed
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
Standards	Luminaire System Efficacy (Lumen/watt)	>/= 100+/-10 Lm/Watt
	Warranty for free replacement (in years)	1
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP66
	Types of LED Modules as per the IS:IS: 16103(Part-2)/2012	Type 3
Reports And Certifications	Photo biological Safety report as per IEC- 62471 issued by NABL/ vs EPA accredited lab to be submitted	Yes
	Test Report for Protection from High Voltage to be submitted	Yes
	Surge Test Report (as per IEC 61000) to be submitted	Yes
	TM- 21 report Test Report issued by NABL/ vs EPA accredited lab to be submitted	Yes
	LM-79 [as per IS- 16106 & IS-10322] Test Report issued by NABL/ vs EPA accredited lab to be submitted	Yes
	Test Report for Over Volatage Cut off with self restart feature to be submitted	Yes
	LED Make	OSRAM / NICHIA / CREE / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / REFOND / NICHIA / CREE / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGE
	Wind Speed report as per IEC 62262 from NABL accredited Lab to be submitted	Yes
	Orinial Test Report from independent NABL Lab for Compliance with CRS Scheme as per IS-15885 & IS-16104 to be submitted	Yes
	Test certificate as per IEC62305 & IEC61643 from NABL/EPA certified third party Lab to be submitted	Yes
	Test Report for Protection from Low Voltage to be submitted	Yes
	LM-80 [as per IS-16107 & IS- 16103] Test Report issued by NABL/ vs EPA accredited lab to be submitted	Yes
Note टिप्पणी:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.		
ePBG Detail ईपीबीजी विवरण		
NA		
Terms and Conditions नियम और शर्तें		
1. General Terms and Conditions-		
1.1 This contract is governed by the General Terms and Conditions , conditions stipulated to this Product/Service as provided in the Marketplace.		
1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and		

Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।