

1	ईमेल आईडी Email ID : buyer196.nl.mh@gembuyer.in संपर्क Contact : - जीएसटीआईएन GSTIN : - पता Address : NTPC Limited, Mouda Super Thermal Power Project, Mouda Ramtek Road, PO Mouda, NAGPUR, MAHARASHTRA-441104, India, NAGPUR, MAHARASHTRA-441104, India	ewit 5MP BULLET CAMERA	-	10	02-Feb-2024	17-Feb-2024
---	--	---------------------------	---	----	-------------	-------------

Product Specification for ewit 5MP BULLET CAMERA

विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
IMAGE SENSOR	Image Sensor Type	CMOS
	Image Sensor Size	0.37 inch
	Camera Image Sensing capacity (Picture Mode)	5MP
	Resolution	D1 (704 x 480 Pixel),HD (1280 x 720 Pixel),Full HD (1920 x 1080 Pixel),4K HD (3840 X 2160 Pixel),1080P (1920 x 1080),720P (1280 x 720),12MP,D1,CIF,480 x 240,5MP(2592x1944),4MP(2560x1440),3MP(2304x1296),2592x1520,704 x 576,704 x 480,640 x 480,3264x 1840,8MP (3840x2160),1280x 960,2688x 1512,1664x 936,960 x 544,384x 216,2592x 1944,800x 600,2688x 1520,2048x 1536,1664x 936,1280x 720 (720p),,1024x 576,480x 360,640x 360,384x 288,800x 600,640x 480,1600 x 900,960 x 540,800 x 450,480 x 270,320 x 180,160 x 90,3840 x2160,Main Stream,5MP(30fps),4MP(30fps),2K(30fps),3MP(30fps),1080P(30fps),720P(30fps),1080 (60 fps),Sub Stream,1080 (30 fps),720P(30 fps),480x240 (30fps),720P(15fps),D1,CIF (30fps),704x480(30fps),640x480(30fps),352x240 (30fps),Third Stream,D1(30fps),480x240(30fps),CIF(30fps),1920 x 1080 (30fps),1280 x 720 (30fps),704 x 576 (30 fps),1280x960 (30fps),640x480 (30fps),352x288 (30 fps),(Fourth Stream 1920x1080, H.265, 30/25FPS),(Fifth Stream 704x480, H.265, 25/30FPS)
	Day/Night Capable	Yes
	IR illumination Range(mtr)	50
CAMERA TYPE	Type of Camera Housing	BULLET CAMERA
	IP Camera	Yes
	PTZ Camera	No
OPTICS	Lens Type	Varifocal
	Focal Length(mm)	6
	Iris Control	Fixed iris
	Focus Mode	Manual
VIDEO	Frame Rate (fps)	30
	Video Compression	H.264,H.265,H.265+
	Video Streaming	Triple compressed stream
PAN / TILT / ZOOM	Panning Range	NA
	Pan Speed (deg/sec)	NA
	Tilt Range below horizontal (deg)	NA
	Tilt Range above horizontal (deg)	NA
	Tilt Speed (deg/sec)	NA
	Optical Zoom	NA
	Digital Zoom	16X

AUDIO	Audio Support	Yes
	Audio Compression	G.711
	Audio Streaming	One-Way
	Number of Audio Input Channel	1
	Number of Audio Output Channel	1
	External Microphone Support	No
ALARM	Alarm Support	Yes
	Number of Alarm Digital Input	2
	Number of Alarm Relay Output	1
	Pre/Post Alarm Buffer	No
SECURITY	Multi Level User ID/Password	Yes
	IP Address Filtering	Yes
	Encrypted Data Transmission	HTTPS (SSL/TSL)
PERFORMANCE	Minimum Illumination for Capturing Color Image	0.001 lux
	Electronic Shutter Speed(sec)	1/50 to 1/10000
	WDR (Wide Dynamic Range)	120 dB
	SNR (Signal to Noise Ratio)	60-70
	Auto Exposure	Auto Level Control,Electronic Level Control
FEATURES	White Balance (Indoor/Outdoor/Manual Selectable)	Yes
	Auto Gain Control (On/Off selectable)	Yes
	Back Light Compensation	Yes
	Remote Administration (Remote configuration and status using web based tool)	Yes
	Remote System Update Over Network	Yes
	PC Client (PC	

	application client with a channel recording feature support)	Yes
	Web Client (Viewer through HTTP system configuration)	Yes
	On Screen Display in English	Yes
	ONVIF Support	Yes
	Presets	0
	Group Touring	0
	Privacy Zones	4
NETWORK AND INTERFACE	Supported Protocols	UDP,SNMP,RSTP,HTTP,SMTP
	IP Support	Static,Dynamic
	Signal Processing	Digital Signal Process
	IPv6 ready	No
	Wireless	Yes
	Simultaneous Connections	4
STORAGE	On Board SD Card Support	No
	SD Card Memory(GB)	32
HOUSING	Installation Type	Indoor,Outdoor
	Material of the Housing construction	Plastic
	Protection	IP67
	Vandal Resistant Housing	No
	If Yes, IK rating	NA
	Mounting bracket	Wall Mounted
	Weight	300 gram
	Dimensions (mm x mm x mm)	-
POWER SUPPLY	Power Input	12 V DC,PoE
	Power Consumption	6 Watt
	Suitable Adapter Shall be Supplied to Make the Equipment Work on 230 V (+/- 10 %), 50 Hz	Yes
OPERATING	Operating Temperature Range	- 20 to +60 deg C

CONDITIONS	Relative Humidity Non Condensing (%)	95	
	WARRANTY / SERVICES	Warranty	2 year
		Time for Replacement of Defective Product During Warranty Period	36 hour
	Supply of Compatible drivers and software included	Yes	
ENVIRONMENTAL / CERTIFICATION	Availability of facility & infrastructure for verification of all parameters, features, and capability with Seller	Yes	
	Availability of facility to test signal to noise ratio of camera at 0-01 lux	Yes	
	Conformity to Dry Heat test at 55 degree C for 16 hours as per IS :9000 latest	Yes	
	Conformity to Damp heat at 40 degree C - 95% RH (cyclic test): two cycles of 16+8 hours as per IS: 9000 latest	Yes	
	Conformity to Cold test at -10 / -20 degree C for 4 hours as per IS: 9000 latest, as applicable	Yes	
	BIS Registration for safety general requirements as per IS 13252 (Part 1):latest	Yes	
	Availability of Type Test Report from Central Govt /NABL/ILAC accredited lab to prove conformity to specification	No	
	Test Report Number and Date	-	
	Name and		

Address of Test Lab	-
Certification	FCC,CE,BIS,RoHS

उत्पाद का बीआईएस लाइसेंस | BIS license of the product: 81015261

ईपीबीजी विवरण | ePBG Detail

NA

नियम और शर्तें | Terms and Conditions

1. General Terms and Conditions-

- 1.1 This contract is governed by the [General Terms and Conditions](#), conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.