

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687703987877

अनुबंध तिथि | Generated Date : 03-Feb-2024

संगठन विवरण Organisation Details		खरीदार विवरण Buyer Details	
प्ररूप Type :	State Government	पद Designation :	BuyerConsignee new
मंत्रालय Ministry :	-	संपर्क नंबर Contact No. :	05832-000000-
विभाग Department :	Urban Development Department Uttar Pradesh	ईमेल आईडी Email ID :	buycon1.np.wazeergnj@gembuyer.in
संगठन का नाम Organisation Name :	Nagar Panchayat Wazirganj Budaun	जीएसटीआईएन GSTIN :	-
कार्यालय क्षेत्र Office Zone:	Nagar Panchayat Wazeerganj Budaun	पता Address :	Nagar Panchayat Wazeerganj Budaun, Budaun, UTTAR PRADESH-243621, India

वित्तीय स्वीकृति विवरण Financial Approval Detail		भुगतान प्राधिकरण विवरण Paying Authority Details	
आईएफडी सहमति IFD Concurrence :	No	Role:	PAO
प्रशासनिक अनुमोदन का पदनाम	EXECUTIVE OFFICER	भुगतान का तरीका	Offline
Designation of Administrative Approval:		Payment Mode:	
वित्तीय अनुमोदन का पदनाम	EXECUTIVE OFFICER	पद Designation :	PAO new
Designation of Financial Approval :		ईमेल आईडी Email ID :	pao1.np.wazeergnj@gembuyer.in
		जीएसटीआईएन GSTIN :	-
		पता Address:	Nagar Panchayat Wazeerganj Budaun, Budaun, UTTAR PRADESH-243621, India

विक्रेता विवरण Seller Details	
जेम विक्रेता आईडी GeM Seller ID :	GNOM220006421707
कंपनी का नाम Company Name :	Yashi Enterprises
संपर्क नंबर Contact No. :	09358615410
ईमेल आईडी Email ID :	yashienterprises8673@gmail.com
पता Address :	188 CIVIL LINES,NEAR HEAD POST OFFICE,,BAREILLY, Bareilly, UTTAR PRADESH-243001, -
एमएसएई पंजीकरण संख्या MSME Registration number :	UDYAM-UP-15-0045903
एमएसई सामाजिक श्रेणी MSE Social Category :	OCBC
एमएसई लिंग श्रेणी MSE Gender :	Male
जीएसटीआईएन GSTIN:	09AMQPM9436J1Z7

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Consignee

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण | Product Details

#	आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : HALONIX Yes WLed Luminaire Light ब्रांड Brand : HALONIX ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : OEM verified Reseller श्रेणी का नाम और चतुर्भासा Category Name & Quadrant: LED Luminaire (for Road and Street Lights) as per IS 10322, IS 16107, IS 16108, IS 16103, IS 10322 (Q3) मॉडल Model: HLSLD-06-90-CWL-R-SH एचएसएन कोड HSN Code: HSN not specified by seller	50	pieces	8,850	NA	442,500
कुल ऑर्डर मूल्य Total Order Value (in INR)						442,500

परेष्ठी विवरण | Consignee Detail

क्र.सं. S.No	परेष्ठी Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा कब तक करना है Delivery To Be Completed By
1	पद Designation : BuyerConsignee new ईमेल आईडी Email ID : buycon1.np.wazeergnj@gembuyer.in संपर्क Contact : 05832-000000- जीएसटीआईएन GSTIN : -	HALONIX Yes WLed Luminaire Light	-	50	03-Feb-2024	18-Feb-2024

Product Specification for HALONIX Yes WLed Luminaire Light

विवरण Specification	उप-विवरण Sub-Spec	मूल्य Value
STANDARDS	LED Luminaire conformity to IS:10322/Part 5/Section 3/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest	Yes
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec.-1)/2012	Type B
	Types of LED Modules as per the IS:IS: 16103(Part-2)/2012	Type 3
	LED Rating (in Watts)/System Wattage/Rated Power	90W
	Luminaire System Efficacy (Lumen/watt)	>/= 100 Lm/Watt
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP66
ELECTRICAL EFFICIENCY	Warranty for free replacement (in years)	5
	Input operating Voltage range and frequency	140 V to 270 V AC at 50 Hz +/- 2 Hz with low voltage withstand at 100 V AC for 48 Hours
	Automatic Higher Cut off voltage above 300 volt	Yes
	Rated voltage	230 V AC 50 Hz
	AC Power Factor at full load	≥ 0.95
	Driver Efficiency (in %age) Upto 100W: ≥85%, Above 100W: >/=90%	Yes
	Total Harmonics Distortion	≤ 10
OPTICAL	"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer (as per Cl. 8 of IS:16104:2012 lates)"	Yes
	LED chip Efficacy	≥130 Lm/Watt
	Colour temperature	6500K
	Working life for LED (Minimum 50,000 burning hours as per LM-80 and LM 21 reports)	Yes
	Colour Rendering Index(CRI)	≥70
	LED Beam Angle	≥120
THERMAL MANAGEMENT	Optic lense material (UV stabilised)	Poly carbonate lense
	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes
	Junction / Soldering point temperature shall not exceed 85 deg.c as per LM 80 report	Yes
	Capacitor shall be rated for a temperature of 105 deg. celsius or better	Yes
	Operating temperature range	-10 deg C to +50 deg C
PROTECTION	Operating Humidity Range	10 % to 95% RH
	Short circuit Protection	Yes
	Over load protection	Yes
	Over Voltage protection	Yes
	Reverse polarity	Yes
	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes
	Insulation resistance between earth and current carrying part	>100 M Ohm
	The luminaire shall be protected against surges and transients (Internal)	>/=5KV
	The luminaire shall be protected against surges and transients of >/=10KV (External)	No
	The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity	Yes
	The luminaire body must be corrosion resistant powder coated	Yes
	All fastners must be of stainless steel	Yes
	Protection of the entire housing (both LED section and driver section) as per IS:10322 (Part 1):1982 latest	IP66
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes
	Luminaries light transparency should be of Toughened glass	Yes

CONSTRUCTIONAL	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degration due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	2 Nos.
	Light Source	SMD LED Chip as per LM 80/IS16106
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	40 cm
MARKING	"Manufactures Name and and brand on the aluminium die cast body "	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
	Diameter of pole Luminiare suitable for: (upto 45W Pole OD: shall be 40mm), (>45W<120W Pole OD: Shall be 50 mm), (above 120W: OD shall be 60 mm for which luminiare is suitable	Yes
Reports And Certifications	LED Make	Other than OSRAM / NICHIA / CREE / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish to the buyer / consignee on demand)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer / consignee on demand (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,	Yes
	LM 80 & TM 21 (Ref. IS:16105:2012) Report and Photo biological report for LED report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer / consignee on demand (LM-80 report shall have the Pohoto Biological re	Yes
	Availability of test Report from Central Government Lab /NABL/ILAC accredited lab to Indian Standrad IS:10322/part 5/sec-3/2012 and IS 16107 (Part 2/Sec 1) : 2012	Yes
	Seller shall furnish the Type test reports to the buyer / consignee on demand	Yes
	DC or AC supplied electronic control gear for LED Module shall comply as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for road and street lighting shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 3): 2012 as applicable on date	Yes

ईपीबीजी विवरण | ePBG Detail

NA

नियम और शर्तें| Terms and Conditions

1. General Terms and Conditions-

1.1 This contract is governed by the [General Terms and Conditions](#), conditions stipulated to this Product/Service as provided in the Marketplace.

1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंटे आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.