

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687736683819

अनुबंध तिथि | Generated Date : 06-Feb-2024

संगठन विवरण | Organisation Details

प्ररूप | Type : State Government
मंत्रालय | Ministry : -
विभाग | Department : Panchayats and Rural Housing Department Gujarat
संगठन का नाम | Organisation Name : N/A
कार्यालय क्षेत्र | Office Zone : Taluka Panchayat Pardi

खरीदार विवरण | Buyer Details

पद | Designation : Talati Cum Mantri Sonwada
संपर्क नंबर | Contact No. : 0263-7626544-
ईमेल आईडी | Email ID : buycon1106.prhdg.gj@gembuyer.in
जीएसटीआईएन | GSTIN : -
पता | Address : Gram Panchayat Office Sonwada, Ta.Pardi, Dist.Valsad, VALSAD, GUJARAT-396125, India

वित्तीय स्वीकृति विवरण | Financial Approval Detail

आईएफडी सहमति | IFD Concurrence : No
प्रशासनिक अनुमोदन का पदनाम | Designation of Administrative Approval: TALATI SIR
वित्तीय अनुमोदन का पदनाम | Designation of Financial Approval : TALATI SIR

भुगतान प्राधिकरण विवरण | Paying Authority Details

Role: PAO
भुगतान का तरीका | Payment Mode: Internet Banking
पद | Designation : Livestock Inspector
ईमेल आईडी | Email ID : pao63.prhdg.gj@gembuyer.in
जीएसटीआईएन | GSTIN : -
पता | Address: Veterinary Dispensary Paradi Opp. DCO School, Station Road Paradi Ta. Paradi, Valsad, GUJARAT-396125, India

विक्रेता विवरण | Seller Details

जेम विक्रेता आईडी | GeM Seller ID : 3D41190000712679
कंपनी का नाम | Company Name : Taru Enterprise
संपर्क नंबर | Contact No. : 08320525981
ईमेल आईडी | Email ID : taruenterprise23@gmail.com
पता | Address : shop no. - 119, nishal center,,pal,adajan suray, Surat, GUJARAT-395009, -
एमएसएमई पंजीकरण संख्या | MSME Registration number : UDYAM-GJ-22-0078235
एमएसई सामाजिक श्रेणी | MSE Social Category : SC
एमएसई लिंग श्रेणी | MSE Gender : Female
जीएसटीआईएन | GSTIN: 24APZPP3861J1Z4

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Buyer

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण | Product Details

#	आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुक्र और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : paramediq Yes WLed Luminaire Light ब्रांड Brand : paramediq ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM केसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्भास्त्र Category Name & Quadrant : LED Luminaire (for Road and Street Lights) as per IS 10322, IS 16107, IS 16108, IS 16103, IS 10322 (Q3) मॉडल Model: PARAMEDIQ 25W IP66 2Y LED LUMINAR एचएसएन कोड HSN Code: HSN not specified by seller	71	pieces	2,100	NA	149,100
कुल और्डर मूल्य Total Order Value (in INR)						149,100

परेष्टी विवरण | Consignee Detail

क्र.सं. S.No	परेष्टी Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा करना है Delivery To Be Completed By
	पद Designation : Talati Cum Mantri Sonwada ईमेल आईडी Email ID : buycon1106.prhdg.gj@gembuyer.in					

1	संपर्क Contact : 0263-7626544- जीएसटीआईएन GSTIN :- पता Address : Gram Panchayat Office Sonwada, Ta.Pardi, Dist.Valsad, Gujarat., VALSAD, GUJARAT-396125, India	paramediq Yes WLed Luminaire Light	-	71	06-Feb-2024	21-Feb-2024
Product Specification for paramediq Yes WLed Luminaire Light						
विवरण Specification	उप-विवरण Sub-Spec	मूल्य Value				
STANDARDS	LED Luminaire conformity to IS:10322/Part 5/Section 3/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest	Yes				
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes				
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec.-1)/2012	Type B				
	Types of LED Modules as per the IS:IS: 16103(Part-2)/2012	Type 3				
	LED Rating (in Watts)/System Wattage/Rated Power	25W				
	Luminaire System Efficacy (Lumen/watt)	>/= 100 Lm/Watt				
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP66				
ELECTRICAL EFFICIENCY	Warranty for free replacement (in years)	2				
	Input operating Voltage range and frequency	+9000 TO 300 VOLTS AT 50HZ=-2				
	Automatic Higher Cut off voltage above 300 volt	Yes				
	Rated voltage	230 V AC 50 Hz				
	AC Power Factor at full load	≥ 0.95				
	Driver Efficiency (in %age) Upto 100W: ≥85%, Above 100W: >/=90%	Yes				
	Total Harmonics Distortion	≤ 10				
OPTICAL	"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer (as per Cl. 8 of IS:16104:2012 lates)"	Yes				
	LED chip Efficacy	≥130 Lm/Watt				
	Colour temperature	6000+-500K				
	Working life for LED (Minimum 50,000 burning hours as per LM-80 and LM 21 reports)	Yes				
	Colour Rendering Index(CRI)	≥70				
	LED Beam Angle	≥120				
THERMAL MANAGEMENT	Optic lense material (UV stabilised)	Poly carbonate lense				
	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes				
	Junction / Soldering point temperature shall not exceed 85 deg.c as per LM 80 report	Yes				
	Capacitor shall be rated for a temperature of 105 deg. celsius or better	Yes				
	Operating temperature range	-10 deg C to +50 deg C				
PROTECTION	Operating Humidity Range	10 % to 95% RH				
	Short circuit Protection	Yes				
	Over load protection	Yes				
	Over Voltage protection	Yes				
	Reverse polarity	Yes				
	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes				
	Insulation resistance between earth and current carrying part	>100 M Ohm				
	The luminaire shall be protected against surges and transients (Internal)	>/=4KV				
	The luminaire shall be protected against surges and transients of >/=10KV (External)	Yes				
	The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity	Yes				
	The luminaire body must be corrosion resistant powder coated	Yes				
	All fastners must be of stainless steel	Yes				
	Protection of the entire housing (both LED section and driver section) as per IS:10322 (Part 1):1982 latest	IP66				
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes				

CONSTRUCTIONAL	Luminaires light transparency should be of Toughened glass	Yes
	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degration due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	1 No.
	Light Source	SMD LED Chip as per LM 80/IS16106
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	50 cm
MARKING	"Manufactures Name and and brand on the aluminium die cast body "	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
	Diameter of pole Luminiare suitable for: (upto 45W Pole OD: shall be 40mm), (>45W<120W Pole OD: Shall be 50 mm), (above 120W: OD shall be 60 mm for which luminiare is suitable	Yes
Reports And Certifications	LED Make	OSRAM / NICHIA / CREE / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish to the buyer / consignee on demand)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer / consignee on demand (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,	Yes
	LM 80 & TM 21 (Ref. IS:16105:2012) Report and Photo biological report for LED report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer / consignee on demand (LM-80 report shall have the Pohoto Biological re	Yes
	Availability of test Report from Central Government Lab /NABL/ILAC accredited lab to Indian Standrad IS:10322/part 5/sec-3/2012 and IS 16107 (Part 2/Sec 1) : 2012	Yes
	Seller shall furnish the Type test reports to the buyer / consignee on demand	Yes
	DC or AC supplied electronic control gear for LED Module shall comply as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for road and street lighting shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 3): 2012 as applicable on date	Yes

टिप्पणी | Note: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

ईपीबीजी विवरण | ePBG Detail

NA

नियम और शर्तें| Terms and Conditions

1. General Terms and Conditions-

- 1.1 This contract is governed by the [General Terms and Conditions](#), conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.

