अनुबंध|Contract



अनुबंध क्रमांक | Contract No: GEMC-511687796489077 अनुबंध तिथि | Generated Date : 07-Feb-2024

संगठन विवरण | Organisation Details

प्ररूप|Type: State Autonomous

मंत्रालय|Ministry:

Department of Panchayati Raj विभाग | Department : संगठन का नाम|Organisation Name : **GADCHIROLI** District Panchayats

कार्यालय क्षेत्र|Office Zone: YEDANUR174889 खरीदार विवरण|Buyer Details

पद|Designation : GRAMSEVAK संपर्क नंबर|Contact No. : 07135-235114-

ईमेल आईडी|Email ID: gpyedanur-mh@panchayat.gov.in

जीएसटीआईएन|GSTIN :

GRAMPANCHAYAT YEDANUR TA CHAMORSHI DIST

पता|Address : GADCHIROLI,

GADCHIROLI, MAHARASHTRA-442603, India

वित्तीय स्वीकृति विवरण|Financial Approval Detail

आईएफडी सहमति IFD Concurrence :

प्रशासनिक अनुमोदन का पदनाम|

Designation of Administrative Approval:

वित्तीय अनुमोदन का पदनाम|

Designation of Financial Approval:

SECRETARY

SECRETARY

भुगतान प्राधिकरण विवरण|Paying Authority Details

BUYER Role: भुगतान का तरीका| MOPR Payment Mode: पद|Designation: GRAMSEVAK

ईमेल आईडी|Email ID: $gpyedanur\hbox{-}mh@panchayat.gov.in$

जीएसटीआईएन|GSTIN :

GRAMPANCHAYAT YEDANUR TA CHAMORSHI DIST

GADCHIROLI, पता|Address:

Chandrapur, MAHARASHTRA-442603, India

विक्रैता विवरण|Seller Details

जेम विक्रैता आईडी|GeM Seller ID : 6ZX4220005298502 कंपनी का नाम|Company Name : VIVEK CHOPARAM MATALE

संपर्क नंबर|Contact No. : 09404130538 ईमेल आईडी|Email ID : vcmatale@gmail.com mata ward wadsa,desaiganj, पता| Address : gadchiroli, MAHARASHTRA-441207, -

एमएसएमई पंजीकरण संख्या|MSME Registration number :

जीएसटीआईएन|GSTIN: 27BMMPM7248B1ZV

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा|GST / Tax invoice to be raised in the name of - Consignee

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण|Product Details

#	⊭ आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : Unbranded Yes WLed Luminaire Light ब्रांड Brand : NA ब्रांड प्रकार Brand Type : Unbranded केंद्रलॉग की स्थित Catalogue Status: Catalogue not verified by OEM कैंसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थांच Category Name & Quadrant : LED Luminaire (for Road and Street Lights) as per IS 10322, IS 16107, IS 16108, IS 16103, IS 10322 (Q3) मॉडल Model: UNBRANDED 36 WATT LED एचएसएन कोड HSN Code: HSN not specified by seller	35	pieces	2,800	NA	98,000
वु	कुल ऑर्डर मूल्य Total Order Value (in INR)					

परेषिती विवरण|Consignee Detail

क्र.सं. S.No	परेषिती Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	ादनाक के बाद डिलीवरी शुरू	वितरण पूरा कब तक करना है Delivery To Be Completed By
1	पद Designation : GRAMSEVAK ईमेल आईडी Email ID : gpyedanur-mh@panchayat.gov.in संपर्क Contact : 07135-235114- जीएसटीआईएन GSTIN : -	Unbranded Yes WLed	-	35	07-Feb-2024	22-Feb-2024

GADCHIRO	s : GRAMPANCHAYAT YEDANUR TA CHAMORSHI DIST LI, LI, MAHARASHTRA-442603, India	Luminaire Light						
Product Specificat	ion for Unbranded Yes WLed Luminaire Light							
विनिर्देश Specification	उप-विनिर्देश Sub-Spec		मू	मूल्य Value				
	LED Luminaire conformity to IS:10322/Part 5/Section 3/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest		2/Sec Ye	Yes				
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)			Yes				
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec1)/2012			Туре В				
STANDARDS	Types of LED Modules as per the IS:IS: 16103(Part-2)/2012			Type 3				
	LED Rating (in Watts)/System Wattage/Rated Power			36W				
	Luminaire System Efficacy (Lumen/watt)			130 Lm/Watt				
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest			IP65				
	Warranty for free replacement (in years)		2	2				
	Input operating Voltage range and frequency			140 to 270 V olts AC at 50 Hz+/-2 with auto below 120V				
	Automatic Higher Cut off voltage above 300 volt			Yes				
	Rated voltage		23	230 V AC 50 Hz				
ELECTRICAL EFFICIENCY	AC Power Factor at full load			≥ 0.95				
	Driver Efficiency (in %age) Upto 100W: ≥85%, Above 100W: >/=90%			Yes				
	Total Harmonics Distortion				≤ 10			
	"The total circuit power shall not be more than 110 percent manufacturer (as per Cl. 8 of IS:16104:2012 lates)"	of the value declared by the	e Ye	S				
	LED chip Efficacy		≥′	30 Lm/Watt				
	Colour temperature			6500K				
DTIGAL	Working life for LED (Minimum 50,000 burning hours as per LM-80 and LM 21 reports)		Ye	Yes				
OPTICAL	Colour Rendering Index(CRI)		≥7	≥70				
	LED Beam Angle		≥′	20				
	Optic lense materal (UV stabilised)		Po	ly carbonate lens	e			
	Heat sink should be die-cast aluminium along with sufficient effectively	t heat sink fins to dissipate	heat Ye	S				
HERMAL	Junctiojn / Soldering point temperature shall not exceed 85	deg.c as per LM 80 report	Ye	s				
MANAGEMENT	Capacitor shall be rated for a temperature of 105 deg. celsius or better			Yes				
	Operating temperature range			-20 deg. C to +50 deg. C				
	Operating Humidity Range		10	% to 95% RH				
	Short circuit Protection		Ye	s				
	Over load protecton		Ye	s				
	Over Voltage protection			Yes				
	Reverse polarity			Yes				
PROTECTION	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)		t) Ye	Yes				
	Insulation resistance between earth and current carrying part			00 M Ohm				
	The luminaire shall be protected against surges and transie	surges and transients (Internal)						
	The luminaire shall be protected against surges and transie	nts of >/=10KV (External)	Ye	S				
	The Luminaires casing/housing (single piece housing) shall lalloy with higher thermal conductivity	be pressure die casted alun	ninium Ye	S				
	The luminaire body must be corrosion resistant powder coa	ted	Ye					
	All fastners must be of stainless steel		Ye	s				
	Protection of the entire housing (both LED section and drive 1):1982 latest	er section) as per IS:10322 (Part	56				
	Extruded silicon loop gasket shall be provided in the lantern seal between the UV Glass cover and the metal housing to e water, insects etc.,	=	-	S				

	Luminaries light transparency should be of Toughened glass	Yes
CONSTRUCTIONAL	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degration due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	1 No.
	Light Source	SMD LED Chip as per LM 80/IS16106
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	50 cm
	"Manufactures Name and and brand on the aluminium die cast body "	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
MARKING	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
	Diameter of pole Luminiare suitable for: (upto 45W Pole OD: shall be 40mm), (>45W<120W Pole OD: Shall be 50 mm), (above 120W: OD shall be 60 mm for which luminiare is suitable	Yes
	LED Make	OSRAM / NICHIA / CREE / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish to the buyer / consignee on demand)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government Lab /NABL/ILAC accrediated lab. Reports shall be furnish to the buyer / consignee on demand (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,	Yes
Reports And Certifications	LM 80 & TM 21 (Ref. IS:16105:2012) Report and Photo biological report for LED report from Central Government Lab /NABL/ILAC accrediated lab. Reports shall be furnish to the buyer / consignee on demand (LM-80 report shall have the Pohoto Biological re	Yes
	Availability of test Report from Central Government Lab /NABL/ILAC accrediated lab to Indian Standrad IS:10322/part 5/sec-3/2012 and IS 16107 (Part 2/Sec 1): 2012	Yes
	Seller shall furnish the Type test reports to the buyer / consignee on demand	Yes
	DC or AC supplied electronic control gear for LED Module shall comlpy as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for road and street lighting shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 3): 2012 as applicable on date	Yes

टिप्पणी | Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

ईपीबीजी विवरण | ePBG Detail

NA

नियम और शर्तें|Terms and Conditions

- 1. General Terms and Conditions-
- 1.1 This contract is governed by the General Terms and Conditions, conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिटे आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

 $Note: This is system generated file. \ No signature is required. \ Print out of this document is not valid for payment/ transaction purpose.$