अनुबंध|Contract



अनुबंध क्रमांक | Contract No: GEMC-511687756179572 अनुबंध तिथि | Generated Date : 19-Feb-2024

संगठन विवरण | Organisation Details

प्ररूप|Type: State Autonomous

मंत्रालय|Ministry:

विभाग | Department : Department of Panchayati Raj संगठन का नाम|Organisation Name: **CHANDRAPUR** District Panchayats

कार्यालय क्षेत्र|Office Zone: TEMBHURWAHI 173975

खरीदार विवरण|Buyer Details

पद|Designation: SACHIV संपर्क नंबर|Contact No. : 07172-235253-

ईमेल आईडी|Email ID : buycon6671.rdprdm.mh@gembuyer.in

जीएसटीआईएन|GSTIN:

At GP Tembhurwahi Taluka Rajura Dist Chandrapur, पता|Address: CHANDRAPUR, MAHARASHTRA-442905, India

वित्तीय स्वीकृति विवरण | Financial Approval Detail

आईएफडी सहमति|IFD Concurrence :

प्रशासनिक अनुमोदन का पदनाम|

Designation of Administrative Approval: वित्तीय अनुमोदन का पदनाम।

Designation of Financial Approval:

भुगतान प्राधिकरण विवरण | Paying Authority Details

Role: BUYER भुगतान का तरीका|

Offline Payment Mode: SACHIV पद|Designation :

ईमेल आईडी|Email ID : buycon6671.rdprdm.mh@gembuyer.in

जीएसटीआईएन|GSTIN :

At GP Tembhurwahi Taluka Rajura Dist Chandrapur, पता|Address:

Chandrapur, MAHARASHTRA-442905, India

विक्रैता विवरण|Seller Details

जेम विक्रैता आईडी|GeM Seller ID : 9F78200001104808 कंपनी का नाम|Company Name : AMPACET ENERGY SYSTEMS

संपर्क नंबर|Contact No. : 09096476435

ईमेल आईडी|Email ID : gemsolution27@gmail.com

MUSALKHEDA, WATHODA CHANDAS, WATHODA CHANDAS, WARUD, पता| Address :

AMRAVATI, MAHARASHTRA-444806, -

एमएसएमई पंजीकरण संख्या|MSME Registration number : UDYAM-MH-20-0085782 एमएसई सामाजिक श्रेणी|MSE Social Category :

एमएसई लिंग श्रेणी|MSE Gender : Male

जीएसटीआईएन|GSTIN: 27AQBPG7941F1ZX

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा|GST / Tax invoice to be raised in the name of - Buyer

secretary

sarpanch

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण|Product Details

#	अाइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उद्याद का नाम Product Name : OSRAM Yes WLed Luminaire Light ब्रांड Brand : OSRAM ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थीश Category Name & Quadrant : LED Luminaire (for Road and Street Lights) as per IS 10322, IS 16107, IS 16108, IS 16103, IS 10322 (Q3) मॉडल Model: OSRAM 48 W LED ROAD STREET LIGHT एचएसएन कोड HSN Code: HSN not specified by seller	40	pieces	2,450	NA	98,000
वु	कुल ऑर्डर मूल्य Total Order Value (in INR)					

परेषिती विवरण|Consignee Detail

क्र.सं. S.No	परेषिती Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा कब तक करना है Delivery To Be Completed By
1	पद Designation : SACHIV ईमेल आईडी Email ID : buycon6671.rdprdm.mh@gembuyer.in संपर्क Contact : 07172-235253- जीएसटीआईएन GSTIN : -	OSRAM Yes WLed Luminaire Light	-	40	19-Feb-2024	05-Mar-2024

Product Specific	cation for OSRAM Yes WLed Luminaire Light				
विनिर्देश Specificat		मूल्य Value			
ічіч (1) эресінсас	LED Luminaire conformity to IS:10322/Part 5/Section 3/2012 latest and IS: 16107 (Part 2/Sec	मूल्य Value			
	1):2012 latest	Yes			
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes			
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec1)/2012	Type B			
STANDARDS	Types of LED Modules as per the IS:IS: 16103(Part-2)/2012	Туре 3			
	LED Rating (in Watts)/System Wattage/Rated Power	48W			
	Luminaire System Efficacy (Lumen/watt)	130 Lm/Watt			
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP65			
	Warranty for free replacement (in years)	2			
	Input operating Voltage range and frequency	AC 70-440V, 50Hz ,90 to 300 Volts AC at 50 Hz+/-2,1 270 V olts AC at 50 Hz+/-2 with auto cutt off at below 120V			
	Automatic Higher Cut off voltage above 300 volt	Yes			
ELECTRICAL	Rated voltage	230 V AC 50 Hz			
EFFICIENCY	AC Power Factor at full load	≥ 0.95			
	Driver Efficiency (in %age) Upto 100W: ≥85%, Above 100W: >/=90%	Yes			
	Total Harmonics Distortion	≤ 10			
	"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer (as per Cl. 8 of IS:16104:2012 lates)"	Yes			
	LED chip Efficacy	≥130 Lm/Watt			
	Colour temperature	5700+/-355K			
OPTICAL	Working life for LED (Minimum 50,000 burning hours as per LM-80 and LM 21 reports)	Yes			
OPTICAL	Colour Rendering Index(CRI)	≥70			
	LED Beam Angle	≥120			
	Optic lense materal (UV stabilised)	Poly carbonate lense			
	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes			
THERMAL	Junctiojn / Soldering point temperature shall not exceed 85 deg.c as per LM 80 report	Yes			
MANAGEMENT	Capacitor shall be rated for a temperature of 105 deg. celsius or better	Yes			
	Operating temperature range	-20 deg. C to +50 deg. C			
	Operating Humidity Range	10 % to 95% RH			
	Short circuit Protection	Yes			
	Over load protecton	Yes			
	Over Voltage protection	Yes			
	Reverse polarity	Yes			
PROTECTION	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes			
	Insulation resistance between earth and current carrying part	>100 M Ohm			
	The luminaire shall be protected against surges and transients (Internal)	>/= 8Kv			
	The luminaire shall be protected against surges and transients of >/=10KV (External)	Yes			
	The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity	Yes			
	The luminaire body must be corrosion resistant powder coated	Yes			
	All fastners must be of stainless steel	Yes			
	Protection of the entire housing (both LED section and driver section) as per IS:10322 (Part 1):1982 latest	IP66			
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes			

	Luminaries light transparency should be of Toughened glass	Yes
CONSTRUCTIONAL	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degration due to heat and ageing within warranty period	Polycarbonate diffuser
	Number of electronic control gear (power supplies)	3 Nos.
	Light Source	SMD LED Chip as per LM 80/IS16106
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	40 cm
	"Manufactures Name and and brand on the aluminium die cast body "	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
MARKING	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
	Diameter of pole Luminiare suitable for: (upto 45W Pole OD: shall be 40mm), (>45W<120W Pole OD: Shall be 50 mm), (above 120W: OD shall be 60 mm for which luminiare is suitable	Yes
	LED Make	OSRAM / NICHIA / CREE / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish to the buyer / consignee on demand)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government Lab /NABL/ILAC accrediated lab. Reports shall be furnish to the buyer / consignee on demand (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,	Yes
Reports And Certifications	LM 80 & TM 21 (Ref. IS:16105:2012) Report and Photo biological report for LED report from Central Government Lab /NABL/ILAC accrediated lab. Reports shall be furnish to the buyer / consignee on demand (LM-80 report shall have the Pohoto Biological re	Yes
	Availability of test Report from Central Government Lab /NABL/ILAC accrediated lab to Indian Standrad IS:10322/part 5/sec-3/2012 and IS 16107 (Part 2/Sec 1): 2012	Yes
	Seller shall furnish the Type test reports to the buyer / consignee on demand	Yes
	DC or AC supplied electronic control gear for LED Module shall comlpy as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for road and street lighting shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 3): 2012 as applicable on date	Yes

टिप्पणी | Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

ईपीबीजी विवरण | ePBG Detail

NA

नियम और शर्तें|Terms and Conditions

- 1. General Terms and Conditions-
- 1.1 This contract is governed by the General Terms and Conditions, conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिटे आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.