

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687701860947

अनुबंध तिथि | Generated Date : 27-Feb-2024

संगठन विवरण | Organisation Details

प्ररूप | Type : Central Autonomous
मंत्रालय | Ministry : Ministry of Education
विभाग | Department : Department of School Education and Literacy
संगठन का नाम | Organisation Name : KENDRIYA VIDYALAYA SANGATHAN
कार्यालय क्षेत्र | Office Zone : K V No 2 Jalandhar Cantt

खरीदार विवरण | Buyer Details

पद | Designation : PGT
संपर्क नंबर | Contact No. : 0181-2262141-
ईमेल आईडी | Email ID : buyer-1670@kvs.gov.in
जीएसटीआईएन | GSTIN : -
पता | Address : Opp Topkhana Bazar , Jalandhar Cantt.,
JALANDHAR, PUNJAB-144005, India

वित्तीय स्वीकृति विवरण | Financial Approval Detail

आईएफडी सहमति | IFD Concurrence : No
प्रशासनिक अनुमोदन का पदनाम | Designation of Administrative Approval : Principal
वित्तीय अनुमोदन का पदनाम | Designation of Financial Approval : PRINCIPAL

भुगतान प्राधिकरण विवरण | Paying Authority Details

Role: PAO
भुगतान का तरीका | Payment Mode: Offline
पद | Designation : PGT HINDI
ईमेल आईडी | Email ID : p.authority-1670@kvs.gov.in
जीएसटीआईएन | GSTIN : -
पता | Address : Opp Topkhana Bazar , Jalandhar Cantt.,
Jalandhar, PUNJAB-144005, India

विक्रेता विवरण | Seller Details

जेम विक्रेता आईडी | GeM Seller ID : 0AR7210001946776
कंपनी का नाम | Company Name : JINISHA ENTERPRISES
संपर्क नंबर | Contact No. : 08146828146
ईमेल आईडी | Email ID : jinishaenterprises2022@gmail.com
पता | Address : H. No A-8, NEW GANESH NAGAR, TALHANROAD, DAKOHA,
Jalandhar, PUNJAB-144023, -
एमएसएमई पंजीकरण संख्या | MSME Registration number : UDYAM-PB-10-0031137
एमएसई सामाजिक श्रेणी | MSE Social Category : OBC
एमएसई लिंग श्रेणी | MSE Gender : Male
जीएसटीआईएन | GSTIN : 03BEIPK2026P1ZH

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Consignee

वितरण निर्देश | Delivery Instructions : as per requirements

उत्पाद विवरण | Product Details

| # | आइटम विवरण Item Description | आइटम विवरण Ordered Quantity | इकाई Unit | इकाई मूल्य (INR) Unit Price (INR) | कर विभाजन (INR) Tax Bifurcation (INR) | मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR) |
|--|---|-------------------------------|-------------|-------------------------------------|---|---|
| 1 | उत्पाद का नाम Product Name : Unbranded Led Flood Light, Power 50 Watt ब्रांड Brand : NA ब्रांड प्रकार Brand Type : Unbranded कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Led Flood Light (Q3) मॉडल Model: EGTFL50w एचएसएन कोड HSN Code: HSN not specified by seller | 3 | pieces | 1,850 | NA | 5,550 |
| कुल ऑर्डर मूल्य Total Order Value (in INR) | | | | | | 5,550 |

परेषिती विवरण | Consignee Detail

| क्र.सं. S.No | परेषिती Consignee | वस्तु Item | लॉट नंबर Lot No. | मात्रा Quantity | दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After | वितरण पूरा कब तक करना है Delivery To Be Completed By |
|----------------|--|--|--------------------|-------------------|---|--|
| 1 | पद Designation : PGT ईमेल आईडी Email ID : buyer-1670@kvs.gov.in संपर्क Contact : 0181-2262141- जीएसटीआईएन GSTIN : - पता Address : Opp Topkhana Bazar , Jalandhar Cantt., | Unbranded Led Flood Light, Power 50 Watt | - | 3 | 27-Feb-2024 | 13-Mar-2024 |

Product Specification for Unbranded Led Flood Light, Power 50 Watt

| विनिर्देश Specification | उप-विनिर्देश Sub-Spec | मूल्य Value |
|---------------------------|---|---|
| Constructional | LED Rating (in Watts)/System Wattage/Rated Power | 50 Watt |
| | Mounting Plate size | (430mm x 340mm)+/-10mm |
| | The Luminaires works on single phase three wires system (Phase, Neutral and Earth) | Yes |
| | The luminaire body must be corrosion resistant powder coated | Yes |
| | Protection of the entire housing as per IS:10322 (Part 1):1982 latest | IP66 |
| | Suitable connector shall be provided for LED connection between driver output and LED | Yes |
| | Length of ISI marked three core wire (shall be provided along with supply of material) | 50 centimeter |
| | Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc., | Yes |
| | The Luminaires casing/housing shall be Spun Aluminium/Die Cast Aluminium with higher thermal conductivity | Yes |
| | Light Source | SMD LED Chip as per LM 80/IS16106 |
| | Toughened Glass shall not get discoloured shall not suffer degradation due to heat and ageing within warranty period | Yes |
| | Luminaries light transparency should be of Toughened glass | Yes |
| | Toughened transparent glass cover thickness | >/=4 mm |
| | Mounting Pipe size | 0 millimeter |
| | Thickness Ik rating | 3mm, IK-08 |
| | Driver components shall be industrial grade or above | Yes |
| | Diffuser Material | UV stabilized injection Moulded Poly Carbonate with Prismatic Cut |
| | Adjustable Mounting Bracket | Yes |
| Electrical Efficiency | AC Power Factor at full load | >/=0.95 |
| | Rated voltage | 230 V AC 50 Hz |
| | Input operating Voltage range and frequency | 90 to 300 Volts AC at 50 Hz+/-2 |
| | Total Harmonics Distortion (as per IS: 16102) | </=10 |
| | Impact Protection | IK-08 |
| | Automatic Higher Cut off voltage above 300 volt | Yes |
| | Driver Efficiency (in %age) | Upto 100W: >/=85% |
| Optical | Working life for LED (as per LM-80 and LM 21 reports) | >/=50000 |
| | LED Beam Angle (degree) | >/=120 |
| | Colour temperature | 6000 +/- 500K |
| | LED chip Efficacy | >/=135 Lm/Watt |
| | Colour Rendering Index(CRI) | >/=80 |
| | Junction Temperature | <85 deg C |
| | Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively | Yes |
| Protection | High voltage test (1.5 KV for one minute between supply terminals and body of the unit) | Yes |
| | Over Voltage Protection | Yes |
| | The luminaire shall be protected against surges and transients of >/=10KV (External) | Yes |
| | Short Circuit Protection | Yes |
| | Over Load Protection | Yes |
| | The luminaire shall be protected against surges and transients (| >/=5KV |

| | | |
|----------------------------|--|--|
| | Internal) | |
| | Insulation resistance between earth and current carrying part | >100 M Ohm |
| | Reverse Polarity | Yes |
| Thermal Management | Operating Humidity Range (RH) | 10 % to 95% |
| | Operating Temperature Range | 0 deg. C to 45 deg. C |
| Marking | Manufacturer's Name, Model Number, Serial Number on the aluminium die cast body Engraved/Embossed | Yes |
| | Date of Manufacture (month-year), and lot number as Identification Mark inside each unit and the outside of each packaging box | Yes |
| | Manufactures Name and and brand on the aluminium die cast body | Engraved/Embossed |
| | The operation characteristics voltage and power be marked inside of each LED luminaire unit | Yes |
| Standards | Luminaire System Efficacy (Lumen/watt) | >= 100+/-10 Lm/Watt |
| | Warranty for free replacement (in years) | 2 |
| | Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group) | Yes |
| | Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest | IP66 |
| | Types of LED Modules as per the IS:IS: 16103(Part-2)/2012 | Type 3 |
| Reports And Certifications | Photo biological Safety report as per IEC- 62471 issued by NABL/ vs EPA accredited lab to be submitted | Yes |
| | Test Report for Protection from High Voltage to be submitted | Yes |
| | Surge Test Report (as per IEC 61000) to be submitted | Yes |
| | TM- 21 report Test Report issued by NABL/ vs EPA accredited lab to be submitted | Yes |
| | LM-79 [as per IS- 16106 & IS-10322] Test Report issued by NABL/ vs EPA accredited lab to be submitted | Yes |
| | Test Report for Over Volatage Cut off with self restart feature to be submitted | Yes |
| | LED Make | OSRAM / NICHIA / CREE / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / REFOND / NICHIA / CREE / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGE |
| | Wind Speed report as per IEC 62262 from NABL accredited Lab to be submitted | Yes |
| | Orinial Test Report from independent NABL Lab for Compliance with CRS Scheme as per IS-15885 & IS-16104 to be submitted | Yes |
| | Test certificate as per IEC62305 & IEC61643 from NABL/EPA certified third party Lab to be submitted | Yes |
| | Test Report for Protection from Low Voltage to be submitted | Yes |
| | LM-80 [as per IS-16107 & IS- 16103] Test Report issued by NABL/ vs EPA accredited lab to be submitted | Yes |

टिप्पणी | Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

ईपीबीजी विवरण | ePBG Detail

NA

नियम और शर्तें | Terms and Conditions

1. General Terms and Conditions-

- 1.1 This contract is governed by the [General Terms and Conditions](#), conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions

(ATC), as applicable

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.