

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687741687448

अनुबंध तिथि | Generated Date : 27-Feb-2024

संगठन विवरण Organisation Details		खरीदार विवरण Buyer Details				
प्रकार Type :	State Government	पद Designation :	TGT			
मंत्रालय Ministry :	-	संपर्क नंबर Contact No. :	011-27682997-			
विभाग Department :	Education Department Delhi	ईमेल आईडी Email ID :	con256.doe.delhi@gembuyer.in			
संगठन का नाम Organisation Name :	Directorate of Education	जीएसटीआईएन GSTIN :	N			
कार्यालय क्षेत्र Office Zone :	Dde North West A	पता Address :	G (CO-ED) SSS, KEWAL PARK, AZAD PUR, NEW DELHI-110033, CENTRAL DELHI, DELHI-110088, India			
वित्तीय स्वीकृति विवरण Financial Approval Detail		भुगतान प्राधिकरण विवरण Paying Authority Details				
आईएफडी सहमति IFD Concurrence :	No	Role:	BUYER			
प्रशासनिक अनुमोदन का पदनाम Designation of Administrative Approval:	PRINCIPAL	भुगतान का तरीका Payment Mode:	Offline			
वित्तीय अनुमोदन का पदनाम Designation of Financial Approval :	DDO	पद Designation :	TGT			
		ईमेल आईडी Email ID :	con256.doe.delhi@gembuyer.in			
		जीएसटीआईएन GSTIN :	N			
		पता Address:	G (CO-ED) SSS, KEWAL PARK, AZAD PUR, NEW DELHI-110033, NORTH WEST DELHI, DELHI-110088, India			
विक्रेता विवरण Seller Details						
जेम विक्रेता आईडी GeM Seller ID :	J3Q3220006709406					
कंपनी का नाम Company Name :	PRAYAG ENTERPRISES					
संपर्क नंबर Contact No. :	08299159944					
ईमेल आईडी Email ID :	prayagenterprises73@gmail.com					
पता Address :	Ground floor Gali no- 22 ,C-1/214,C Block Khajuri Khass, East Delhi, DELHI-110094, -					
एमएसएमई पंजीकरण संख्या MSME Registration number :	UDYAM-DL-05-0017248					
एमएसई सामाजिक श्रेणी MSE Social Category :	General					
एमएसई लिंग श्रेणी MSE Gender :	Male					
जीएसटीआईएन GSTIN:	07EEGPP6642H1Z6					
*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा GST / Tax invoice to be raised in the name of - Buyer						
वितरण निर्देश Delivery Instructions : .						
उत्पाद विवरण Product Details						
#	आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : Artis Intel Atom n2800; clock frequency 1.86GHz Public Address System ब्रांड Brand : Artis ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Public Address System (Q3) मॉडल Model: Artis BT908 WIRELESS TROLLEY BLUETOOTH SPEAKER एचएसएन कोड HSN Code: HSN not specified by seller	1	pieces	20,000	NA	20,000
कुल ऑर्डर मूल्य Total Order Value (in INR)						20,000
परिप्रेषित विवरण Consignee Detail						
क्र.सं. S.No	परिप्रेषित Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा कब तक करना है Delivery To Be Completed By
1	पद Designation : CONSIGNEE ईमेल आईडी Email ID : sunita.sk222@gmail.com संपर्क Contact : - जीएसटीआईएन GSTIN : N	Artis Intel Atom n2800; clock frequency 1.86GHz	-	1	27-Feb-2024	13-Mar-2024

पता | Address : G (CO-ED) SSS, KEWAL PARK, AZAD PUR, NEW DELHI-110033, CENTRAL DELHI, DELHI-110088, India

Public Address System

Product Specification for Artis Intel Atom n2800; clock frequency 1.86GHz Public Address System

विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
Specification	Microphone input	Nominal level 14 mV at 3.3 k Ω (MIC power supply voltage 2.5 V)
	Line output	Nominal level 0 dB and 0.775 V
	Floating contacts	2 inputs for floating contacts (each capable of reading 5 level inputs)
	Control input	0 - 10 V, for controlling the volume remotely
	Relay output	(switch-over contact) 30 V/1 A, 100000 switching cycles
	Audio output	70 V/100 V
	Extension plug	Yes
	Ports	RJ 45 modular plug-in ports with LEDs for IP uplink/downlink
	Connection terminals	Pluggable screw-in terminals for connecting the power supply, output, microphone, inputs, line output, 70 V/100 V audio output, loudspeakers
	Power Supply:	230V AC and external power supply, 20-26 VDC (max. 2.6 A at 4 Ω /50 W or max. 1.3 A at 8 Ω /25 W, 3 A at 70 V/100 V audio output) or PoE (IEEE 802.3af), power consumption of terminal device: Class 0 (0.44 W to 12.95 W), with attenuated output power (up to 12 dB attenuation corresponds to an output power of approx. 6 W)
	Cabling	min. Cat. 5 Line length of up to 100 m in LAN
	Protocol	IoIP® protocol based on UDP/IP
	Marking	NA
	Line Monitoring	Output or speaker circuit
	Fault Detection	Detection, Optical and Acoustic display on the control stand in case of short circuit, earth fault, interruption or a change in impedance if the speaker circuit connected on the output side
	Design	plastic; front panel: white aluminum (RAL 9006); rear housing: graphite grey (RAL 7024); degree of protection IP 50 rating; installable as a console or as a built-in control desk; easy-to-clean and chemical-resistant foil surface
	Operating range	0°C to +70°C; max. non-condensing relative ambient humidity 80%;
	Features	Monochrome LCD display; capable of being backlit white, graphical menu guidance, 128x64 pixel resolution, 3-colour multi-function LED display for voice call indication
	Keypad	full alphanumeric keypad, 12-part (0-9, T, X), 4 function keys, white backlight; actuation force: 3N, 1.5x10 ⁶ switching cycles, 8 one-touch dialling buttons with 3-colour LEDs
	Microphone	Omnidirectional electret microphone; max. 7 m speaking distance
	Loudspeaker	2x 8 Ω loudspeakers with a special membrane; 85 dB/W/m sound pressure
	Amplifier	integrated Class D amplifier; 2.5 W
	Max sound pressure	99 dB
	Handset/headset	EM sensitivity: 14 mVrms; impedance EM: 3.3 k Ω ; EM supply: 2.5 V; EP level: 850 mVrms at 0 dBm0; EP impedance: 200 Ω
	Transmission bandwidth	16,000 Hz
	Transfer rate	10/100 Mbit/s (full/half duplex)

	Inputs	Audio Line In 3.5mm Jack Stereo, USB 2.0 Type A
	Outputs	Audio Line Out Stereo 3.5mm Jack (For Headphones Or External Speakers)
	Connections	pluggable screw-in terminals; extension plug: Handset module, one-touch dialling module, gooseneck module, headset module, IP-uplink: shielded RJ45 modular plug-in port
	Power supply	PoE (IEEE 802.3af); power consumption of terminal device: Class 0 (0.44 W to 12.95 W) or external power supply, 20-30 VDC, Type PA30W24V possible; power consumption: max. 5.7 W
	Dimensions W x H x D	290mm x 109mm x 198mm (Including Housing)
	Weight	Aproxx 1.5Kg
The intercom system or control unit of the intercom system	32 one big touch keys	Yes
	4 large label fields	NA
	RGB Backlit buttons	Yes
	Degree of protection	NA
	Easy to clean and chemical resistant surface foil	Yes
	Front panel white aluminum (RAL 9006); rear housing graphite grey (RAL 7024)	NA
	Switching cycles	NA
	Actuation Force : 3N	NA
	Ribbon cable to base terminal (length: 35 cm) or ribbon cable to the next one-touch key module CDDD 32P	NA
	Power supply: external supply, 20-30VDC, type PA30W24V possible	Yes
	Temperature range: 0° to +70°C; up to 80% non-condensing relative ambient humidity	Yes
	Mounting:console or built-in control desk; mounted with back housing supplied	Yes
	Dimensions W x H x D: including back housing: 262x196x45 mm	Yes
	Weight:approx 850 g	NA
Stand Alone Touch Module	Industrial PC with Windows 7 Embedded for a variety of applications; For use of one-touch key or video monitor-module of Intercom Client, ComWIN Light or ComWIN Weg Client; Can also be used for third-party software products (building management systems, video management systems, etc); protection class IP 20; material plastic; scope of supply: module with back housing, power supply, brief description; plastic; front panel white aluminium (RAL 9006); back housing graphite grey (RAL 7024); protection class IP 20 (with headset plugged in); easy-to-clean and chemical-resistant foil surface; scratch-proof genuine glass display	NA
	Processor	Intel Atom n2800; clock frequency 1.86GHz
	Display	8,4" (21,3 cm) TFT-LCD colour-display with touch functionality
	Connection:Line-Out 3,5mm jack; DVI-I Port; 2x USB2; 2x RJ45 (Uplink/Downlink)	Yes
	Memory	1GB RAM, MicroSD Port (16/32 GB) Class 10 supported.
	Power supply: external power source, 12VDC; plug in power unit PA30W12V in scope of delivery	Yes
	Temperature range: 0° to +40°C; up to 80% non-condensing relative ambient humidity	Yes
	Mounting: console or built-in control desk; mounted with back housing supplied	Yes
Dimensions W x H x D:	290mm x 109mm x 198mm (Including Housing)	
	Module with back housing, connector, mounting materials :Relay output (switch-over contact) 30 V/1 A, 100000 switching cycles plastic; front panel white aluminum (RAL 9006); back housing graphite grey (RAL 7024); protection class IP 50 (with headset plugged in); easy-to-clean and chemical-resistant foil surface	No
	Connection: connecting cable to base terminal (length: 50 cm); 4C4P socket for headset	No
	Power supply: from base terminal	Yes
	Temperature range: 0° to +70°C; up to 80% non-condensing relative ambient humidity	Yes
	Mounting:console or built-in control desk; mounted with back housing supplied	Yes
	Dimensions W x H x D: including back housing: 55x196x43 mm	No
	Weight:approx 420g	No
	plastic; front panel white aluminum (RAL 9006); back housing and handset graphite grey (RAL	

General	Design :	7024); protection class IP 40; easy-to-clean and chemical-resistant foil surface
	Connection:4-pin cable connecting cable with plug (length: 50 cm)	Yes
	Power supply: from base terminal	Yes
	Temperature range: 0° to +70°C; up to 80% non-condensing relative ambient humidity	Yes
	Microphone: Omnidirectional electret microphone	Yes
	Loudspeaker: 50Ω	Yes
	Frequency range: 200–16,000 Hz	Yes
	Button: push-to-talk key	Yes
	Mounting:console or built-in control desk; mounted with back housing supplied	Yes
	Dimensions W x H x D: including back housing:	290mm x 109mm x 198mm (Including Housing)
	Weight:	Aproxx 1.5Kg

टिप्पणी | Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

ईपीबीजी विवरण | ePBG Detail

NA

नियम और शर्तें | Terms and Conditions

1. General Terms and Conditions-

- 1.1 This contract is governed by the [General Terms and Conditions](#), conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.