

## अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687748097563

अनुबंध तिथि | Generated Date : 01-Mar-2024

संगठन विवरण   Organisation Details	खरीदार विवरण   Buyer Details
प्ररूप   Type : Central Government मंत्रालय   Ministry : Ministry of Finance विभाग   Department : Department of Revenue संगठन का नाम   Organisation Name : N/A कार्यालय क्षेत्र   Office Zone: Customs Excise And Service Tax Appellate Tribunal	पद   Designation : Registrar संपर्क नंबर   Contact No. : 011-26101583- ईमेल आईडी   Email ID : bineeshkr.ks@gov.in जीएसटीआईएन   GSTIN : 07DELCO8254B1DZ पता   Address : WEST BLOCK NO. 2, R.K.PURAM, NEW DELHI, DELHI-110066, India

वित्तीय स्वीकृति विवरण   Financial Approval Detail	भुगतान प्राधिकरण विवरण   Paying Authority Details
आईएफडी सहमति   IFD Concurrence : Yes प्रशासनिक अनुमोदन का पदनाम   Designation of Administrative Approval: Registrar वित्तीय अनुमोदन का पदनाम   Designation of Financial Approval : Registrar	Role: DDO भुगतान का तरीका   Payment Mode: PFMS पद   Designation : Account Officer ईमेल आईडी   Email ID : ao.dl-cestat@gov.in जीएसटीआईएन   GSTIN : N पता   Address: WEST BLOCK NO. 2, R.K.PURAM, WEST DELHI, DELHI-110066, India

विक्रेता विवरण   Seller Details
जेम विक्रेता आईडी   GeM Seller ID : B815180000323367 कंपनी का नाम   Company Name : Saiansh Enterprises संपर्क नंबर   Contact No. : 09811275756 ईमेल आईडी   Email ID : ashoknayak_25@rediffmail.com पता   Address : 195/2, Mehrauli, Mehrauli, Mehrauli, South West delhi, DELHI-110030, - एमएसएमई पंजीकरण संख्या   MSME Registration number : - जीएसटीआईएन   GSTIN: 07AGGPN9285Q1ZC

\*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Buyer

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण   Product Details						
#	आइटम विवरण   Item Description	आइटम विवरण   Ordered Quantity	इकाई   Unit	इकाई मूल्य (INR)   Unit Price (INR)	कर विभाजन (INR)   Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित)   Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम   Product Name : R&M MARKETING Free standing PARTITION PANEL Conformity to technical requirements ब्रांड   Brand : R&M MARKETING ब्रांड प्रकार   Brand Type : Registered Brand कैटलॉग की स्थिति   Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है   Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थांश   Category Name & Quadrant : Free standing PARTITION PANEL (Q3) मॉडल   Model: RM -60MP एचएसएन कोड   HSN Code: HSN not specified by seller	1,360	square foot	227	NA	308,720
कुल ऑर्डर मूल्य   Total Order Value (in INR)						308,720

परोक्ष विवरण   Consignee Detail						
क्र.सं.   S.No	परोक्षी   Consignee	वस्तु   Item	लॉट नंबर   Lot No.	मात्रा   Quantity	दिनांक के बाद डिलीवरी शुरू करना है   Delivery Start After	वितरण पूरा कब तक करना है   Delivery To Be Completed By
1	पद   Designation : Registrar ईमेल आईडी   Email ID : bineeshkr.ks@gov.in संपर्क   Contact : 011-26101583- जीएसटीआईएन   GSTIN : 07DELCO8254B1DZ पता   Address : WEST BLOCK NO. 2, R.K.PURAM, NEW DELHI, DELHI-110066, India	R&M MARKETING Free standing PARTITION PANEL Conformity to technical requirements	-	1,360	01-Mar-2024	15-Apr-2024

**Product Specification for R&M MARKETING Free standing PARTITION PANEL Conformity to technical requirements**

विनिर्देश   Specification	उप-विनिर्देश   Sub-Spec	मूल्य   Value
GENERIC	Product utility	For open plan office layout
	Elevation of Panels from ground (with legs) by	40 millimeter
	Panel thickness	52.4 mm (having cable management facility)
	Provisions for Panels to form any geometric configurations Hint : Panels can be connected together with various post connectors in many geometric configurations	Yes
	Panel structure Hint : Panels are supported on legs with levellers at various locations (depending on the layout requirements)	For 52.4 mm – 2 nos. Vertical trim + Horizontal trims (at every division of blocks/tiles) + Blocks (for intermediate panels) + 1 no. of fabricated bottom frame (welded structure) + bottom tiles + top tiles + 1 no. of top trim
	Additional requirement	N.A
MATERIAL	Vertical (uprights) and Horizontal trim made of Hint : Blocks and metal frame are held together by uprights at both ends of the panel and horizontals between each block and tile	Aluminium extrusions having material AL96063-T6 and average wall thickness of 1.2 mm and powder coated with epoxy-polyester powder
	Blocks made out of	Particle board with fabric (Fabric Block- 38 mm Honeycomb+ 3 mm MDF both side + 0.6 Fabric)
	Bottom frame (welded structure) comprises of	L – channels made of 2 mm thick CRCA conforming to IS 513 + formed plates of 3 mm thick Hot rolled steel conforming to IS 2062 and ERW steel tube of size 35 mm x 15 mm x 1.6 mm thick in oval cross section conforming to IS 7138 welded together and bolted to the uprights by screws
	Top and End trim made of	Aluminium extrusions
	End trim's cap made of	Aluminium casting
	Brackets made of	Full gable end bracket made from 1.2 mm thick MS CRCA grade D conforming to IS 513
	Bracket sizes/width	450 mm
	Panel legs (used for supporting panels) made of	Fabricated by CO2 welding 38 mm x 25 mm x 16 bg conforming to IS 7138
	Panel legs (single side) size for 52[dot]4 mm panel thickness (tolerances : +/- 10 mm) Hint : select 'NA' if single side panel legs (for 52[dot]4 mm panel thickness) not required	N.A
	Panel legs (double side) size for 52[dot]4 mm panel thickness (tolerances : +/- 10 mm) Hint : select 'NA' if double side panel legs (for 52[dot]4 mm panel thickness) not required	N.A
	Panel legs (double side) size for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : select 'NA' if double side panel legs (for 22[dot]8 mm panel thickness) not required	1100 mm
DIMENSIONS	Height of assembled panels - with legs including top trim and glide screws (tolerances : +/- 10 mm)	4 foot
	Width of assembled panels Hint : In pitch of 6 inches	2 foot
	Blocks for 52[dot]4 mm panel thickness Hint : these blocks are located in mid segment of the panels and can be provided with cut outs for mounting switch boxes (above or below the work tops)	Comprises of 38 mm thick paper honeycomb + 3 mm MDF on each sides + 0.6 mm decorative laminate on both sides – Particle board framing used on outer boundary of these blocks as well as intermediately at certain locations forming conduit for passing cables
	Top tiles finish for 52[dot]4 mm panel thickness Hint : These tiles are slide in to the panels from top before fixing the top horizontal and supported from top and bottom side with clips fitted in horizontal extrusion	Laminated tiles (9 mm to 9.5 mm thick pre-laminated particle board conforming to IS 12823 having all its edges with minimum 0.5 mm thick PVC edging)
	Height of Top tiles for 52[dot]4 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	260 mm (for panel height of 3 feet, 4 feet and 5 feet)
	Width of Top tiles for 52[dot]4 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	285 mm
	Split Top tiles for 52[dot]4 mm and 22[dot]8 mm panel thickness Hint : For two different finishes in single panels	Available
	Height of Split top tiles for 52[dot]4 mm and 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes (according to panel height) are including the fabric or edge banding thickness if applicable	260 mm (for panel height of 3 feet, 4 feet and 5 feet)
	Width of Split top tiles for 52[dot]4 mm and 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	290 mm

PANEL COMPONENTS	Bottom tiles finish for 52[dot]4 mm panel thickness Hint : Bottom tiles are press fitted on to the assembly frame of the panel with the help of snap on clips – Switches can be mounted on these bottom tiles as per buyer's requirement	Post-laminated tiles
	Height of Bottom tiles for 52[dot]4 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	265 mm
	Width of Bottom tiles for 52[dot]4 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	280 mm
	Bottom Blocks for 22[dot]8 mm panel thickness	N.A
	Height of Bottom Blocks for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	260 mm
	Width of Bottom Blocks for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	285 mm
	Intermediate Blocks for 22[dot]8 mm panel thickness	N.A
	Height of Intermediate Blocks for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	N.A
	Width of Intermediate Blocks for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	285 mm
	Top Blocks for 22[dot]8 mm panel thickness	Laminate finish (made from 18 mm thick particle board)
	Height of Top Blocks for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	260 mm
	Width of Top Blocks for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	285 mm
	End panel 22[dot]8 mm (off module fixing) Hint : used to connect 22[dot]8 mm panel and 52[dot]4 mm panel at the centre of 22[dot]8 mm panel	Not available
	Height of End panel 22[dot]8 mm (tolerances : +/- 10 mm) Hint : This can be used in aisle conditions only	1200 mm
	Width of End panel 22[dot]8 mm (tolerances : +/- 10 mm) Hint : This can be used in aisle conditions only	N.A
	Bottom screen of end panel 22[dot]8 mm (off module fixing)	N.A
	Top screen of end panel 22[decimal]8 mm (off module fixing)	Laminate finish blocks (made from 18 mm thick particle board)
	Panel joinery / Posts (22[decimal]8 mm panels cannot be interconnected – these are joined as fin panels to 52[decimal]4 mm panels only using fin posts) Hint : panel can be joined to each other directly with 180 degree joinery or with help of post to	Single side middle fin - for connecting 22.8 mm panels as fins with 52.4 mm on spine
Stability post – according to unit height - to avoid movement of free standing panels (tolerances : +/- 10 mm) Hint : End trim fixing is not required alongwith stability post	1200 mm (for 4 feet unit height)	
WARRANTY	Warranty period in number of years	1
CERTIFICATION	Test reports to be furnished to buyer's on demand	1. Yes
	OEM of offered product is ISO 9001:2015 certified	Yes
	OEM of offered product is ISO 14001:2015 certified	No
	OEM of offered product is ISO 18001:2007/45001:2018 certified	No
<p><b>टिप्पणी   Note::</b> Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.</p>		
<p><b>ईपीबीजी विवरण   ePBG Detail</b></p>		
<p>NA</p>		

## नियम और शर्तें | Terms and Conditions

### 1. General Terms and Conditions-

1.1 This contract is governed by the [General Terms and Conditions](#), conditions stipulated to this Product/Service as provided in the Marketplace.

1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.