

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687754000961

अनुबंध तिथि | Generated Date : 01-Mar-2024

संगठन विवरण Organisation Details	खरीदार विवरण Buyer Details
प्ररूप Type : State Government	पद Designation : Gramsevak
मंत्रालय Ministry : -	संपर्क नंबर Contact No. : 02344-246404-
विभाग Department : Rural Development Department	ईमेल आईडी Email ID : buycon795.zps.mh@gembuyer.in
संगठन का नाम Organisation Name : ZILLA PARISHAD SANGLI	जीएसटीआईएन GSTIN : -
कार्यालय क्षेत्र Office Zone : Jath panchayat Samiti	पता Address : Grampanchayat Avandhi Tal Jath, SANGLI, MAHARASHTRA-416404, India

वित्तीय स्वीकृति विवरण Financial Approval Detail	भुगतान प्राधिकरण विवरण Paying Authority Details
आईएफडी सहमति IFD Concurrence : No	Role: PAO
प्रशासनिक अनुमोदन का पदनाम Designation of Administrative Approval: SARPANCH AND GRAMSEVAK GP - AVANDHI	भुगतान का तरीका Payment Mode: Offline
वित्तीय अनुमोदन का पदनाम Designation of Financial Approval: SARPANCH AND GRAMSEVAK GP - AVANDHI	पद Designation : Sarapanch
	ईमेल आईडी Email ID : pao1439.zps.mh@gembuyer.in
	जीएसटीआईएन GSTIN : -
	पता Address: Grampanchayat Avandhi Tal Jath, Sangli, MAHARASHTRA-416404, India

विक्रेता विवरण Seller Details
जेम विक्रेता आईडी GeM Seller ID : LI0B220006879345
कंपनी का नाम Company Name : shreenath traders
संपर्क नंबर Contact No. : 07972741903
ईमेल आईडी Email ID : poojamundhe2244@gmail.com
पता Address : G.NO.06/A,FADTARWADI,MUNDHEWADI,POST- JIHE ,FADTARWADI,SATARA,MAHARASHTRA,415004,POST- JIHE ,FADTARWADI,SATARA,MAHARASHTRA,415004, SATARA, MAHARASHTRA-415004, India
एमएसएमई पंजीकरण संख्या MSME Registration number : UDYAM-MH-30-0048907
एमएसई सामाजिक श्रेणी MSE Social Category : OBC
एमएसई लिंग श्रेणी MSE Gender : Female
जीएसटीआईएन GSTIN: 27HNJPM8453G1ZF

*जिसके नाम के पक्ष में GST/TAX इनवाइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Consignee

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण Product Details						
#	आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : Unbranded Yes WLed Luminaire Light ब्रांड Brand : NA ब्रांड प्रकार Brand Type : Unbranded कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : LED Luminaire (for Road and Street Lights) as per IS 10322, IS 16107, IS 16108, IS 16103, IS 10322 (Q3) मॉडल Model: S2225-PREMIUM SERIES एचएसएन कोड HSN Code: HSN not specified by seller	50	pieces	415	NA	20,750
कुल ऑर्डर मूल्य Total Order Value (in INR)						20,750

परेषिती विवरण Consignee Detail						
क्र.सं. S.No	परेषिती Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिलोके के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा कब तक करना है Delivery To Be Completed By
	पद Designation : Gramsevak ईमेल आईडी Email ID : buycon795.zps.mh@gembuyer.in संपर्क Contact : 02344-246404-	Unbranded Yes WLed				

1	जीएसटीआईएन GSTIN : - पता Address : Grampanchayat Avandhi Tal Jath, SANGLI, MAHARASHTRA-416404, India	Luminaire Light	-	50	01-Mar-2024	16-Mar-2024
Product Specification for Unbranded Yes WLed Luminaire Light						
	विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value			
STANDARDS		LED Luminaire conformity to IS:10322/Part 5/Section 3/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest	Yes			
		Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes			
		Types of LED Luminaire as per the IS: 16107(Part-2/ Sec.-1)/2012	Type B			
		Types of LED Modules as per the IS:IS: 16103(Part-2)/2012	Type 3			
		LED Rating (in Watts)/System Wattage/Rated Power	18W			
		Luminaire System Efficacy (Lumen/watt)	>= 100 Lm/Watt			
		Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP65			
		Warranty for free replacement (in years)	2			
ELECTRICAL EFFICIENCY		Input operating Voltage range and frequency	90 to 300 Volts AC at 50 Hz+/-2			
		Automatic Higher Cut off voltage above 300 volt	Yes			
		Rated voltage	230 V AC 50 Hz			
		AC Power Factor at full load	≥ 0.95			
		Driver Efficiency (in %age) Upto 100W: ≥85%, Above 100W: >/=90%	Yes			
		Total Harmonics Distortion	≤ 10			
		"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer (as per Cl. 8 of IS:16104:2012 lates)"	Yes			
OPTICAL		LED chip Efficacy	≥130 Lm/Watt			
		Colour temperature	6000+/-500K			
		Working life for LED (Minimum 50,000 burning hours as per LM-80 and LM 21 reports)	Yes			
		Colour Rendering Index(CRI)	≥70			
		LED Beam Angle	≥120			
		Optic lense materal (UV stabilised)	Poly carbonate lense			
THERMAL MANAGEMENT		Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes			
		Junctiojn / Soldering point temperature shall not exceed 85 deg.c as per LM 80 report	Yes			
		Capacitor shall be rated for a temperature of 105 deg. celsius or better	Yes			
		Operating temperature range	-20 deg. C to +50 deg. C			
		Operating Humidity Range	10 % to 95% RH			
PROTECTION		Short circuit Protection	Yes			
		Over load protecton	Yes			
		Over Voltage protection	Yes			
		Reverse polarity	Yes			
		High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes			
		Insulation resistance between earth and current carrying part	>100 M Ohm			
		The luminaire shall be protected against surges and transients (Internal)	>/=4KV			
		The luminaire shall be protected against surges and transients of >/=10KV (External)	Yes			
		The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity	Yes			
		The luminaire body must be corrosion resistant powder coated	Yes			
		All fastners must be of stainless steel	Yes			
		Protection of the entire housing (both LED section and driver section) as per IS:10322 (Part 1):1982 latest	IP66			
		Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes			
		Luminaries light transparency should be of Toughened glass	Yes			

CONSTRUCTIONAL	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degradation due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	2 Nos.
	Light Source	SMD LED Chip as per LM 80/IS16106
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	100 cm
MARKING	"Manufactures Name and and brand on the aluminium die cast body "	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
	Diameter of pole Luminiare suitable for: (upto 45W Pole OD: shall be 40mm), (>45W<120W Pole OD: Shall be 50 mm), (above 120W: OD shall be 60 mm for which luminiare is suitable	Yes
Reports And Certifications	LED Make	OSRAM / NICHIA / CREE / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish to the buyer / consignee on demand)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer / consignee on demand (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,	Yes
	LM 80 & TM 21 (Ref. IS:16105:2012) Report and Photo biological report for LED report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer / consignee on demand (LM-80 report shall have the Pohoto Biological re	Yes
	Availability of test Report from Central Government Lab /NABL/ILAC accredited lab to Indian Standrad IS:10322/part 5/sec-3/2012 and IS 16107 (Part 2/Sec 1) : 2012	Yes
	Seller shall furnish the Type test reports to the buyer / consignee on demand	Yes
	DC or AC supplied electronic control gear for LED Module shall comply as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for road and street lighting shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 3): 2012 as applicable on date	Yes
<p>टिप्पणी Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.</p>		
<p>ईपीबीजी विवरण ePBG Detail</p>		
<p>NA</p>		
<p>नियम और शर्तें Terms and Conditions</p>		
<p>1. General Terms and Conditions-</p>		
<p>1.1 This contract is governed by the General Terms and Conditions, conditions stipulated to this Product/Service as provided in the Marketplace.</p>		
<p>1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable</p>		
<p>नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।</p>		
<p>Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.</p>		

