

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687752309631

अनुबंध तिथि | Generated Date : 02-Mar-2024

संगठन विवरण Organisation Details		खरीदार विवरण Buyer Details	
प्ररूप Type :	State Autonomous	पद Designation :	GENDER
मंत्रालय Ministry :	-	संपर्क नंबर Contact No. :	-
विभाग Department :	Education Department Gujarat	ईमेल आईडी Email ID :	buycon354.ssas.gj@gembuyer.in
संगठन का नाम Organisation Name :	Sarva Shiksha Abhiyan (SSA)	जीएसटीआईएन GSTIN :	-
कार्यालय क्षेत्र Office Zone:	DISTRICT PROJECT CO ORDINATOR OFFICE SURAT	पता Address :	Samagra Shiksha, School NO 19/20, 2nd Floor, Opp Dutch Garden, Nanpura, Surat, SURAT, GUJARAT-395001, India

वित्तीय स्वीकृति विवरण Financial Approval Detail		भुगतान प्राधिकरण विवरण Paying Authority Details	
आईएफडी सहमति IFD Concurrence :	No	Role:	BUYER
प्रशासनिक अनुमोदन का पदनाम	DPC	भुगतान का तरीका	Offline
Designation of Administrative Approval:		Payment Mode:	
वित्तीय अनुमोदन का पदनाम	DAO	पद Designation :	GENDER
Designation of Financial Approval :		ईमेल आईडी Email ID :	buycon354.ssas.gj@gembuyer.in
		जीएसटीआईएन GSTIN :	24SRTD03708F1DQ
		पता Address:	Samagra Shiksha, School NO 19/20, 2nd Floor, Opp Dutch Garden, Nanpura, Surat, Surat, GUJARAT-395001, India

विक्रेता विवरण Seller Details	
जेम विक्रेता आईडी GeM Seller ID :	O1LW210002902345
कंपनी का नाम Company Name :	JHANVI INTERNATIONAL
संपर्क नंबर Contact No. :	09925023252
ईमेल आईडी Email ID :	jhanviinternational98@gmail.com
पता Address :	7, E-704,AASHIRWAD AVENUE,VIP ROAD,ALTHAN, Surat, GUJARAT-395017, -
एमएसएमई पंजीकरण संख्या MSME Registration number :	-
जीएसटीआईएन GSTIN:	24AQGPG2291K1ZU

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Buyer

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण | Product Details

#	आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : nete Sanitary Napkins Incinetator Machine with Smoke Control Unit ब्रांड Brand : nete ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्भूति Category Name & Quadrant : Sanitary Napkins Incinetator Machine with Smoke Control Unit (Q3) मॉडल Model: NETEMJP एचएसएन कोड HSN Code: HSN not specified by seller	4	pieces	53,100	NA	212,400

कुल ऑर्डर मूल्य | Total Order Value (in INR) 212,400

परेष्ठी विवरण | Consignee Detail

क्र.सं. S.No	परेष्ठी Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा कब तक करना है Delivery To Be Completed By
	पद Designation : GENDER ईमेल आईडी Email ID : buycon354.ssas.gj@gembuyer.in संपर्क Contact : -	nete Sanitary Napkins				

1	जीएसटीआईएन GSTIN :- पता Address : Samagra Shiksha, School NO 19/20, 2nd Floor, Opp Dutch Garden, Nanpura, Surat, SURAT, GUJARAT-395001, India	Incinerator Machine with Smoke Control Unit	-	4	02-Mar-2024	17-Mar-2024
---	--	---	---	---	-------------	-------------

Product Specification for nete Sanitary Napkins Incinerator Machine with Smoke Control Unit

विवरण Specification	उप-विवरण Sub-Spec	मूल्य Value
GENERAL	Type	Wall Mountable
	Purpose	Burn used Sanitary Napkins to sterile ash and stop automatically
	Color	Blue
	Operation Mode	Electronically operated, fully Automatic
	Loading Type	Front loading
	Stand provided	No
	Number of chambers	NA
	Trap Door available	Yes
	All MS parts Powder coated	Yes
	Spare parts should be available for Minimum 5 years from date of supply	Yes
DIMENSIONS OF MAIN UNIT	All electrical parts are ISI Marked	Yes
	Thickness of thermal Insulation material (mm)	25 millimeter
	Thickness of MS/SS sheet of housing cabinet (external) (mm)	1.2 millimeter
	Thickness of MS/SS sheet of burning chamber (internal) (mm) (Min)	3 millimeter
	Machine Width(mm)	701-900
	Machine Depth (mm)	701-900
	Machine Height(mm)	901-1200
	Machine Weight(kg)	51-250
	Door width(mm)	151-200
	Door height(mm)	101-150
	Thickness of door including insulation (mm)	25 millimeter
	Internal/burning chamber shape	Rectangular cubical
	Flexible emission Outlet pipe dia (mm)	40 millimeter
	Detachable ash tray length (mm)	301-400
	Detachable ash tray width (mm)	151-200
	Detachable ash tray height (mm)	31-50
MATERIAL OF MACHINE UNIT	Stand Height (mm)	0 millimeter
	Stand Width (mm)	NA for wall mountable
	Stand Depth (mm)	NA for wall mountable
	Material of Housing cabinet (External)	Mild Steel(CRCA) sheet
CONSTRUCTIONAL FEATURES	Material of Burning chamber (Internal)	Mild Steel(CRCA) sheet
	Finish of MS parts of cabinet	Epoxy anti rust proof painting for superior finish
	Material of Thermal Insulation	High Density Ceramic Fiber sheet
	Thermal insulation of burning chamber housed in outer chamber	Yes
	Burning Chamber tray provided	Yes
	Emission Outlet pipe location	Top of machine
	Means of connecting the unit outlet with flue gas emission pipe	Clamped
	Type of door lock provided	Magnetic lock
	Temperature indicator provided	Yes
	Timer provided	Yes

CONTROL & FUNCTIONAL FEATURES	Auto cut-off temperature display	Yes
	Digital display to see actual and set temperature	Yes
	Minimum Burning temperature (degree C)	800
	Burning Capacity per day (Number of Napkins)	200-500
	Burning Capacity at a time (Number of Napkins)	1-15
	Residue Ash per Napkin (gms)	2 gram
	Burning time of full capacity Napkins/pads (minutes) (Max)	30 minute
	Skin temperature of the unit under operation (deg C)	16-20
	Installation, training, demonstration and plumbing included	Yes
ELECTRICAL AND SAFETY FEATURES	Automatic digital controller for time	Yes
	Automatic digital controller for temperature	Yes
	Equipment ON/OFF indicator provided	Yes
	Power supply	230v +/-10%, 50Hz, Single phase, AC supply
	Electrical Power Consumption(Watt)	1501-3000
	Minimum length of power chord to be supplied along with machine (mtr)	2 meter
	Type of Heater	Ceramic heater containing coil
	Power saver (auto power cut-off)	Yes
	Safety MCB provided (16A to 30A)	Yes
	Protection against electric shock when checked as per IS:302-1/2008	Yes
	Minimum Insulation Resistance (IR) at 500 VDC (Mega Ohm)	2
	Maximum Electrical Insulation and Leakage current as per IS:302-1/2008, (mA)	0.21
	Maximum Earthing continuity test when tested as per IS:302-1/2008 (Ohm)	0.1
	HV test at 1000 V rms for 1 Sec when tested as per IS:302-1/2008	No breakdown shall occur during the test
SMOKE CONTROL UNIT (SCU)	Type of SCU (Smoke Control Unit)	Top mounted
	Material of housing of Smoke Control Unit (SCU)	Mild Steel(CRCA) cabinet
	Finish of MS parts of SCU cabinet	Epoxy anti rust proof painting for superior finish
	Overall height of SCU (mm)	325
	Overall width of SCU (mm)	501-800
	Overall depth of SCU (mm)	301-500
	Number of chambers for filtration of smoke emission	Not required
	Both carbon Control and Foul odour Control Chambers for filtration of smoke emission	Not Required
	Number of filters in Carbon control chamber	Not Required
	Type of filters in Carbon control chamber	Not Required
	Number of filters in Odour control chamber	Not Required
	Type of filters in Odour control chamber	Not Required
	Blower type	NA
	Blower RPM	1800
	Power supply of SCU	230v +/-10%, 50Hz, Single phase, AC supply
	Minimum length of flexible emission outlet pipe to be supplied along with machine (mtr)	3
	Cost of additional flexible emission outlet pipe, if required on actuals to be paid by the user	Yes
ENVIRONMENTAL FEATURES	Conformity to CPCB, Min of Environment & Forests standard, Solid Waste Management Rules (SWM), 2016	Yes
	Particulates (Half hourly average) (mg/Nm3) (Max)	50
	HCl (Half hourly average) (mg/Nm3) (Max)	50
	SO2 (Half hourly average) (mg/Nm3) (max)	200
	CO (Half hourly average) (mg/Nm3) (Max)	100

EMISSION STANDARD FOR SMOKE	CO (Daily average) (mg/Nm3) (Max)	50
	Total Organic Carbon (Half hourly average) (mg/Nm3) (Max)	20
	HF (Half hourly average) (mg/Nm3) (Max)	4
	"Nox (NO and NO2 expressed as NO2) (Half hourly average) (mg/Nm3) (Max)"	400
	Total dioxins and furans (6 to 8 hours sampling basis, Please refer guidelines for 17 concerned congeners for toxic equivalence values to arrive at total toxic equivalence) (ng TEQ/Nm3) (Max)	0.1
	Cd + Th + their compounds (Sampling time anywhere between 30 minutes and 8 hours) (mg/Nm3) (Max)	0.05
	Hg and its compounds (Sampling time anywhere between 30 minutes and 8 hours) (mg/Nm3) (Max)	0.05
	Sb+As+Pb+Cr+Co+Cu+Mn+Ni+V+their compounds (Sampling time anywhere between 30 minutes and 8 hours) (mg/Nm3) (Max)	0.5
	Loss on ignition (max) (% dry weight of the material)	5
PACKING	Packing	Carton Box
MARKING AND INSTRUCTIONS	The appliance is marked as per IS:302-1/2008	Yes
CERTIFICATION	Submission of Test Report from Central Govt/CSIR Lab/NABL/ILAC accredited Lab specifically containing Electrical & Electronic parameters, Thermal insulation material of burning chamber in addition to declared specification parameter at time of supply	Yes
	Submission Test Report for equipment for compliance of Flue gas emission and ash upon combustion of Sanitary Napkins/Pads to Central Pollution Control Board (CPCB) norms from NABL accredited lab/CSIR Lab at the time of supply	Yes
	Certification Available	Other
	Certificate for Manufacturing premises available	ISO
	Compliance certificate is to be furnished after conducting comprehensive performance test by the supplier	Yes
PERFORMANCE REQUIREMENTS	Submission of all the certifications to the buyer along with supplies	Yes
	Warranty in Years (Option of comprehensive warranty is available through bidding only, which if opted will supersede normal warranty in the catalogue)	1

टिप्पणी| Note: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

ईपीबीजी विवरण | ePBG Detail

NA

नियम और शर्तें| Terms and Conditions

1. Special terms and conditions- Version:2 effective from 03-11-2023

1.1.1. Comprehensive warranty:

Comprehensive warranty shall include preventive maintenance including calibration as per technical/ service /operational manual of the manufacturer, service charges and spares. During the warranty period commencing from date of the successful completion of warranty period, Service personnel shall visit each consignee site as recommended in the manufacturer♦♦♦s technical/ service /operational manual, at least once in six months. warranty shall not be including the consumables .Further there will be 98% uptime warranty during warranty period on 24 (hrs) X 7 (days) X 365 (days) basis, with penalty, to extend warranty period by double the downtime period.

2. Service centres:

Details of Service outlets in India to render services for equipment to be furnished to buyer/consignees with complete address ,telephone numbers, e mails etc at time of making the supplies .It shall be the responsibility of seller to ensure that authorized service centres are available to cater to the areas where supplies are made within reasonable distance from where the service calls can be handled. Details of toll free numbers for service call and online registration of service requests also to be provided buyer/consignee at the time of supplies.

3. Source of supply:

It shall be responsibility of seller to provide Documents regarding source of equipments such as copy of Performa invoice or any other documents to establish that the products supplied are manufactured by OEM indicated and sourced from them.

4. Packing and Marking:

Medical equipments being very delicate and sensitive packing for the goods should be strong and durable enough to withstand transit including transhipment (if any), rough handling, open storage etc. without any damage, deterioration etc. .The size, weights and volumes of the packing cases, remoteness of the final destination of the goods, availability or otherwise of transport and handling facilities at all points during transit up to final destination. Quality of packing, the manner of marking within & outside the packages and provision of accompanying documentation shall take in to consideration the type of medical equipments being supplied. The accessories shall be suitably labelled and packed .Each of the package shall be marked on three sides with indelible paint of proper quality: indicating contract number and date , brief description of goods including quantity , Packing list reference number , country of origin of goods and any other relevant details.

5. Spare Parts:

Seller shall provide materials, information etc. pertaining to spare parts manufactured and supplied by the OEM . It shall be ensured that the required spares are available for

purchase at least for 10 years from date of supplies .In case due to any reasons the production of the spare parts is discontinued sufficient advance notice should be given to the buyer/consignee before such discontinuation to provide adequate time to purchase the required spare parts etc. Further, OEM and their service centres/dealers shall carry sufficient inventories to assure ex-stock supply of consumables and spares for the equipments so that the same are available.

OEM or reseller shall always accord most favoured client status to the buyer/consignee and shall give the most competitive price for spares and consumables of its machines/equipments supplied

6. Installation, Training, Manuals:

Seller shall be responsible to carry out Installation & commissioning, Supervision and Demonstration of the goods. They shall provide required jigs and tools for assembly, minor civil works for the completion of the installation and Training of Consignee's representatives for operating and maintaining the equipment and Supplying required number of operation & maintenance manual for the goods. In case the category parameters are specifying any requirements regarding the installations , training and manuals the same shall also be applicable.

7. Electrical safety checking:

Sellers are required to make sure that they furnish the list of equipments for carrying out routine and preventive maintenance to buyer/consignee .They should make sure to periodically check the electrical safety aspects as per BIS Safety Standards or equivalent .In case they do not have required equipment for such testing should ensure that the equipments checked for electrical safety compliance through labs with facilities for such checking during every preventive maintenance call.

8. Software:

All software updates should be provided free of cost during warranty period.

2. General Terms and Conditions-

2.1 This contract is governed by the [General Terms and Conditions](#), conditions stipulated to this Product/Service as provided in the Marketplace.

2.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.