

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687773900432

अनुबंध तिथि | Generated Date : 13-Mar-2024

बोली/आरए/पीबीपी संख्या | Bid/RA/PBP No.: [GEM/2023/B/4381528](#)

संगठन विवरण Organisation Details	खरीदार विवरण Buyer Details
प्रकार Type : Central PSU मंत्रालय Ministry : Ministry of Coal विभाग Department : Materials Management संगठन का नाम Organisation Name : Central Coalfields Limited कार्यालय क्षेत्र Office Zone: Central Coalfields Limited	पद Designation : Debapriya Roy संपर्क नंबर Contact No. : - ईमेल आईडी Email ID : debapriya.roy@nic.in जीएसटीआईएन GSTIN : 20AAACC7476RHZT पता Address : Regional Stores Piparwar P. O. Bachra District. Chatra, CHATRA, JHARKHAND-829201, India

वित्तीय स्वीकृति विवरण Financial Approval Detail	भुगतान प्राधिकरण विवरण Paying Authority Details
आईएफडी सहमति IFD No Concurrence : प्रशासनिक अनुमोदन का पदनाम Designation General Manager, Piparwar Area of Administrative Approval: वित्तीय अनुमोदन का पदनाम Designation of Financial Approval : Budget No. AFM/PPR/23-24/RB/GMU/18/62 DATED 13.03.2024/Amount: Rs. 15,77,480.00/Profit center :CCL3122/COMMITMENT ITEM:CONSUMPTION-OTHRCONSUMABLES/GL Account:40000061/For Fund purpose only	Role: PAO भुगतान का तरीका Payment Mode: Offline पद Designation : Area Finance Manager Piparwar CCL ईमेल आईडी Email ID : s.kumar6950@nic.in जीएसटीआईएन GSTIN : 20AAACC7476RHZT पता Address: GM Office Piparwar P.O. Bachra District Chatra, Chatra, JHARKHAND-829201, India भुगतान समयसीमा Payment Timelines: Payments shall be made to the seller within 21 days of issue of consignee receipt-cum-acceptance certificate (CRAC) and on-line submission of bills (This is in supersession of 10-days time as provided in clause 12 of GeM GTC)

विक्रेता विवरण Seller Details
जेम विक्रेता आईडी GeM Seller ID : 895A180000100878 कंपनी का नाम Company Name : GLYNC TECH PRIVATE LIMITED संपर्क नंबर Contact No. : 09910009981 ईमेल आईडी Email ID : prashar.raahul@gmail.com पता Address : B-1/A-26, MOHAN CO-OPERATIVE INDS. ESTATE, MATHURA ROAD, BADARPUR, NEW DELHI, DELHI-110044, - एमआईआई स्थिति MII Status : True एमएसएमई सत्यापित MSME verified : Yes एमएसएमई पंजीकरण संख्या MSME Registration number : UDYAM-DL-09-0002780 एमएसई सामाजिक श्रेणी MSE Social Category : General एमएसई लिंग श्रेणी MSE Gender : Male जीएसटीआईएन GSTIN: 07AAGCG0244D1Z4

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Consignee

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण Product Details						
#	आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : GLYNC 300W LED Luminaire For Flood Light ब्रांड Brand : GLYNC ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: OEM verified catalogue कैसे बेचा जा रहा है Selling As : OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : LED Luminaire (for Flood Light) as per IS 10322, IS 16107 (Q3) मॉडल Model: GLYNC-TIN300 एचएसएन कोड HSN Code: 94054090	227	pieces	3,445	NA	782,015
2	उत्पाद का नाम Product Name : GLYNC 200W LED Luminaire For Flood Light ब्रांड Brand : GLYNC ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: OEM verified catalogue कैसे बेचा जा रहा है Selling As : OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : LED Luminaire (for Flood Light) as per IS 10322, IS 16107 (Q3)	80	pieces	1,992	NA	159,360

मॉडल Model: GLYNC-TIN200 एचएसएन कोड HSN Code: 94054090						
3	उत्पाद का नाम Product Name : GLYNC 100W LED Luminaire For Flood Light ब्रांड Brand : GLYNC ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: OEM verified catalogue कैसे बेचा जा रहा है Selling As : OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : LED Luminaire (for Flood Light) as per IS 10322, IS 16107 (Q3) मॉडल Model: GLYNC-TIN100 एचएसएन कोड HSN Code: 94054090	45	pieces	1,254	NA	56,430
कुल ऑर्डर मूल्य Total Order Value (in INR)						997,805
परोक्षिती विवरण Consignee Detail						
क्र.सं. S.No	परोक्षिती Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा कब तक करना है Delivery To Be Completed By
1	पद Designation : - ईमेल आईडी Email ID : debapriya.roy@nic.in संपर्क Contact : - जीएसटीआईएन GSTIN : 20AAACC7476RHZT पता Address : Regional Stores Piparwar P. O. Bachra District. Chatra, CHATRA, JHARKHAND-829201, India	GLYNC 300W LED Luminaire For Flood Light	-	227	13-Mar-2024	11-Jun-2024
		GLYNC 200W LED Luminaire For Flood Light	-	80	13-Mar-2024	11-Jun-2024
		GLYNC 100W LED Luminaire For Flood Light	-	45	13-Mar-2024	11-Jun-2024
Product Specification for GLYNC 300W LED Luminaire For Flood Light						
विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value				
STANDARDS	LED Luminaire conformity to IS:10322/Part 5/Section 5/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest	Yes				
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes				
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec.-1)/2012	Type B				
	Types of LED Modules as per the IS: 16103(Part-2)/2012	Type 3				
	LED Rating/System Wattage/Rated Power	300W				
	Luminaire System Efficacy (Lumen/watt)	>/= 100 Lm/Watt				
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP66				
	Mounting brackets (included)	Adjustable				
	Warranty for free replacement (in Years)	3				
ELECTRICAL EFFICIENCY	Input operating Voltage range and frequency	90 to 300 V olts AC at 50 Hz+/-2 Hz				
	Automatic Higher Cut off voltage above 300 volt	Yes				
	Rated voltage	230 V AC 50 Hz				
	AC Power Factor at full load	≥ 0.95				
	Driver Efficiency (in %age)	≥85				
	Total Harmonics Distortion (in %age)	≤ 10				
	"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer"	Yes				
OPTICAL	LED chip Efficacy	≥130 Lm/Watt				
	Colour temperature (+/-500K)	6000K				
	Working life for LED (Minimum 50,000 burning hours as per LM-80 report)	Yes				
	Colour Rendering Index(CRI)	≥70				
	Beam Angle	≥120				
	Optic lense materal (UV stabilised) (Write NA for without optic lense supply)	Poly carbonate lense				
	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes				
	Capacitor shall be rated for a temperature of 105 deg. celsius or better	Yes				

THERMAL MANAGEMENT	Junction temperature	< 85 degC
	Operating temperature range	-20 deg C to +50 deg C
	Operating Humidity Range	10 % to 95% RH
PROTECTION	Short circuit Protection	Yes
	Over load protecton	Yes
	Over Voltage protection	Yes
	Reverse polarity	Yes
	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes
	Insulation resistance between earth and current carrying part	>100 M ohm
	The luminaire shall be protected against surges and transients (Internal)	>/=5KV
	The luminaire shall be protected against surges and transients of >/=10KV (External)	Yes
CONSTRUCTIONAL	The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity	Yes
	The luminaire body must be corrosion resistant epoxy powder coated	Yes
	All fastners must be of stainless steel	Yes
	The entire housing (both LED section and driver section) shall be dust and water proof having IP 66 protection as per IS:10322 (Part 1):1982 latest	Yes
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes
	Luminaries light transparency should be of Toughened glass	Yes
	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degraation due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	2 Nos.
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	50 cm
Light Source	SMD LED Chip as per LM 80/IS16106	
MARKING	"Manufactures Name and and brand on the aluminium die cast body	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
REPORTS AND CERTIFICATIONS	LED Make	OSRAM / NICHIA/CREE / SAMSUNG / SEOUL / LUMILED / PHILIPS / EDISON / SYSKA / LUMENMAX / EVERLIGHT / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish on demand by buyer/consignee)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government lab/NABL/ILAC accredited lab. Reports shall be furnish on demany by buyer (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,)	Yes
	LM 80 & TM 21 (Part of LM 80) (Ref. IS:16105:2012) Reports and Photo biological report for LED report from Central Government lab /NABL/ILAC accredited lab. Reports shall be furnish on demany by buyer (LM-80 report shall haveand the Pohoto Biological report of the LED Chip being used in the luminaire)	Yes
	Availability of test Report from Central Government lab/NABL/ILAC accredited lab to Indian Standrad IS:10322/part 5/sec-5/2012 and IS 16107 (Part 2/Sec 1) : 2012	Yes
	Seller has to furnish Type test report on demand by buyer/consignee	Yes
	DC or AC supplied electronic control gear for LED Module shall complpy as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for Flood Light shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 5): 2012 as applicable on the date	Yes

Product Specification for GLYNC 200W LED Luminaire For Flood Light

विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
STANDARDS	LED Luminaire conformity to IS:10322/Part 5/Section 5/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest	Yes
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec.-1)/2012	Type B
	Types of LED Modules as per the IS: 16103(Part-2)/2012	Type 3
	LED Rating/System Wattage/Rated Power	200W
	Luminaire System Efficacy (Lumen/watt)	>= 100 Lm/Watt
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP66
	Mounting brackets (included)	Adjustable
	Warranty for free replacement (in Years)	3
ELECTRICAL EFFICIENCY	Input operating Voltage range and frequency	90 to 300 V olts AC at 50 Hz+/-2 Hz
	Automatic Higher Cut off voltage above 300 volt	Yes
	Rated voltage	230 V AC 50 Hz
	AC Power Factor at full load	≥ 0.95
	Driver Efficiency (in %age)	≥85
	Total Harmonics Distortion (in %age)	≤ 10
	"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer"	Yes
OPTICAL	LED chip Efficacy	≥130 Lm/Watt
	Colour temperature (+/-500K)	6000K
	Working life for LED (Minimum 50,000 burning hours as per LM-80 report)	Yes
	Colour Rendering Index(CRI)	≥70
	Beam Angle	≥120
	Optic lense material (UV stabilised) (Write NA for without optic lense supply)	Poly carbonate lense
THERMAL MANAGEMENT	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes
	Capacitor shall be rated for a temperature of 105 deg. celsius or better	Yes
	Junction temperature	< 85 degC
	Operating temperature range	-20 deg C to +50 deg C
	Operating Humidity Range	10 % to 95% RH
PROTECTION	Short circuit Protection	Yes
	Over load protecton	Yes
	Over Voltage protection	Yes
	Reverse polarity	Yes
	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes
	Insulation resistance between earth and current carrying part	>100 M ohm
	The luminaire shall be protected against surges and transients (Internal)	>/=5KV
	The luminaire shall be protected against surges and transients of >/=10KV (External)	Yes
CONSTRUCTIONAL	The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity	Yes
	The luminaire body must be corrosion resistant epoxy powder coated	Yes
	All fastners must be of stainless steel	Yes
	The entire housing (both LED section and driver section) shall be dust and water proof having IP 66 protection as per IS:10322 (Part 1):1982 latest	Yes
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes
	Luminaries light transparency should be of Toughened glass	Yes
	Toughned transparent glass cover thickness	>/=4 mm

	Toughned Glass shall not get discoloured shall not suffer degradation due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	3 Nos.
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	50 cm
	Light Source	SMD LED Chip as per LM 80/IS16106
MARKING	"Manufactures Name and and brand on the aluminium die cast body	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
REPORTS AND CERTIFICATIONS	LED Make	OSRAM / NICHIA/CREE / SAMSUNG / SEOUL / LUMILED / PHILIPS / EDISON / SYSKA / LUMENMAX / EVERLIGHT / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish on demand by buyer/consignee)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government lab/NABL/ILAC accredited lab. Reports shall be furnish on demany by buyer (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,)	Yes
	LM 80 & TM 21 (Part of LM 80) (Ref. IS:16105:2012) Reports and Photo biological report for LED report from Central Government lab /NABL/ILAC accredited lab. Reports shall be furnish on demany by buyer (LM-80 report shall haveand the Pohoto Biological report of the LED Chip being used in the luminaire)	Yes
	Availability of test Report from Central Government lab/NABL/ILAC accredited lab to Indian Standrad IS:10322/part 5/sec-5/2012 and IS 16107 (Part 2/Sec 1) : 2012	Yes
	Seller has to furnish Type test report on demand by buyer/consignee	Yes
	DC or AC supplied electronic control gear for LED Module shall complpy as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for Flood Light shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 5): 2012 as applicable on the date	Yes
Product Specification for GLYNC 100W LED Luminaire For Flood Light		
विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
STANDARDS	LED Luminaire conformity to IS:10322/Part 5/Section 5/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest	Yes
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec.-1)/2012	Type B
	Types of LED Modules as per the IS: 16103(Part-2)/2012	Type 3
	LED Rating/System Wattage/Rated Power	100W
	Luminaire System Efficacy (Lumen/watt)	>= 100 Lm/Watt
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP66
	Mounting brackets (included)	Adjustable
	Warranty for free replacement (in Years)	3
ELECTRICAL EFFICIENCY	Input operating Voltage range and frequency	90 to 300 V olts AC at 50 Hz+/-2 Hz
	Automatic Higher Cut off voltage above 300 volt	Yes
	Rated voltage	230 V AC 50 Hz
	AC Power Factor at full load	≥ 0.95
	Driver Efficiency (in %age)	≥85
	Total Harmonics Distortion (in %age)	≤ 10
	"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer"	Yes

OPTICAL	LED chip Efficacy	≥130 Lm/Watt
	Colour temperature (+/-500K)	6000K
	Working life for LED (Minimum 50,000 burning hours as per LM-80 report)	Yes
	Colour Rendering Index(CRI)	≥70
	Beam Angle	≥120
	Optic lense materal (UV stabilised) (Write NA for without optic lense supply)	Poly carbonate lense
THERMAL MANAGEMENT	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes
	Capacitor shall be rated for a temperature of 105 deg. celsius or better	Yes
	Junction temperature	< 85 degC
	Operating temperature range	-10 deg C to +55 deg C
	Operating Humidity Range	10 % to 95% RH
PROTECTION	Short circuit Protection	Yes
	Over load protecton	Yes
	Over Voltage protection	Yes
	Reverse polarity	Yes
	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes
	Insulation resistance between earth and current carrying part	>100 M ohm
	The luminaire shall be protected against surges and transients (Internal)	>/=5KV
	The luminaire shall be protected against surges and transients of >/=10KV (External)	Yes
CONSTRUCTIONAL	The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity	Yes
	The luminaire body must be corrosion resistant epoxy powder coated	Yes
	All fastners must be of stainless steel	Yes
	The entire housing (both LED section and driver section) shall be dust and water proof having IP 66 protection as per IS:10322 (Part 1):1982 latest	Yes
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes
	Luminaries light transparency should be of Toughened glass	Yes
	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degration due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	2 Nos.
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	50 cm
Light Source	SMD LED Chip as per LM 80/IS16106	
MARKING	"Manufactures Name and and brand on the aluminium die cast body	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
	LED Make	OSRAM / NICHIA/CREE / SAMSUNG / SEOUL / LUMILED / PHILIPS / EDISON / SYSKA / LUMENMAX / EVERLIGHT / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish on demand by buyer/consignee)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government lab/NABL/ILAC accredited lab. Reports shall be furnish on demany by buyer (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc..)	Yes

REPORTS AND CERTIFICATIONS	LM 80 & TM 21 (Part of LM 80) (Ref. IS:16105:2012) Reports and Photo biological report for LED report from Central Government lab /NABL/ILAC accredited lab. Reports shall be furnish on demany by buyer (LM-80 report shall haveand the Pohoto Biological report of the LED Chip being used in the luminaire)	Yes
	Availability of test Report from Central Government lab/NABL/ILAC accredited lab to Indian Standrad IS:10322/part 5/sec-5/2012 and IS 16107 (Part 2/Sec 1) : 2012	Yes
	Seller has to furnish Type test report on demand by buyer/consignee	Yes
	DC or AC supplied electronic control gear for LED Module shall complpy as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for Flood Light shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 5): 2012 as applicable on the date	Yes

ईपीबीजी विवरण | ePBG Detail

सलाहकार बैंक Advisory Bank :	State Bank of India
ईपीबीजी प्रतिशत (%) ePBG Percentage(%):	3.00
बोली लगाने वाले को बोली के नियमों और शर्तों के अनुसार लागू ईपीबीजी प्रस्तुत करना होगा The bidder shall furnish ePBG as applicable as per bid's terms and conditions	

नियम और शर्तें | Terms and Conditions

1. General Terms and Conditions-

- 1.1 This contract is governed by the [General Terms and Conditions](#), conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

2. Buyer Added Bid Specific Terms and Conditions-

2.1 Generic

OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 25 percent of bid quantity at the time of placement of contract. The purchaser also reserves the right to increase the ordered quantity by up to 25% of the contracted quantity during the currency of the contract at the contracted rates. Bidders are bound to accept the orders accordingly.

2.2 Generic

Bidder shall submit the following documents along with their bid for Vendor Code Creation:

- Copy of PAN Card.
- Copy of GSTIN.
- Copy of Cancelled Cheque.
- Copy of EFT Mandate duly certified by Bank.

2.3 Generic

Data Sheet of the product(s) offered in the bid, are to be uploaded along with the bid documents. Buyers can match and verify the Data Sheet with the product specifications offered. In case of any unexplained mismatch of technical parameters, the bid is liable for rejection.

2.4 Generic

Experience Criteria: The Bidder or its OEM {themselves or through reseller(s)} should have regularly, manufactured and supplied same or similar Category Products to any Central / State Govt Organization / PSU / Public Listed Company for 2 years before the bid opening date. Copies of relevant contracts to be submitted along with bid in support of having supplied some quantity during each of the year. In case of bunch bids, the primary product having highest value should meet this criterion.

2.5 Generic

Manufacturer Authorization:Wherever Authorised Distributors/service providers are submitting the bid, Authorisation Form /Certificate with OEM/Original Service Provider details such as name, designation, address, e-mail Id and Phone No. required to be furnished along with the bid

2.6 Scope of Supply:

Scope of supply (Bid price to include all cost components) : Only supply of Goods

2.7 Purchase Preference (Centre):

Purchase preference to Micro and Small Enterprises (MSEs): Purchase preference will be given to MSEs as defined in Public Procurement Policy for Micro and Small Enterprises (MSEs) Order, 2012 dated 23.03.2012 issued by Ministry of Micro, Small and Medium Enterprises and its subsequent Orders/Notifications issued by concerned Ministry. If the bidder wants to avail the Purchase preference, the bidder must be the manufacturer of the offered product in case of bid for supply of goods. Traders are excluded from the purview of Public Procurement Policy for Micro and Small Enterprises. In respect of bid for Services, the bidder must be the Service provider of the offered Service. Relevant documentary evidence in this regard shall be uploaded along with the bid in respect of the offered product or service. If L-1 is not an MSE and MSE Seller (s) has/have quoted price within L-1+ 15% of margin of purchase preference /price band defined in relevant policy, such Seller shall be given opportunity to match L-1 price and contract will be awarded for percentage of 25% of total value.

2.8 Purchase Preference (Centre):

Purchase Preference linked with Local Content (PP-LC) Policy:

The bid clause regarding "Preference to Make In India products" stands modified in this bid and shall be governed by the PPLC Policy No. FP-20013/2/2017-FP-PNG dated 17.11.2020 issued by MoP&NG as amended up to date. Accordingly, bidders with Local Content less than or equal to 20% will be treated as "Non Local Supplier". The prescribed LC shall be applicable on the date of Bid opening. Sanctions on the bidders for false / wrong declaration or not fulfilling the Local Content requirement shall be as per the PPLC policy. Further following additional provisions are added in the certification and verification of local content provision of the Preference to Make in India clause:

- i. In case of foreign bidder, certificate from the statutory auditor or cost auditor of their own office or subsidiary in India giving the percentage of local content is also acceptable. In case office or subsidiary in India does not exist or Indian office/subsidiary is not required to appoint statutory auditor or cost auditor, certificate from practicing cost accountant or practicing chartered accountant giving the percentage of local content is also acceptable.
- ii. Along with Each Invoice: The local content certificate (issued by statutory auditor on behalf of procuring company) shall be submitted along with each invoice raised. However, the % of local content may vary with each invoice while maintaining the overall % of local content for the total work/purchase of the pro-rata local content requirement. In case, it is not satisfied cumulatively in the invoices raised up to that stage, the supplier shall indicate how the local content requirement would be met in the subsequent stages.
- iii. The bidder shall submit an undertaking from the authorized signatory of bidder having the Power of Attorney along with the bid stating the bidder meets the mandatory minimum LC requirement and such undertaking shall become a part of the contract.

2.9 Service & Support:

Availability of Service Centres: Bidder/OEM must have a Functional Service Centre in the State of each Consignee's Location in case of carry-in warranty. (Not applicable in case of goods having on-site warranty). If service center is not already there at the time of bidding, successful bidder / OEM shall have to establish one within 30 days of award of contract. Payment shall be released only after submission of documentary evidence of having Functional Service Centre.

2.10 Service & Support:

Dedicated /toll Free Telephone No. for Service Support : BIDDER/OEM must have Dedicated/toll Free Telephone No. for Service Support.

2.11 Service & Support:

Escalation Matrix For Service Support : Bidder/OEM must provide Escalation Matrix of Telephone Numbers for Service Support.

2.12 Certificates:

Bidder's offer is liable to be rejected if they don't upload any of the certificates / documents sought in the Bid document, ATC and Corrigendum if any.

2.13 Certificates:

ISO 9001: The bidder or the OEM of the offered products must have ISO 9001 certification.

2.14 Certificates:

The bidder is required to upload, along with the bid, all relevant certificates such as BIS licence, type test certificate, approval certificates and other certificates as prescribed in the Product Specification given in the bid document.

2.15 Warranty:

Warranty period of the supplied products shall be 3 years from the date of final acceptance of goods or after completion of installation, commissioning & testing of goods (if included in the scope of supply), at consignee location. OEM Warranty certificates must be submitted by Successful Bidder at the time of delivery of Goods. The seller should guarantee the rectification of goods in case of any break down during the guarantee period. Seller should have well established Installation, Commissioning, Training, Troubleshooting and Maintenance Service group in INDIA for attending the after sales service. Details of Service Centres near consignee destinations are to be uploaded along with the bid.

2.16 Past Project Experience:

Proof for Past Experience and Project Experience clause: For fulfilling the experience criteria any one of the following documents may be considered as valid proof for meeting the experience criteria:a. Contract copy along with Invoice(s) with self-certification by the bidder that service/supplies against the invoices have been executed.b. Execution certificate by client with contract value.c. Any other document in support of contract execution like Third Party Inspection release note, etc.Proof for Past Experience and Project Experience clause: For fulfilling the experience criteria any one of the following documents may be considered as valid proof for meeting the experience criteria:a. Contract copy along with Invoice(s) with self-certification by the bidder that service/supplies against the invoices have been executed.b. Execution certificate by client with contract value.c. Any other document in support of contract execution like Third Party Inspection release note, etc.

2.17 Sample Clause:

After award of contract – Successful Bidder shall have to get advance sample approved from buyer before bulk manufacturing / starting bulk supplies. Successful Bidder shall submit

2 samples for Buyer's approval, within 7 days of award of contract. Buyer shall, as per contract specifications framework, either approve the advance sample or will provide complete list of modification required in the sample within 5 days of receipt of advance sample. Seller shall be required to ensure supply as per approved sample with modifications as communicated by Buyer. If there is delay from buyer side in approval of advance sample – the delivery period shall be refixed without LD for the period of delay in sample approval. In case, the sample is found to have major deviations / not conforming to the Contract specifications, the buyer at its discretion may call for fresh samples for approval before allowing bulk supplies or may terminate the contract after notifying the deviations to the seller. Unless otherwise provided in the contract, all samples required for test shall be supplied by the contractor free of cost. Where under the contract, the contractor is required to submit an advance sample, any expenses incurred by the contractor on or in connection with the production of stores in bulk, before the sample has been approved unconditionally shall be borne by the Seller and he shall not claim any compensation in the event of such sample being found unacceptable by the Buyer / Consignee.

2.18 Forms of EMD and PBG:

Bidders can also submit the EMD with Account Payee Demand Draft in favour of

Central Coalfields Limited, Piparwar Area
payable at
Ranchi

Bidder has to upload scanned copy / proof of the DD along with bid and has to ensure delivery of hardcopy to the Buyer within 5 days of Bid End date / Bid Opening date.

2.19 Buyer Added Bid Specific ATC:

Buyer uploaded ATC document [Click here to view the file](#) .

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.