

## अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687771054160

अनुबंध तिथि | Generated Date : 17-Mar-2024

## संगठन विवरण | Organisation Details

प्ररूप | Type : State Government  
मंत्रालय | Ministry : -  
विभाग | Department : Education Department Chandigarh  
संगठन का नाम | Organisation Name : N/A  
कार्यालय क्षेत्र | Office Zone: Manimajra

## खरीदार विवरण | Buyer Details

पद | Designation : BUYER  
संपर्क नंबर | Contact No. : 0172-2738424-  
ईमेल आईडी | Email ID : clerk-gmsssmhc@chd.nic.in  
जीएसटीआईएन | GSTIN : -  
पता | Address : Govt. Model Sr. Sec. School, Modren Housing complex,manimajra, CHANDIGARH, CHANDIGARH-160101, India

## वित्तीय स्वीकृति विवरण | Financial Approval Detail

आईएफडी सहमति | IFD Concurrence : No  
प्रशासनिक अनुमोदन का पदनाम | Designation of Administrative Approval: PRINCIPAL  
वित्तीय अनुमोदन का पदनाम | Designation of Financial Approval : PRINCIPAL

## भुगतान प्राधिकरण विवरण | Paying Authority Details

Role: BUYER  
भुगतान का तरीका | Payment Mode: Offline  
पद | Designation : BUYER  
ईमेल आईडी | Email ID : clerk-gmsssmhc@chd.nic.in  
जीएसटीआईएन | GSTIN : -  
पता | Address: Govt. Model Sr. Sec. School, Modren Housing complex,manimajra, CHANDIGARH, CHANDIGARH-160101, India

## विक्रेता विवरण | Seller Details

जेम विक्रेता आईडी | GeM Seller ID : EAFB180000527935  
कंपनी का नाम | Company Name : GUPTA BROTHERS  
संपर्क नंबर | Contact No. : 09872745999  
ईमेल आईडी | Email ID : vinodkumargupta2230@gmail.com  
पता | Address : 1566,SECTOR 22-B,CHANDIGARH, CHANDIGARH, CHANDIGARH-160022, -  
एमएसएमई पंजीकरण संख्या | MSME Registration number : -  
जीएसटीआईएन | GSTIN: 04AFFPG6817D1ZV

\*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Buyer

## वितरण निर्देश | Delivery Instructions : NA

## उत्पाद विवरण | Product Details

#	आइटम विवरण   Item Description	आइटम विवरण   Ordered Quantity	इकाई   Unit	इकाई मूल्य (INR)   Unit Price (INR)	कर विभाजन (INR)   Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित)   Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम   Product Name : Ahuja Radios Intel Atom n2800; clock frequency 1.86GHz Public Address System ब्रांड   Brand : Ahuja Radios ब्रांड प्रकार   Brand Type : Registered Brand कैटलॉग की स्थिति   Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है   Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थांश   Category Name & Quadrant : Public Address System (Q3) मॉडल   Model: AHUJA CMA 4400 (02), AHUJA CMC 4100 (03), AHUJA CMD 4200 (12), AHUJA AWM-520VH (01), AHUJA AWM- 520 VL (02), AHUJA PS 500T (12), EXTENSION BOARD (01), RACK (01) एचएसएन कोड   HSN Code: 8518	1	pieces	20,487	NA	20,487
कुल ऑर्डर मूल्य   Total Order Value (in INR)						20,487

## परेषिती विवरण | Consignee Detail

क्र.सं.   S.No	परेषिती   Consignee	वस्तु   Item	लॉट नंबर   Lot No.	मात्रा   Quantity	दिनांक के बाद डिलीवरी शुरू करना है   Delivery Start After	वितरण पूरा कब तक करना है   Delivery To Be Completed By
	पद   Designation : BUYER ईमेल आईडी   Email ID : clerk-gmsssmhc@chd.nic.in संपर्क   Contact : 0172-2738424-	Ahuja Radios Intel Atom				

1	जीएसटीआईएन   GSTIN :- पता   Address : Govt. Model Sr. Sec. School, Modren Housing complex,manimajra, CHANDIGARH, CHANDIGARH-160101, India	n2800; clock frequency 1.86GHz Public Address System	-	1	17-Mar-2024	01-Apr-2024
Product Specification for Ahuja Radios Intel Atom n2800; clock frequency 1.86GHz Public Address System						
विनिर्देश   Specification	उप-विनिर्देश   Sub-Spec				मूल्य   Value	
Specification	Microphone input				Nominal level 14 mV at 3.3 kΩ (MIC power supply voltage 2.5 V)	
	Line output				Nominal level 0 dB and 0.775 V	
	Floating contacts				NA	
	Control input				0 - 10 V, for controlling the volume remotely	
	Relay output				(switch-over contact) 30 V/1 A, 100000 switching cycles	
	Audio output				70 V/100 V	
	Extension plug				EXTENSION PLUG	
	Ports				RJ45 Shielded Plug-in	
	Connection terminals				Pluggable screw-in terminals for connecting the power supply, output, microphone, inputs, line output, 70 V/100 V audio output, loudspeakers	
	Power Supply:				Standard 12V 3-5A	
	Cabling				min. Cat. 5 Line length of up to 100 m in LAN	
	Protocol				RS-485 (EIA 485) Half Duplex Serial Communication / TCP/IP	
	Marking				NA	
	Line Monitoring				Output or speaker circuit	
	Fault Detection				Self Acknowledgement Display On Screen Via 485 Serial Data Input	
	Design				Plastic Front Panel With 7 Inch Touch LCD : Degree of protection IP50 rating ; Installable as console ; easy to clean	
	Operating range				0°C to +70°C; max. non- condensing relative ambient humidity 80%;	
	Features				Monochrome LCD display; capable of being backlit white, graphical menu guidance, 128x64 pixel resolution, 3- colour multi-function LED display for voice call indication	
	Keypad				On Touch Screen Display Standard Keyboard	
	Microphone				Omnidirectional electret microphone; max. 7 m speaking distance	
	Loudspeaker				2x 8 Ω loudspeakers with a special membrane; 85 dB/W/m sound pressure	
	Amplifier				integrated Class D amplifier; 2.5 W	
	Max sound pressure				99 dB	
	Handset/headset				NA	

	Transmission bandwidth	16,000 Hz
	Transfer rate	9600 Kbps (Half/Full Duplex)
	Inputs	Audio Line In 3.5mm Jack Stereo, USB 2.0 Type A
	Outputs	Audio Line Out Stereo 3.5mm Jack (For Headphones Or External Speakers)
	Connections	pluggable screw-in terminals; extension plug: Handset module, one-touch dialling module, gooseneck module, headset module, IP-uplink: shielded RJ45 modular plug-in port
	Power supply	12V-3A SMPS, Line Regulation (±): 0.5%, Frequency Range: 47 ~ 63 Hz, Universal AC input
	Dimensions W x H x D	290mm x 109mm x 198mm (Including Housing)
	Weight	approx. 920 g
The intercom system or control unit of the intercom system	32 one big touch keys	No
	4 large label fields	NA
	RGB Backlit buttons	NA
	Degree of protection	NA
	Easy to clean and chemical resistant surface foil	Yes
	Front panel white aluminum (RAL 9006); rear housing graphite grey (RAL 7024)	Yes
	Switching cycles	NA
	Actuation Force : 3N	NA
	Ribbon cable to base terminal (length: 35 cm) or ribbon cable to the next one-touch key module CDDD 32P	NA
	Power supply: external supply, 20-30VDC, type PA30W24V possible	NA
	Temperature range: 0° to +70°C; up to 80% non-condensing relative ambient humidity	Yes
	Mounting:console or built-in control desk; mounted with back housing supplied	NA
	Dimensions W x H x D: including back housing: 262x196x45 mm	NA
	Weight:approx 850 g	Yes
Stand Alone Touch Module	Industrial PC with Windows 7 Embedded for a variety of applications; For use of one-touch key or video monitor-module of Intercom Client, ComWIN Light or ComWIN Weg Client; Can also be used for third-party software products (building management systems, video management systems, etc); protection class IP 20; material plastic; scope of supply: module with back housing, power supply, brief description; plastic; front panel white aluminium (RAL 9006); back housing graphite grey (RAL 7024); protection class IP 20 (with headset plugged in); easy-to-clean and chemical-resistant foil surface; scratch-proof genuine glass display	NA
	Processor	Intel Atom n2800; clock frequency 1.86GHz
	Display	8,4" (21,3 cm) TFT-LCD colour-display with touch functionality
	Connection:Line-Out 3,5mm jack; DVI-I Port; 2x USB2; 2x RJ45 (Uplink/Downlink)	Yes
	Memory	1GB RAM, MicroSD Port (16/32 GB) Class 10 supported.
	Power supply: external power source, 12VDC; plug in power unit PA30W12V in scope of delivery	Yes
	Temperature range: 0° to +40°C; up to 80% non-condensing relative ambient humidity	Yes
	Mounting: console or built-in control desk; mounted with back housing supplied	Yes
	Dimensions W x H x D:	290mm x 109mm x 198mm (Including Housing)
	Module with back housing, connector, mounting materials :Relay output (switch-over contact) 30 V/1 A, 100000 switching cycles plastic; front panel white aluminum (RAL 9006); back housing graphite grey (RAL 7024); protection class IP 50 (with headset plugged in); easy-to-clean and chemical-resistant foil surface	No
	Connection: connecting cable to base terminal (length: 50 cm); 4C4P socket for headset	No
	Power supply: from base terminal	Yes

General	Temperature range: 0° to +70°C; up to 80% non-condensing relative ambient humidity	Yes
	Mounting:console or built-in control desk; mounted with back housing supplied	Yes
	Dimensions W x H x D: including back housing: 55x196x43 mm	Yes
	Weight:approx 420g	Yes
	Design :	Plastic Front Panel With 7Inch Touch LCD : Degree of protection IP50 rating ; Installable as console ; easy to clean
	Connection:4-pin cable connecting cable with plug (length: 50 cm)	Yes
	Power supply: from base terminal	Yes
	Temperature range: 0° to +70°C; up to 80% non-condensing relative ambient humidity	Yes
	Microphone: Omnidirectional electret microphone	Yes
	Loudspeaker: 50Ω	Yes
	Frequency range: 200–16,000 Hz	Yes
	Button: push-to-talk key	Yes
	Mounting:console or built-in control desk; mounted with back housing supplied	Yes
	Dimensions W x H x D: including back housing:	55x238.5x74 mm
	Weight:	Aproxx 1.5Kg
टिप्पणी   <b>Note::</b> Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.		
ईपीबीजी विवरण   ePBG Detail		
NA		
नियम और शर्तें   Terms and Conditions		
1. General Terms and Conditions-		
1.1 This contract is governed by the <a href="#">General Terms and Conditions</a> , conditions stipulated to this Product/Service as provided in the Marketplace.		
1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable		
नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।		
Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.		