

## अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687771749203

अनुबंध तिथि | Generated Date : 18-Mar-2024

## संगठन विवरण | Organisation Details

प्ररूप | Type : Central Government  
मंत्रालय | Ministry : Ministry of Information and Broadcasting  
विभाग | Department : Ministry of Information and Broadcasting  
संगठन का नाम | Organisation Name : All India Radio  
कार्यालय क्षेत्र | Office Zone : AIR JABALPUR

## खरीदार विवरण | Buyer Details

पद | Designation : Engineering Assistant  
संपर्क नंबर | Contact No. : 0761-2972005-  
ईमेल आईडी | Email ID : satyendrarajak@prasarbharati.gov.in  
जीएसटीआईएन | GSTIN : 23AAAJP0288R2ZM  
पता | Address : ALL INDIA RADIO, NEAR TV TOWER, KATANGA, JABALPUR, JABALPUR, MADHYA PRADESH-482001, India

## वित्तीय स्वीकृति विवरण | Financial Approval Detail

आईएफडी सहमति | IFD Concurrence : No  
प्रशासनिक अनुमोदन का पदनाम | Designation of Administrative Approval : SAO  
वित्तीय अनुमोदन का पदनाम | Designation of Financial Approval : DDG

## भुगतान प्राधिकरण विवरण | Paying Authority Details

Role: PAO  
भुगतान का तरीका | Payment Mode: Offline  
पद | Designation : ASSISTANT DIRECTOR  
ईमेल आईडी | Email ID : rajeevgangra@prasarbharati.gov.in  
जीएसटीआईएन | GSTIN : 23AAAJP0288R2ZM  
पता | Address : All India Radio NEAR TV TOWER, KATANGA, JABALPUR, Jabalpur, MADHYA PRADESH-482001, India

## विक्रेता विवरण | Seller Details

जेम विक्रेता आईडी | GeM Seller ID : 08PK210001936363  
कंपनी का नाम | Company Name : Yes Celebration  
संपर्क नंबर | Contact No. : 09529523999  
ईमेल आईडी | Email ID : yescelebration@gmail.com  
पता | Address : Behind Chawla Nursing Home, Yes Celebration, Baba Shyam Singh Colony, Hanumangarh, RAJASTHAN-335512, -  
एमएसएमई पंजीकरण संख्या | MSME Registration number : UDYAM-RJ-16-0010336  
एमएसई सामाजिक श्रेणी | MSE Social Category : General  
एमएसई लिंग श्रेणी | MSE Gender : Male  
जीएसटीआईएन | GSTIN : 08ANSPT1206C1Z1

\*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Buyer

## वितरण निर्देश | Delivery Instructions : NA

## उत्पाद विवरण | Product Details

#	आइटम विवरण   Item Description	आइटम विवरण   Ordered Quantity	इकाई   Unit	इकाई मूल्य (INR)   Unit Price (INR)	कर विभाजन (INR)   Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित)   Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम   Product Name : Orient electric 60W LED Luminaire For Flood Light ब्रांड   Brand : Orient electric ब्रांड प्रकार   Brand Type : Registered Brand कैटलॉग की स्थिति   Catalogue Status : OEM verified catalogue कैसे बेचा जा रहा है   Selling As : OEM verified Reseller श्रेणी का नाम और चतुर्थांश   Category Name & Quadrant : LED Luminaire (for Flood Light) as per IS 10322, IS 16107 (Q3) मॉडल   Model: Orient electric best quality flood light एचएसएन कोड   HSN Code: HSN not specified by seller	6	pieces	2,300	NA	13,800
कुल ऑर्डर मूल्य   Total Order Value (in INR)						13,800

## प्रेषिती विवरण | Consignee Detail

क्र.सं.   S.No	प्रेषिती   Consignee	वस्तु   Item	लॉट नंबर   Lot No.	मात्रा   Quantity	दिनांक के बाद डिलीवरी शुरू करना है   Delivery Start After	वितरण पूरा कब तक करना है   Delivery To Be Completed By
1	पद   Designation : CHHINDWARA CONSIGNEE UDC ईमेल आईडी   Email ID : pnikitanaidu@prasarbharati.gov.in संपर्क   Contact : - जीएसटीआईएन   GSTIN : -	Orient electric 60W LED Luminaire For Flood	-	6	18-Mar-2024	02-Apr-2024

	पता  Address : AKASHVANI , KUKDA HILLS TV TOWER CHHINDWARA M.P, CHHINDWARA, MADHYA PRADESH-480001, India	Light				
Product Specification for Orient electric 60W LED Luminaire For Flood Light						
विनिर्देश   Specification	उप-विनिर्देश   Sub-Spec		मूल्य   Value			
STANDARDS	LED Luminaire conformity to IS:10322/Part 5/Section 5/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest		Yes			
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)		Yes			
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec.-1)/2012		Type B			
	Types of LED Modules as per the IS: 16103(Part-2)/2012		Type 3			
	LED Rating/System Wattage/Rated Power		60W			
	Luminaire System Efficacy (Lumen/watt)		>= 100 Lm/Watt			
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest		IP66			
	Mounting brackets (included)		Adjustable			
	Warranty for free replacement (in Years)		3			
ELECTRICAL EFFICIENCY	Input operating Voltage range and frequency		90 to 300 V olts AC at 50 Hz+/-2 Hz			
	Automatic Higher Cut off voltage above 300 volt		Yes			
	Rated voltage		230 V AC 50 Hz			
	AC Power Factor at full load		≥ 0.95			
	Driver Efficiency (in %age)		≥85			
	Total Harmonics Distortion (in %age)		≤ 10			
	"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer"		Yes			
OPTICAL	LED chip Efficacy		≥130 Lm/Watt			
	Colour temperature (+/-500K)		6000K			
	Working life for LED (Minimum 50,000 burning hours as per LM-80 report)		Yes			
	Colour Rendering Index(CRI)		≥70			
	Beam Angle		≥120			
	Optic lense materal (UV stabilised) (Write NA for without optic lense supply)		Poly carbonate lense			
THERMAL MANAGEMENT	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively		Yes			
	Capacitor shall be rated for a temperature of 105 deg. celsius or better		Yes			
	Junction temperature		< 85 degC			
	Operating temperature range		-10 deg C to +50 deg C			
	Operating Humidity Range		10 % to 95% RH			
PROTECTION	Short circuit Protection		Yes			
	Over load protecton		Yes			
	Over Voltage protection		Yes			
	Reverse polarity		Yes			
	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)		Yes			
	Insulation resistance between earth and current carrying part		>100 M ohm			
	The luminaire shall be protected against surges and transients ( Internal)		>=5KV			
	The luminaire shall be protected against surges and transients of >=10KV (External)		Yes			
	The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity		Yes			
	The luminaire body must be corrosion resistant epoxy powder coated		Yes			
	All fastners must be of stainless steel		Yes			
	The entire housing (both LED section and driver section) shall be dust and water proof having IP 66 protection as per IS:10322 (Part 1):1982 latest		Yes			
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,		Yes			

CONSTRUCTIONAL	Luminaries light transparency should be of Toughened glass	Yes
	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degration due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	2 Nos.
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	50 cm
	Light Source	SMD LED Chip as per LM 80/IS16106
MARKING	"Manufactures Name and and brand on the aluminium die cast body	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
REPORTS AND CERTIFICATIONS	LED Make	OSRAM / NICHIA/CREE / SAMSUNG / SEOUL / LUMILED / PHILIPS / EDISON / SYSKA / LUMENMAX / EVERLIGHT / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish on demand by buyer/consignee)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government lab/NABL/ILAC accredited lab. Reports shall be furnish on demany by buyer (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,)	Yes
	LM 80 & TM 21 (Part of LM 80) (Ref. IS:16105:2012) Reports and Photo biological report for LED report from Central Government lab /NABL/ILAC accredited lab. Reports shall be furnish on demany by buyer (LM-80 report shall haveand the Pohoto Biological report of the LED Chip being used in the luminaire)	Yes
	Availability of test Report from Central Government lab/NABL/ILAC accredited lab to Indian Standrad IS:10322/part 5/sec-5/2012 and IS 16107 (Part 2/Sec 1) : 2012	Yes
	Seller has to furnish Type test report on demand by buyer/consignee	Yes
	DC or AC supplied electronic control gear for LED Module shall comlpy as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for Flood Light shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 5): 2012 as applicable on the date	Yes
ईपीबीजी विवरण   ePBG Detail		
NA		
<b>नियम और शर्तें   Terms and Conditions</b>		
<b>1. General Terms and Conditions-</b>		
1.1 This contract is governed by the <a href="#">General Terms and Conditions</a> , conditions stipulated to this Product/Service as provided in the Marketplace.		
1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable		
नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।		
Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.		