## अनुबंध|Contract



अनुबंध क्रमांक | Contract No: GEMC-511687764203332 अनुबंध तिथि | Generated Date : 26-Mar-2024

संगठन विवरण|Organisation Details

प्ररूप|Type : Central Government मंत्रालय|Ministry : Ministry of Finance विभाग|Department : Department of Revenue

संगठन का

नाम | Organisation Name Central Board of Excise and Customs (CBEC)

Office Of Commissioner Of Customs (general), New Custom

कार्यालय क्षेत्र|Office Zone: House, Near Igia, New Delhi

खरीदार विवरण|Buyer Details

पद|Designation : executive assistant संपर्क नंबर|Contact No. : 011-25654156-ईमेल आईडी|Email ID : vivekk.q081401@qov.in

जीएसटीआईएन|GSTIN: -

New Custom House Near IGI Airport, पता|Address :

भुगतान प्राधिकरण विवरण|Paying Authority Details

DDO

NEW DELHI, DELHI-110037, India

### वित्तीय स्वीकृति विवरण|Financial Approval Detail

आईएफडी सहमति IFD Concurrence : Yes

प्रशासनिक अनुमोदन का पदनाम|

Designation of Administrative Approval:

वित्तीय अनुमोदन का पदनाम|

Designation of Financial Approval :

es Role: Additional Commissioner भुगतान का तरीका|

भुगतान का तरीका| Payment Mode:

पद | Designation : Administrative Officer  $$\hat{\eta}$$  b.tete1968@gov.in

जीएसटीआईएन|GSTIN: N

पता|Address: New Custom House Near IGI Airport, SOUTH WEST DELHI, DELHI-110037, India

विक्रैता विवरण|Seller Details

जेम विक्रैता आईडी|GeM Seller ID : 2CCF180000099709 कंपनी का नाम|Company Name : STREET COBBLER संपर्क नंबर|Contact No. : 09711376507

ईमेल आईडी|Email ID : streetcobbler@gmail.com

Pathak Medical Centre, ground floor, c-1/36,SHANTI NIWAS,Street Number 5, Uttam Nagar, New Delhi, South West Delhi,

पता| Address : Delhi, 110059,UTTAM NAGAR, West Delhi, DELHI-110059, - एमएसएमई पंजीकरण संख्या|MSME Registration number : UDYAM-DL-10-0004475

एमएसई सामाजिक श्रेणी|MSE Social Category : SC एमएसई लिंग श्रेणी|MSE Gender : Female जीएसटीआईएन|GSTIN: 07AZHPK9998D2ZP

\*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा|GST / Tax invoice to be raised in the name of - Buyer

Additional Commissioner

वितरण निर्देश | Delivery Instructions : NA

#### उत्पाद विवरण|Product Details

#	आइटम विवरण Item Description	आइटम विवरण  Ordered Quantity	इकाई   Unit	इकाई मूल्य (INR)  Unit Price (INR)	कर विभाजन (INR)  Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित)  Price (Inclusive of all Duties and Taxes in INR)
1	उद्याद का नाम  Product Name : Aster LiteAster Industries 700W LED Luminaire For Flood Light ब्रांड Brand : Aster LiteAster Industries ब्रांड प्रकार Brand Type : Unregistered Brand कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थाश Category Name & Quadrant : LED Luminaire (for Flood Light) as per IS 10322, IS 16107 (Q3) गाँडल Model: AST-LFL-700 एचएसएन कोड HSN Code: HSN not specified by seller	16	pieces	5,975	NA	95,600
व	कल ऑर्डर मल्य   Total Order Value (in INR)					

#### परेषिती विवरण|Consignee Detail

क्र.सं. S.No	परेषिती Consignee	वस्तु Item	लॉट नंबर  Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है  Delivery Start After	वितरण पूरा कब तक करना है  Delivery To Be Completed By
	पद। Designation : executive assistant					

1	ईमेल आईडी Email ID : vivekk.g081401@gov.in संपर्क Contact : 011-25654156- जीएसटीआईएन GSTIN : - पता Address : New Custom House Near IGI Airport, NEW DELHI, DELHI-110037, India	Aster LiteAster Industries 700W LED Luminaire For Flood Light	-	16	26-Mar-2024	10-Apr-2024		
Product Sp	ecification for Aster LiteAster Industries 700W LE	D Luminaire For Flood	l Light					
विनिर्देश Speci	ication उप-विनिर्देश Sub-Spec			मूल्य Value	मूल्य Value			
	LED Luminaire conformity to IS:10322/Part 5/Section 5 latest	LED Luminaire conformity to IS:10322/Part 5/Section 5/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest			Yes			
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)			Yes	Yes			
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec1)/2012			Туре В			
	Types of LED Modules as per the IS: 16103(Part-2)/2012			Type 3	Type 3			
STANDARDS	LED Rating/System Wattage/Rated Power	LED Rating/System Wattage/Rated Power			700W			
	Luminaire System Efficacy (Lumen/watt)	Luminaire System Efficacy (Lumen/watt)			>/= 100 Lm/Watt			
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest			IP66			
	Mounting brackets (included)			Adjustable	Adjustable			
	Warranty for free replacement (in Years)			2	2			
	Input operating Voltage range and frequency			90 to 300 V d	90 to 300 V olts AC at 50 Hz+/-2 Hz			
	Automatic Higher Cut off voltage above 300 volt	Automatic Higher Cut off voltage above 300 volt			Yes			
	Rated voltage	Rated voltage			230 V AC 50 Hz			
ELECTRICAL	AC Power Factor at full load	AC Power Factor at full load			≥ 0.95			
EFFICIENCY	Driver Efficiency (in %age)	Driver Efficiency (in %age)			≥85			
	Total Harmonics Distortion (in %age)	Total Harmonics Distortion (in %age)			≤ 10			
	"The total circuit power shall not be more than 110 per manufacturer"	cent of the value declared b	y the	Yes				
	LED chip Efficacy	LED chip Efficacy			≥130 Lm/Watt			
	Colour temperature (+/-500K)			6500K	6500K			
	Working life for LED (Minimum 50,000 burning hours a	Working life for LED (Minimum 50,000 burning hours as per LM-80 report)			Yes			
OPTICAL	Colour Rendering Index(CRI)	Colour Rendering Index(CRI)			≥75			
	Beam Angle	Beam Angle			≥120			
	Optic lense materal (UV stabilised) (Write NA for withou	Optic lense materal (UV stabilised) (Write NA for without optic lense supply)			NA			
	Heat sink should be die-cast aluminium along with suff	ficient heat sink fins to dissip	oate heat effe	ctively Yes				
	Capacitor shall be rated for a temperature of 105 deg.	celsius or better		Yes				
THERMAL MANAGEMENT	Junction temperature				< 85 degC			
WANAGEWENT	Operating temperature range				-20 deg C to +50 deg C			
	Operating Humidity Range			10 % to 95%	RH			
	Short circuit Protection			Yes				
	Over load protecton			Yes				
	Over Voltage protection	·			Yes			
	Reverse polarity			Yes	+			
PROTECTION	High voltage test (1.5 KV for one minute between supp	1.5 KV for one minute between supply terminals and body of the unit)			Yes			
	Insulation resistance between earth and current carryi	-		>100 M ohm				
	The luminaire shall be protected against surges and tra			>/=4KV				
	The luminaire shall be protected against surges and tra		al)	Yes				
	The Luminaires casing/housing (single piece housing) with higher thermal conductivity							
		luminaire body must be corrosion resistant epoxy powder coated			Yes			
	All fastners must be of stainless steel				Yes			
	The entire housing (both LED section and driver section protection as per IS:10322 (Part 1):1982 latest	n) shall be dust and water pi	roof having IP					
	Extruded silicon loop gasket shall be provided in the la between the UV Glass cover and the metal housing to	=	-					

	etc.,	
	Luminaries light transparency should be of Toughened glass	Yes
CONSTRUCTIONAL	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degration due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	4 Nos.
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	50 cm
	Light Source	SMD LED Chip as per LM 80/IS16106
	"Manufactures Name and and brand on the aluminium die cast body	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
MARKING	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
	LED Make	OSRAM / NICHIA/CREE / SAMSUNG / SEOUL / LUMILED / PHILIPS / EDISON / SYSKA / LUMENMAX / EVERLIGHT / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish on demand by buyer/consignee)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government lab/NABL/ILAC accrediated lab. Reports shall be furnish on demany by buyer (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,)	Yes
REPORTS AND CERTIFICATIONS	LM 80 & TM 21 (Part of LM 80) (Ref. IS:16105:2012) Reports and Photo biological report for LED report from Central Government lab /NABL/ILAC accrediated lab. Reports shall be furnish on demany by buyer (LM-80 report shall haveand the Pohoto Biological report of the LED Chip being used in the luminaire)	Yes
	Availability of test Report from Central Government lab/NABL/ILAC accrediated lab to Indian Standrad IS:10322/part 5/sec-5/2012 and IS 16107 (Part 2/Sec 1): 2012	Yes
	Seller has to furnish Type test report on demand by buyer/consignee	Yes
	DC or AC supplied electronic control gear for LED Module shall comlpy as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for Flood Light shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 5): 2012 as applicable on the date	Yes
		Yes

# ईपीबीजी विवरण | ePBG Detail

### NA

## नियम और शर्तें|Terms and Conditions

- 1. General Terms and Conditions-
- 1.1 This contract is governed by the General Terms and Conditions, conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.