अनुबंध|Contract



अनुबंध क्रमांक|Contract No: GEMC-511687783397920

अनुबंध तिथि | Generated Date : 28-Mar-2024

बोली/आरए/पीबीपी संख्या|Bid/RA/PBP No.: <u>GEM/2023/B/4138305</u>

अनुसूची नाम|Schedule Name:Schedule 1,Schedule 2

संगठन विवरण|Organisation Details

प्ररूप|Type : Central PSU मंत्रालय|Ministry : Ministry of Power विभाग|Department : Contracts and Materials

संगठन का नाम | Organisation Name : Ratnagiri Gas and Power Private Limited

कार्यालय क्षेत्र|Office Zone: Maharashtra

खरीदार विवरण|Buyer Details

पद|Designation : Manager संपर्क नंबर|Contact No. : 02359-241133-

ईमेल आईडी|Email ID : buycon3.rgppl.mh@gembuyer.in

जीएसटीआईएन|GSTIN: 27AADCR1375F1ZG

RATNAGIRI GAS AND POWER PRIVATE LTD. Anjanwel (PO),

पता|Address : Guhagar Taluk Ratnagiri Dist.,

RATNAGIRI, MAHARASHTRA-415703, India

वित्तीय स्वीकृति विवरण|Financial Approval Detail

आईएफडी सहमित IFD Concurrence : No

प्रशासनिक अनुमोदन का पदनाम| DGM

Designation of Administrative Approval: वित्तीय अनुमोदन का पदनाम|

Designation of Financial Approval :

... NA

भुगतान प्राधिकरण विवरण | Paying Authority Details

Role: PAO भुगतान का तरीका|

Payment Mode: Internet Banking

पद|Designation : Assistant Manager1
ईमेल आईडी|Email ID : pay2.rgppl.mh@gembuyer.in

जीएसटीआईएन|GSTIN : -

RATNAGIRI GAS AND POWER PRIVATE LTD. Anjanwel (PO),

पता|Address: Guhagar Taluk Ratnagiri Dist.,

Ratnagiri, MAHARASHTRA-415703, India

विक्रैता विवरण|Seller Details

जेम विक्रेता आईडी|GeM Seller ID : CE2D180000113026 कंपनी का नाम|Company Name : M/S TECHTRONIX संपर्क नंबर|Contact No. : 09415079721

ईमेल आईडी|Email ID : techana@rediffmail.com 113/34,SWAROOP NAGAR, पता| Address :

Kanpur Nagar, UTTAR PRADESH-208002, -एमएसएमई सत्यापित|MSME verified : No

एमएसएमई पंजीकरण संख्या|MSME Registration number : UDYAM-UP-43-0040087

एमएसई सामाजिक श्रेणी|MSE Social Category : General एमएसई लिंग श्रेणी|MSE Gender : Male

जीएसटीआईएन|GSTIN: 09ADEPG8733B1ZR

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा|GST / Tax invoice to be raised in the name of - Consignee

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण|Product Details

#	अाइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name: Metravi 3.5 digit Backlit LCD Hand Held True Rms Clamp Meter ब्रांड Brand: Metravi ब्रांड Brand: Metravi ब्रांड प्रकार Brand Type: Registered Brand कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As: OEM verified Reseller श्रेणी का नाम और चतुर्थाश Category Name & Quadrant: true rms clamp meter (Q3) मॉडल Model: METRAVI PRO-474 TRMS CLAMP METER एचएसएन कोड HSN Code: 9030	3	pieces	23,400	NA	70,200
2	उत्पाद का नाम Product Name : Metravi Category III 1000 V of IEC 61010 Not Available Insulation Tester ब्रांड Brand : Metravi ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्यांश Category Name & Quadrant : Insulation Tester (Q3) मॉडल Model: METRAVI DIT-909 Insulation Tester एचएसएन कोड HSN Code: 9030	3	pieces	28,490	NA	85,470
कु	कुल ऑर्डर मूल्य Total Order Value (in INR)					

क्र.सं. S.No		परेषिती Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा क तक करना है Delivery To Be Completed By
संपर्क Contact : 0: 1 जीएसटीआईएन GS1 पता Address : RA (PO), Guhagar Ta		Designation : - आईडी Email ID : buycon40.rgppl.mh@gembuyer.in Contact : 02359-241128- ઘરીઆईएन GSTIN : 27AADCR1375F1ZG Address : RATNAGIRI GAS AND POWER PRIVATE LTD. Anjanwel), Guhagar Taluk Ratnagiri Dist., NAGIRI, MAHARASHTRA-415703, India	Metravi 3.5 digit Backlit LCD Hand Held True Rms Clamp Meter	-	3	28-Mar-2024	27-May-2024
			Metravi Category III 1000 V of IEC 61010 Not Available Insulation Tester	-	3	28-Mar-2024	27-May-2024
Product :	Specification	for Metravi 3.5 digit Backlit LCD Hand Held	l True Rms Clamp Met	er			
विनिर्देश Sp	ecification	उप-विनिर्देश Sub-Spec				मूल्य Value	
		Туре				Hand Held	
GENERAL FE	ΔTI IDES	Display				3.5 digit Backlit	LCD
JEINEIVAET E	RIORES	Measurement Type				True RMS	
		count				6000	
		Resistance Measurement Range		10 kiloOhm			
		Resistance Measurement Accuracy (+/-)		1 percent			
		Frequency Measurement Range		0.5 kiloHertz			
		Frequency Measurement Accuracy (+/-)	cy Measurement Accuracy (+/-)		0.5 percent		
		AC Current Measurement Range		1000 Ampère			
		AC Current Measurement Accuracy (+/-)			2 percent		
MEASUREME	NT FEATURES	AC Voltage Measurement Range			1000 Volt		
		AC Voltage Measurement Accuracy (+/-)			1 percent		
				1000 Ampère			
		-		2 percent			
		·			1000 Volt		
					1 percent		
					Auto Power Off		
				34 millimeter			
GENERIC		Dimensions (H x W x L) (mm x mm x mm)				0	
SLINLKIC							
		Weight				350 gram	1
		Power Requirements				Battery Operate	
		Type of Battery				Non- Recharge	abie (Alkaline)
		if rechargeable , then chemistry of the battery		NA			
OWER REQ	UIREMENTS	if Non-rechargeable , then size of the battery / cell				AAA	
		Number of non- rechargeable the battery / cell			1		
		Voltage of rechargeable Battery milliamphere hour				0	
		Suitable charger/adaptor provided			NA		
		Minimum Operating Temperature				-10 degree Celsius	
OPERATING	CONDITION	Maximum Operating Temperature		50 degree Celsius			
		Operating Humidity (RH)				80 percent	
		Safety Certification			CE		
SAFETY		I Safety Rating				CAT III 600 V of IEC 61010 -2- D31	
	c	Dataila aftha Chandand Assassaina Consultad with the	Equipment			Manual,LEADS	
ACCESSORIE	3	Details of the Standard Accessories Supplied with the	Equipment		<u> </u>	Wandai,EEAD3	

yes

The equipment supplied with calibration certificate

	conformity to Dry Heat for 16 hrs at a specified maximum temp	No
	conformity to Cold Test for 4 hrs at a specified minimum temp in accordance with IS:9000/part-2/section-4/1977 latest	No
TEST REPORT DETAILS & TESTS	conformity to Damp Heat (Cyclic)Test for 2 Cycles of 24 h each at a temp of 40 degree C & 95% RH	No
	Availability of Test Reports from Central Govt/NABL/ILAC approved accredited lab to prove conformity to the specification	No
	Test Report Number and date for the specification test	NA
	Name and address of the Lab for the specification test	NA

হিম্মণী Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

खरीदार परिभाषित अतिरिक्त विशिष्टता के लिए |Buyer Defined Additional Specification for Metravi 3.5 digit Backlit LCD Hand Held True Rms Clamp Meter

विनिर्देश Specification	मूल्य Value
Technical Parameter 1	1. AC AMPS RANGE SHALL BE 0-1000 AMP (ACCURACY: 2%+- 5 COUNTS). 2. DC AMPS RANGE SHALL BE 0-1000 AMP (ACCURACY: 1.5%+- 5 COUNTS). 3. AC AMPS RANGE VIA I-FLEX SHALL BE UP TO 2500 AMP (ACCURACY: 2%+- 5 COUNTS). 4. AC VOLTS RANGE SHALL BE 0-1000 VOLTS (AUTO RANGING) (ACCURACY: 1%RDG+- 5 COUNTS). 5. DC VOLTS RANGE SHALL BE 0-1000 VOLTS (AUTO RANGING) (ACCURACY: 1%RDG+- 5 COUNTS). 6. CONTINUITY RESIARANCE RANGE SHALL BE =30 AND CONTINUITY BUZZER WITH BUZZER SOUNDS
Technical Parameter 2	7. RESISTANCE RANGE SHALL BE 0 T0 60 K. 8. FREQUANCY RANGE SHALL BE 0 T0 500 HZ. 9. DIAMETER OF MEASURABLE CONDUCTOR (JAW OPENING) SHALL BE 34MM (APPROX). 10. OPERATING TEMPERATURE RANGE SHALL BE -10C TO 50C (APPROX.). 11. INRUSH INTEGRATION TIME SHALL BE: 100MS. 12. RESOLUTION SHALL BE 0.1A OR 0.1V 13. WEIGHT SHALL BE 400G (APPROX.).
Technical Parameter 3	14. DISPLAY HOLD MAX/MIN BACKLIGHT LED DISPLAY. 15. ACCESSORIES SHALL BE TEST LEAD BATTERY I-FLEX FLEXIBLE CURRENT PROBE CARRYING CASE AND INSTRUCTION MANUAL. 16. SAFETY STANDARD SHALL BE EN/IEC 61010-1:2001; 1000V CAT III OR EQUIVALENT 17. WARRANTY SHALL BE THREE YEARS OF INSTRUMENT AND ACCESSORIES. 18. VENDOR SHALL SUBMIT THE WARRANTY AND CALIBRATION CERTIFICATE WITH CALIBRATION DATE."

$Product\ Specification\ for\ Metravi\ Category\ III\ 1000\ V\ of\ IEC\ 61010\ Not\ Available\ Insulation\ Tester$

विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
	Туре	Hand Held
	Measurement Range	0.01 M Ohm to 10 G Ohm
PERFORMANCE	Measurement Accuracy	4 percent
PERFORMANCE	Measurement Resolution	0.1 megaOhm
	Test Voltage	1000 Volt
	Test Current	2 milliAmpère
	AC/DC Voltage Measurement (Volt)	600
OTHER MEASUREMENT	AC/DC Voltage Measurement Resolution (Volts)	0.1
	AC/DC Voltage Measurement Accuracy (%)	2.0
	Pass Fail Function	No
	Data Logging	NA
	PC interface along with suitable & driven software	Not Available
FEATURES	Live Circuit Detection	inhibit test terminal voltage >30 V prior to initialization of test
	Auto Discharge Time (Second)	Less than 0.5
	Any Other Features	Auto Range
CENEDIC	Dimensions (mm x mm x mm)	175×110×62.5
GENERIC	Weight	580 gram
SAFETY	Safety rating	Category III 1000 V of IEC 61010
	Power Requirements	Battery Operated
	Type of Battery	Non- Rechargeable (Alkaline)
	if rechargeable , then chemistry of the battery	NA
POWER REQUIREMENT	if Non-rechargeable , then size of the battery / cell	AA

	Number of non- rechargeable the battery / cell	4
	Voltage of rechargeable Battery	0 Volt
	Capacity of rechargeable battery (milli ampere hour)	0
ACCESSORIES	Standard Accessories Supplied with the Equipment	Test probe
WARRANTY	Warranty	1 year
	Minimum Operating Temperature	-10 degree Celsius
OPERATING CONDITION	Maximum Operating Temperature	55 degree Celsius
	Operating Humidity (RH)	90 percent
	The equipment supplied with calibration certificate	YES
	conformity to Dry Heat for 16 hrs at a specified maximum temp	No
	conformity to Cold Test for 4 hrs at a specified minimum temp in accordance with IS:9000/part- 2/section-4/1977 latest	No
TEST REPORT DETAILS	conformity to Damp Heat (Cyclic)Test for 2 Cycles of 24 hours each at a temp of 40 degree C & 95% RH	No
	Availability of Test Reports from Central Govt/NABL/ILAC approved accredited lab to prove conformity to the specification	No
	Test Report Number and date for the specification test	NA
	Name and address of the Lab for the specification test	NA

टिप्पणी | Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

खरीदार परिभाषित अतिरिक्त विशिष्टता के लिए |Buyer Defined Additional Specification for Metravi Category III 1000 V of IEC 61010 Not Available Insulation Tester

विनिर्देश Specification	मूल्य Value
Technical Sheet 1	"1 KV INSULATION TESTER BATTERY OPERATED TEST RANGE UPTO 10 GOHM AND TEST VOLTAGES 50 V 100 V 250 V 500 V 1000 VALONG WITH VOLTAGE CONTINUITY AND RESISTANCE MEASUREMENT FUNCTION AND AS PER ATTACHED DETAILED SPECIFICATION 1 KV INSULATION TESTER BATTERY OPERATED
Technical Sheet 2	TEST RANGE- 0.01 M TO 10 G TEST VOLTAGES - 50 V 100 V 250 V VOLTAGE MEASUREMENT-0.1 V TO 600 V (AC/DC) RESISTANCE - 0.01 OHM TO 20.00 KOHM CONTINUITY -200MA OVERVOLTAGE CATAGORY-CAT IV 600 V

ईपीबीजी विवरण | ePBG Detail

सलाहकार बैंक Advisory Bank :	NA
ईपीबीजी प्रतिशत (%) ePBG Percentage(%):	

नियम और शर्तें|Terms and Conditions

- 1. General Terms and Conditions-
- 1.1 This contract is governed by the General Terms and Conditions, conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable
- 2. Buyer Added Bid Specific Terms and Conditions-
- 2.1 Generic

OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 25 percent of bid quantity at the time of placement of contract. The purchaser also reserves the right to increase the ordered quantity by up to 25% of the contracted quantity during the currency of the contract at the contracted rates. Bidders are bound to accept the orders accordingly.

2.2 Scope of Supply:

Scope of supply (Bid price to include all cost components): Only supply of Goods

2.3 Buyer Added Bid Specific ATC:

Buyer Added text based ATC clauses

*Vendor has to submit seal and signed Tender Documents.

*Vendor has to submit technical brochure along with tender documents.

*Vendor may use TReDS payment.	
2.4 Buyer Added Bid Specific ATC:	
Buyer uploaded ATC document <u>Click here to view the file</u> .	
2 - C - 2 - 3 - 2 - C	
नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिटे आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।	
Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.	