

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687751437527

अनुबंध तिथि | Generated Date : 08-Apr-2024

बोली/आरए/पीबीपी संख्या | Bid/RA/PBP No.: [GEM/2024/B/4420498](#)

| संगठन विवरण Organisation Details | खरीदार विवरण Buyer Details |
|---|--|
| प्रकार Type : Central PSU मंत्रालय Ministry : Ministry of Social Justice and Empowerment विभाग Department : Department of Social Justice and Empowerment संगठन का नाम Organisation Name : Artificial Limbs Manufacturing Corporation of India (ALIMCO) कार्यालय क्षेत्र Office Zone: Hq, Kanpur | पद Designation : Dy MANAGER संपर्क नंबर Contact No. : 0512-2770873- ईमेल आईडी Email ID : bycon4.alimco.kanpur@gembuyer.in जीएसटीआईएन GSTIN : - पता Address : ALIMCO, G. T. ROAD, NARAMAU, KANPUR - 209217, KANPUR NAGAR, UTTAR PRADESH-209217, India |

| वित्तीय स्वीकृति विवरण Financial Approval Detail | भुगतान प्राधिकरण विवरण Paying Authority Details |
|---|--|
| आईएफडी सहमति IFD Concurrence : No प्रशासनिक अनुमोदन का पदनाम Designation of Administrative Approval: DGM PD वित्तीय अनुमोदन का पदनाम Designation of Financial Approval: SM FA | Role: PAO भुगतान का तरीका Payment Mode: Internet Banking पद Designation : ASSISTANT MANAGER(FINANCE) ईमेल आईडी Email ID : jm4_fa@alimco.in जीएसटीआईएन GSTIN : N पता Address: ALIMCO, G. T. ROAD, NARAMAU, KANPUR - 209217, KANPUR CITY, UTTAR PRADESH-209217, India |

| विक्रेता विवरण Seller Details | |
|--|--|
| जेम विक्रेता आईडी GeM Seller ID : 895A180000100878 कंपनी का नाम Company Name : GLYNC TECH PRIVATE LIMITED संपर्क नंबर Contact No. : 09910009981 ईमेल आईडी Email ID : prashar.rahul@gmail.com पता Address : B-1/A-26, MOHAN CO-OPERATIVE INDS. ESTATE, MATHURA ROAD, BADARPUR, NEW DELHI, DELHI-110044, - एमआईआई स्थिति MII Status : True एमएसएमई सत्यापित MSME verified : Yes एमएसएमई पंजीकरण संख्या MSME Registration number : UDYAM-DL-09-0002780 एमएसएमई सामाजिक श्रेणी MSE Social Category : General एमएसएमई लिंग श्रेणी MSE Gender : Male जीएसटीआईएन GSTIN: 07AAGCG0244D1Z4 | |

*जिसके नाम के पक्ष में GST/TAX इनवाइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Buyer

वितरण निर्देश | Delivery Instructions : NA

| # | आइटम विवरण Item Description | आइटम विवरण Ordered Quantity | इकाई Unit | इकाई मूल्य (INR) Unit Price (INR) | कर विभाजन (INR) Tax Bifurcation (INR) | मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR) |
|--|--|-------------------------------|-------------|-------------------------------------|---|---|
| 1 | उत्पाद का नाम Product Name : GLYNC 36W Led Recessed Luminaire ब्रांड Brand : GLYNC ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: OEM verified catalogue कैसे बेचा जा रहा है Selling As : OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : LED Luminaire (Recessed Luminaire) (V2) (Q3) मॉडल Model: GLYNC - CAL036 एचएसएन कोड HSN Code: 94054090 | 50 | pieces | 1,023 | NA | 51,150 |
| कुल ऑर्डर मूल्य Total Order Value (in INR) | | | | | | 51,150 |

| परोक्षी विवरण Consignee Detail | | | | | | |
|----------------------------------|---------------------|--------------|--------------------|-------------------|---|--|
| क्र.सं. S.No | परोक्षी Consignee | वस्तु Item | लॉट नंबर Lot No. | मात्रा Quantity | दिलोके के बाद डिलीवरी शुरू करना है Delivery Start After | वितरण पूरा कब तक करना है Delivery To Be Completed By |
| | | | | | | |

| | | | | | | |
|---|--|-------------------------------------|---|----|-------------|-------------|
| 1 | ईमेल आईडी Email ID : shipping_mm@alimco.in संपर्क Contact : 0512-2770873- जीएसटीआईएन GSTIN : 09AABCA8899F1Z6 पता Address : ALIMCO, G. T. ROAD, NARAMAU, KANPUR - 209217, KANPUR NAGAR, UTTAR PRADESH-209217, India | GLYNC 36W Led Recessed Luminaire | - | 50 | 08-Apr-2024 | 23-Apr-2024 |
|---|--|-------------------------------------|---|----|-------------|-------------|

Product Specification for GLYNC 36W Led Recessed Luminaire

| विनिर्देश Specification | उप-विनिर्देश Sub-Spec | मूल्य Value |
|----------------------------------|--|---|
| Standards | Conformity to Indian Standard | IS:10322/part 5/sec-2/2012 and IS 16107 (Part 2/Sec 1) : 2012 for Recess type |
| | Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group) | Yes |
| | DC or AC supplied electronic control gear for LED Module shall comply as per IS:15885 (Part 2/Sec.13) | Yes |
| | Luminaire Class (as per Cl. 2.1 Section 2 of IS: 10322 (Part-1) | Class I |
| | Types of LED Modules as per the IS: 16103(Part-2)/2012 | Type 3 |
| | Rating of Recess type LED Luminaire/System Wattage/Rated Power | 36W |
| | Light Intensity(System Lumens) 80 Lm/Watt for 3000 deg K, 90 Lm/Watt for 4000 deg K, 100 Lm/Watt for 6000 deg K | Yes |
| | Color temperature (+/- 500 K) | 6000 deg K |
| Type of fixture (in feet) | 2x2(30W to 48W) | |
| Constructional | Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest (Minimum) | IP20 |
| | Mounting Type | Recess Type |
| | Diffuser Material | Poly carbonate (UV Stabilized) |
| | The luminaire body must be corrosion resistant epoxy powder coated / anodizing | Yes |
| | All fastners must be of nickel/chrome plated | Yes |
| | Number of electronic control gear (power supplies) | 1 |
| | Light Source | SMD LED Chip as per LM 80/IS16106 |
| Warranty for free replacement | 2 Years | |
| Electrical Efficiency Management | Operating Voltage and frequency range | 140V to 280 V at 50 Hz AC |
| | Rated Voltage | 230 V AC 50 Hz |
| | AC Power Factor | >/=0.90 |
| | Driver Efficiency | >/=85 |
| | Total Harmonics Distortion (</=20% (for upto 20W) (</=10% (for above 20W) | Yes |
| | The total circuit power shall not be more than 110 percent of the value declared by the manufacturer (as per Cl 8 of IS:16104:2012 latest) | Yes |
| Optical Management | LED chip Efficacy (>/=130 Lm/Watt for 6000 deg K, >/=120 Lm/Watt for 4000 deg K, >/=110 Lm/Watt for 3000 deg K) | Yes, with higher efficacy >/=140 Lm/Watt |
| | Working life for LED : (Minimum 50,000 burning hours as per LM-80 report) | Yes |
| | Color Rendering Index(CRI) | >/=80 |
| | Beam Angle | >/=120 |
| | Reflector type | Diffuser |
| Thermal Management | Fixture / Luminaire should be die-cast aluminium /CRCA/Extruded Aluminium | Yes |
| | Capacitor shall be rated for a temperature of 105 deg. Celsius or better | Yes |
| | Junction temperature / soldering temperature | < 85 deg C |
| | Operating temperature range | -10 deg. C to +50 deg. C |
| | Humidity Range | 10 % to 95% RH |
| | Short circuit Protection | Yes |
| | Over Load Protection | Yes |
| | High voltage test (1.5 KV for one minute between supply terminals | Yes |

| | | |
|----------------------------|--|---|
| Protection | and body of the unit) | |
| | Insulation resistance between earth and current carrying part | Yes |
| | The luminaire shall be protected against surges and transients of >/=2.5 KV | Yes |
| Marking | Manufactures Name and brand shall available on the body of the Luminaire | Engraved/Embsded |
| | Each LED liminaire shall have the manufacturer's name, model number, serial number, date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box | Yes |
| | The operation characteristics such as rated voltage and rated power in watts shall be marked inside each LED luminaire unit | Yes |
| Reports and Certifications | LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government LAB /NABL/ILAC accredited lab Reports shall be furnish to the buyer on demand (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc) | Yes |
| | LM 80 &TM21(Ref. IS:16105:2012) Report and Photo biological report for LED report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer on demand (LM-80 report shall have the Photo Biological report of the LED | Yes |
| | Availability of test Report from Central Government Lab /NABL/ILAC accredited lab to Indian Standrad IS:10322/part 5/sec-2/2012 and IS 16107 (Part 2/Sec 1) : 2012 | Yes |
| | Seller has to furnish Type test report to the buyer on demand | Yes |
| | DC or AC supplied electronic control gear for LED Module shall comply as per IS:15885 (Part 2/Sec.13) | Yes |
| | LED Luminaire for rcess type shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 2): 2012 as applicable on date | Yes |
| | LED Make | EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / SEOUL / SAMSUNG / OSRAM / REFOND / NICHIA / CREE / LUMILEDS / PHILIPS / SYSKA / LUMENMAX, Other than EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / SEOUL / SAMSUNG / OSRAM / REFOND / NICHIA / CREE / LUMILEDS / PHILIPS / SYSKA / LUMENMAX |

शुद्धिपत्र | Corrigendum

1. तक बढ़ाया गया | Extended Upto : 2024-01-23 17:00:00
2. तक बढ़ाया गया | Extended Upto : 2024-01-30 14:00:00

ईपीबीजी विवरण | ePBG Detail

| | |
|---|----|
| सलाहकार बैंक Advisory Bank : | NA |
| ईपीबीजी प्रतिशत (%) ePBG Percentage(%): | NA |

नियम और शर्तें | Terms and Conditions

1. General Terms and Conditions-

- 1.1 This contract is governed by the [General Terms and Conditions](#), conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

2. Buyer Added Bid Specific Terms and Conditions-

2.1 Generic

OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 25 percent of bid quantity at the time of placement of contract. The purchaser also reserves the right to increase the ordered quantity by up to 25% of the contracted quantity during the currency of the contract at the contracted rates. Bidders are bound to accept the orders accordingly.

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.

