

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687749792031

अनुबंध तिथि | Generated Date : 28-May-2024

संगठन विवरण Organisation Details	खरीदार विवरण Buyer Details
प्ररूप Type : State Government मंत्रालय Ministry : - विभाग Department : Commercial Tax Department Uttar Pradesh संगठन का नाम Organisation Name : N/A कार्यालय क्षेत्र Office Zone: Lucknow	पद Designation : DC संपर्क नंबर Contact No. : 05452-202236- ईमेल आईडी Email ID : surendra.1581981@gov.in जीएसटीआईएन GSTIN : 09ALDA01080C1D7 पता Address : OFFICE OF THE DEPUTY COMMISSIONER COMMERCIAL TAX DEPARTMENT T.J COMPLEX NAIGANJ NEAR POLYTECHNIC CHAURAHA, JAUNPUR, UTTAR PRADESH-222001, India

वित्तीय स्वीकृति विवरण Financial Approval Detail	भुगतान प्राधिकरण विवरण Paying Authority Details
आईएफडी सहमति IFD Concurrence : No प्रशासनिक अनुमोदन का पदनाम Designation of Administrative Approval: DEPUTY COMMISSIONER COMMERCIAL TAX DEPARTMENT वित्तीय अनुमोदन का पदनाम Designation of Financial Approval: DEPUTY COMMISSIONER COMMERCIAL TAX DEPARTMENT	Role: BUYER भुगतान का तरीका Payment Mode: Offline पद Designation : DC ईमेल आईडी Email ID : surendra.1581981@gov.in जीएसटीआईएन GSTIN : 09ALDA01080C1D7 पता Address : OFFICE OF THE DEPUTY COMMISSIONER COMMERCIAL TAX DEPARTMENT T.J COMPLEX NAIGANJ NEAR POLYTECHNIC CHAURAHA, Jaunpur, UTTAR PRADESH-222001, India

विक्रेता विवरण Seller Details
जेम विक्रेता आईडी GeM Seller ID : BB87190001047016 कंपनी का नाम Company Name : M/S BIMALA ENTERPRISES संपर्क नंबर Contact No. : 08953465386 ईमेल आईडी Email ID : bimalaenterprises4d@gmail.com पता Address : 3RD FLOOR, DHARMA VILLA, WAZIDPUR TIRAH, HUSSAINABAD, Jaunpur, UTTAR PRADESH-222002, - एमएसएमई पंजीकरण संख्या MSME Registration number : UDYAM-UP-38-0008801 एमएसई सामाजिक श्रेणी MSE Social Category : General एमएसई लिंग श्रेणी MSE Gender : Male जीएसटीआईएन GSTIN: 09AVYPM9204D1Z4 (R)

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Buyer

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण Product Details						
#	आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : Unbranded Free standing PARTITION PANEL Conformity to technical requirements ब्रांड Brand : NA ब्रांड प्रकार Brand Type : Unbranded कैटलॉग की स्थिति Catalogue Status : Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Free standing PARTITION PANEL (Q3) मॉडल Model : Aluminium partition एचएसएन कोड HSN Code : HSN not specified by seller	225	square foot	108	NA	24,300
कुल ऑर्डर मूल्य Total Order Value (in INR)						24,300

परेषिती विवरण Consignee Detail						
क्र.सं. S.No	परेषिती Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा कब तक करना है Delivery To Be Completed By

1	<p>पद Designation : DC ईमेल आईडी Email ID : surendra.1581981@gov.in संपर्क Contact : 05452-202236- जीएसटीआईएन GSTIN : 09ALDA01080C1D7 पता Address : OFFICE OF THE DEPUTY COMMISSIONER COMMERCIAL TAX DEPARTMENT T.J COMPLEX NAIGANJ NEAR POLYTECHNIC CHAURAHA, JAUNPUR, UTTAR PRADESH-222001, India</p>	Unbranded Free standing PARTITION PANEL Conformity to technical requirements	-	225	28-May-2024	12-Jul-2024
Product Specification for Unbranded Free standing PARTITION PANEL Conformity to technical requirements						
विनिर्देश Specification		उप-विनिर्देश Sub-Spec	मूल्य Value			
GENERIC	Product utility		For open plan office layout			
	Elevation of Panels from ground (with legs) by		40 millimeter			
	Panel thickness		52.4 mm (having cable management facility), 22.8 mm (no cable management ability)			
	Provisions for Panels to form any geometric configurations Hint : Panels can be connected together with various post connectors in many geometric configurations		Yes			
	Panel structure Hint : Panels are supported on legs with levellers at various locations (depending on the layout requirements)		For 52.4 mm – 2 nos. Vertical trim + Horizontal trims (at every division of blocks/tiles) + Blocks (for intermediate panels) + 1 no. of fabricated bottom frame (welded structure) + bottom tiles + top tiles + 1 no. of top trim, For 22.8 mm – 2 nos. Vertical trim + Horizontal trims (at every division of blocks/tiles) + Blocks (Intermediate/Top/Bottom) + 1 no. of top trim + 1 no. of end trim + 1 no. of end trim's cap			
	Additional requirement		N.A			
MATERIAL	Vertical (uprights) and Horizontal trim made of Hint : Blocks and metal frame are held together by uprights at both ends of the panel and horizontals between each block and tile		Aluminium extrusions having material AL96063-T6 and average wall thickness of 1.2 mm and powder coated with epoxy-polyester powder			
	Blocks made out of		Particle board with laminate – (Laminate Block- 38 mm Honeycomb+ 3 mm MDF both side + 0.6 Laminate)			
	Bottom frame (welded structure) comprises of		L – channels made of 2 mm thick CRCA conforming to IS 513 + formed plates of 3 mm thick Hot rolled steel conforming to IS 2062 and ERW steel tube of size 35 mm x 15 mm x 1.6 mm thick in oval cross section conforming to IS 7138 welded together and bolted to the uprights by screws			
	Top and End trim made of		Aluminium extrusions			
	End trim's cap made of		Aluminium casting			
	Brackets made of		Full gable end bracket made from 1.2 mm thick MS CRCA grade D conforming to IS 513, Work surface bracket and Holder bracket made from 2 mm thick CRCA grade D steel conforming to IS 513 - 19			
	Bracket sizes/width		450 mm, 600 mm, 750 mm			
	Panel legs (used for supporting panels) made of		Fabricated by CO2 welding 38 mm x 25 mm x 16 bg conforming to IS 7138			
	Panel legs (single side) size for 52[dot]4 mm panel thickness (tolerances : +/- 10 mm) Hint : select 'NA' if single side panel legs (for 52[dot]4 mm panel thickness) not required		N.A			
	Panel legs (double side) size for 52[dot]4 mm panel thickness (tolerances : +/- 10 mm) Hint : select 'NA' if double side panel legs (for 52[dot]4 mm panel thickness) not required		1255 mm			
DIMENSIONS	Height of assembled panels - with legs including top trim and glide screws (tolerances : +/- 10 mm)		4 foot			
	Width of assembled panels Hint : In pitch of 6 inches		1.00065695589787 foot			
	Blocks for 52[dot]4 mm panel thickness Hint : these blocks are located in mid segment of the panels and can be provided with cut outs for mounting switch boxes (above or below the work tops)		Comprises of 38 mm thick paper honeycomb + 3 mm MDF on each sides + 0.6 mm fabric on both sides – Particle board framing used on outer boundary of these blocks as well as intermediately at certain locations forming conduit for passing cables			
	Top tiles finish for 52[dot]4 mm panel thickness Hint : These tiles are slide in to the panels from top before fixing the top horizontal and supported from top and bottom side with clips fitted in horizontal extrusion		Plain metal tiles (0.6 mm thick MS CRCA Grade D Conforming to IS 513 powder coated with Epoxy – polyester finish)			
	Height of Top tiles for 52[dot]4 mm panel thickness					

PANEL COMPONENTS

(tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	N.A
Width of Top tiles for 52[dot]4 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	1035 mm
Split Top tiles for 52[dot]4 mm and 22[dot]8 mm panel thickness Hint : For two different finishes in single panels	Not available
Height of Split top tiles for 52[dot]4 mm and 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes (according to panel height) are including the fabric or edge banding thickness if applicable	N.A
Width of Split top tiles for 52[dot]4 mm and 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	N.A
Bottom tiles finish for 52[dot]4 mm panel thickness Hint : Bottom tiles are press fitted on to the assembly frame of the panel with the help of snap on clips – Switches can be mounted on these bottom tiles as per buyer's requirement	N.A
Height of Bottom tiles for 52[dot]4 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	N.A
Width of Bottom tiles for 52[dot]4 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	280 mm
Bottom Blocks for 22[dot]8 mm panel thickness	N.A
Height of Bottom Blocks for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	N.A
Width of Bottom Blocks for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	285 mm
Intermediate Blocks for 22[dot]8 mm panel thickness	Laminate finish(made from 18 mm thick particle board)
Height of Intermediate Blocks for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	N.A
Width of Intermediate Blocks for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	735 mm
Top Blocks for 22[dot]8 mm panel thickness	White board finish (made of 16 mm thick particle board laminated with 0.6 mm thick white glossy high pressure laminate on both sides and having all its edges with minimum 0.5 mm thick PVC edging)
Height of Top Blocks for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	375 mm
Width of Top Blocks for 22[dot]8 mm panel thickness (tolerances : +/- 10 mm) Hint : sizes are including the fabric or edge banding thickness if applicable	1335 mm
End panel 22[dot]8 mm (off module fixing) Hint : used to connect 22[dot]8 mm panel and 52[dot]4 mm panel at the centre of 22[dot]8 mm panel	Not available
Height of End panel 22[dot]8 mm (tolerances : +/- 10 mm) Hint : This can be used in aisle conditions only	1200 mm
Width of End panel 22[dot]8 mm (tolerances : +/- 10 mm) Hint : This can be used in aisle conditions only	N.A
Bottom screen of end panel 22[dot]8 mm (off module fixing)	Metal finish blocks (made from two components – both components are 0.8 mm thick M.S. CRCA Grade D conforming to IS 513 powder coated with epoxy polyester finish and fastened together using M6 nutserts)
Top screen of end panel 22[decimal]8 mm (off module fixing)	N.A
Panel joinery / Posts (22[decimal]8 mm panels cannot be	

	interconnected – these are joined as fin panels to 52[decimal]4 mm panels only using fin posts) Hint : panel can be joined to each other directly with 180 degree joinery or with help of post to	4 way 90 degree
	Stability post – according to unit height - to avoid movement of free standing panels (tolerances : +/- 10 mm) Hint : End trim fixing is not required alongwith stability post	1350 mm (for 4.5 feet unit height)
WARRANTY	Warranty period in number of years	1
CERTIFICATION	Test reports to be furnished to buyer's on demand	1. Yes
	OEM of offered product is ISO 9001:2015 certified	Yes
	OEM of offered product is ISO 14001:2015 certified	No
	OEM of offered product is ISO 18001:2007/45001:2018 certified	No
टिप्पणी Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.		
ईपीबीजी विवरण ePBG Detail		
NA		
नियम और शर्तें Terms and Conditions		
1. General Terms and Conditions-		
1.1 This contract is governed by the General Terms and Conditions , conditions stipulated to this Product/Service as provided in the Marketplace.		
1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable		
नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।		
Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.		