

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687780703789

अनुबंध तिथि | Generated Date : 28-May-2024

बोली/आरए/पीबीपी संख्या | Bid/RA/PBP No.: [GEM/2024/B/4940175](#)

संगठन विवरण Organisation Details		खरीदार विवरण Buyer Details	
प्ररूप Type :	State Autonomous	पद Designation :	Executive officer
मंत्रालय Ministry :	-	संपर्क नंबर Contact No. :	-
विभाग Department :	Housing and Urban Development Department Jammu and Kashmir	ईमेल आईडी Email ID :	eobasholi-jk@nic.in
संगठन का नाम Organisation Name :	N/A	जीएसटीआईएन GSTIN :	N
कार्यालय क्षेत्र Office Zone:	Directorate Of Urban Local Bodies Jammu	पता Address :	OFFICE OF THE MUNICIPAL COMMITTEE BASOHLI, KATHUA, JAMMU & KASHMIR-184201, India

वित्तीय स्वीकृति विवरण Financial Approval Detail		भुगतान प्राप्तिकरण विवरण Paying Authority Details	
आईएफडी IFD Concurrence :	No	Role:	BUYER
प्रशासनिक अनुमोदन का पदनाम	EXECUTIVE OFFICER	भुगतान का तरीका	Offline
Designation of Administrative Approval:		Payment Mode:	
वित्तीय अनुमोदन का पदनाम	EXECUTIVE OFFICER	पद Designation :	Executive officer
Designation of Financial Approval :		ईमेल आईडी Email ID :	eobasholi-jk@nic.in
		जीएसटीआईएन GSTIN :	N
		पता Address:	OFFICE OF THE MUNICIPAL COMMITTEE BASOHLI, KATHUA, JAMMU & KASHMIR-184201, India

विक्रेता विवरण Seller Details	
जेम विक्रेता आईडी GeM Seller ID :	CBE7180000615672
कंपनी का नाम Company Name :	SHAM LAL AND SONS
संपर्क नंबर Contact No. :	09419151595
ईमेल आईडी Email ID :	pankaj.dogra9@gmail.com
पता Address :	01,NAGRI ROAD,opp. DIST JAIL,KATHUA, Kathua, JAMMU & KASHMIR-184101, -
एमएसएमई पंजीकरण संख्या MSME Registration number :	UDYAM-JK-09-0003199
एमएसई सामाजिक श्रेणी MSE Social Category :	General
एमएसई लिंग श्रेणी MSE Gender :	Male
जीएसटीआईएन GSTIN:	01AKPPS8374Q1Z5 (R)

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Buyer

वितरण निर्देश Delivery Instructions : NA	
--	--

#	आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : Unbranded Yes WLed Luminaire Light ब्रांड Brand : NA ब्रांड प्रकार Brand Type : Unbranded कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्भास Category Name & Quadrant : LED Luminaire (for Road and Street Lights) as per IS 10322, IS 16107, IS 16108, IS 16103, IS 10322 (Q3) मॉडल Model: SSK-ST-45W-S एचएसएन कोड HSN Code: HSN not specified by seller	50	pieces	1,775	NA	88,750
2	उत्पाद का नाम Product Name : Unbranded 100 meter Single Core Flexible Copper Cable ब्रांड Brand : NA ब्रांड प्रकार Brand Type : Unbranded कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्भास Category Name & Quadrant : Multicore Cable as per IS 694 (Q3) मॉडल Model: 1.5Sq mm Single Core Cable एचएसएन कोड HSN Code: HSN not specified by seller	10	pieces	2,050	NA	20,500
3	उत्पाद का नाम Product Name : Unbranded Yes WLed Luminaire Light ब्रांड Brand : NA ब्रांड प्रकार Brand Type : Unbranded कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्भास Category Name & Quadrant : LED Luminaire (for Road and Street Lights) as per	80	pieces	525	NA	42,000

IS 10322, IS 16107, IS 16108, IS 16103, IS 10322 (Q3) मॉडल Model: SSK-ST-45W-S एचएसएन कोड HSN Code: HSN not specified by seller										
कुल ऑर्डर मूल्य Total Order Value (in INR)										
परेष्ठी विवरण Consignee Detail										
क्र.सं. S.No	परेष्ठी Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After					
1	पद Designation :- ईमेल आईडी Email ID : eobasholi-jk@nic.in संपर्क Contact :- जीएसटीआईएन GSTIN : N पता Address : OFFICE OF THE MUNICIPAL COMMITTEE BASOHLI, KATHUA, JAMMU & KASHMIR-184201, India	Unbranded Yes WLed Luminaire Light	-	50	28-May-2024					
		Unbranded 100 meter Single Core Flexible Copper Cable	-	10	28-May-2024					
		Unbranded Yes WLed Luminaire Light	-	80	28-May-2024					
Product Specification for Unbranded Yes WLed Luminaire Light										
विवरण Specification	उप-विवरण Sub-Spec	मूल्य Value								
STANDARDS	LED Luminaire conformity to IS:10322/Part 5/Section 3/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest	Yes								
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes								
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec.-1)/2012	Type B								
	Types of LED Modules as per the IS:IS: 16103(Part-2)/2012	Type 3								
	LED Rating (in Watts)/System Wattage/Rated Power	45W								
	Luminaire System Efficacy (Lumen/watt)	>/= 100 Lm/Watt								
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP65								
ELECTRICAL EFFICIENCY	Warranty for free replacement (in years)	2								
	Input operating Voltage range and frequency	90 to 300 Volts AC at 50 Hz+/-2								
	Automatic Higher Cut off voltage above 300 volt	Yes								
	Rated voltage	240 V AC 50 Hz								
	AC Power Factor at full load	≥ 0.95								
	Driver Efficiency (in %age) Upto 100W: ≥85%, Above 100W: >/=90%	Yes								
	Total Harmonics Distortion	≤ 10								
OPTICAL	"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer (as per Cl. 8 of IS:16104:2012 lates)"	Yes								
	LED chip Efficacy	≥130 Lm/Watt								
	Colour temperature	6000+/-500K								
	Working life for LED (Minimum 50,000 burning hours as per LM-80 and LM 21 reports)	Yes								
	Colour Rendering Index(CRI)	≥70								
	LED Beam Angle	≥120								
	Optic lense material (UV stabilised)	Poly carbonate lense								
THERMAL MANAGEMENT	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes								
	Junction / Soldering point temperature shall not exceed 85 deg.c as per LM 80 report	Yes								
	Capacitor shall be rated for a temperature of 105 deg. celsius or better	Yes								
	Operating temperature range	-10 deg C to +50 deg C								
	Operating Humidity Range	10 % to 95% RH								
	Short circuit Protection	Yes								
	Over load protection	Yes								
	Over Voltage protection	Yes								
	Reverse polarity	Yes								

PROTECTION	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes
	Insulation resistance between earth and current carrying part	>100 M Ohm
	The luminaire shall be protected against surges and transients (Internal)	>/=5KV
	The luminaire shall be protected against surges and transients of >/=10KV (External)	No
CONSTRUCTIONAL	The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity	Yes
	The luminaire body must be corrosion resistant powder coated	Yes
	All fastners must be of stainless steel	Yes
	Protection of the entire housing (both LED section and driver section) as per IS:10322 (Part 1):1982 latest	IP66
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes
	Luminaries light transparency should be of Toughened glass	Yes
	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degradation due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	1 No.
	Light Source	SMD LED Chip as per LM 80/IS16106
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
MARKING	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	50 cm
	"Manufactures Name and and brand on the aluminium die cast body "	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
Reports And Certifications	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
	Diameter of pole Luminiare suitable for: (upto 45W Pole OD: shall be 40mm), (>45W<120W Pole OD: Shall be 50 mm), (above 120W: OD shall be 60 mm for which luminiare is suitable	Yes
	LED Make	OSRAM / NICHIA / CREE / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish to the buyer / consignee on demand)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer / consignee on demand (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,	Yes
	LM 80 & TM 21 (Ref. IS:16105:2012) Report and Photo biological report for LED report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer / consignee on demand (LM-80 report shall have the Pohoto Biological re	Yes
	Availability of test Report from Central Government Lab /NABL/ILAC accredited lab to Indian Standrad IS:10322/part 5/sec-3/2012 and IS 16107 (Part 2/Sec 1) : 2012	Yes
	Seller shall furnish the Type test reports to the buyer / consignee on demand	Yes
DC or AC supplied electronic control gear for LED Module shall comply as per IS:15885 (Part 2/Sec.13)		
LED Luminaire for road and street lighting shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 3): 2012 as applicable on date		

टिप्पणी | Note: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

Product Specification for Unbranded 100 meter Single Core Flexible Copper Cable

विवरण Specification	उप-विवरण Sub-Spec	मूल्य Value
Standards And Certification	Certification	IS-694:(Latest)
General Features	Nominal Thickness Of Insulation	0.5 millimeter
	Pack Type	Carton Packing
	Current Rating in Amps	7 Ampère
	Warranty	12 month
	No. Of Cores	Single Core
	Type Of Product	Flexible Copper Cable
	Nominal Area in Sq mm	1.5
	Voltage, Volts	1100 Volt
	Color	Red
	Number Of Strands	14
	Conductor Material	Copper
	Cable Length	100 meter

टिप्पणी|Note: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

Product Specification for Unbranded Yes WLed Luminaire Light

विवरण Specification	उप-विवरण Sub-Spec	मूल्य Value
STANDARDS	LED Luminaire conformity to IS:10322/Part 5/Section 3/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest	Yes
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec.-1)/2012	Type B
	Types of LED Modules as per the IS:IS: 16103(Part-2)/2012	Type 3
	LED Rating (in Watts)/System Wattage/Rated Power	45W
	Luminaire System Efficacy (Lumen/watt)	>/= 100 Lm/Watt
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP65
	Warranty for free replacement (in years)	2
ELECTRICAL EFFICIENCY	Input operating Voltage range and frequency	90 to 300 Volts AC at 50 Hz+/-
	Automatic Higher Cut off voltage above 300 volt	Yes
	Rated voltage	240 V AC 50 Hz
	AC Power Factor at full load	≥ 0.95
	Driver Efficiency (in %age) Upto 100W: ≥85%, Above 100W: >/=90%	Yes
	Total Harmonics Distortion	≤ 10
	"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer (as per Cl. 8 of IS:16104:2012 latest)"	Yes
OPTICAL	LED chip Efficacy	≥130 Lm/Watt
	Colour temperature	6000+/-500K
	Working life for LED (Minimum 50,000 burning hours as per LM-80 and LM 21 reports)	Yes
	Colour Rendering Index(CRI)	≥70
	LED Beam Angle	≥120
	Optic lense material (UV stabilised)	Poly carbonate lense
THERMAL MANAGEMENT	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes
	Junction / Soldering point temperature shall not exceed 85 deg.c as per LM 80 report	Yes
	Capacitor shall be rated for a temperature of 105 deg. celsius or better	Yes
	Operating temperature range	-10 deg C to +50 deg C
	Operating Humidity Range	10 % to 95% RH

PROTECTION	Short circuit Protection	Yes
	Over load protecton	Yes
	Over Voltage protection	Yes
	Reverse polarity	Yes
	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes
	Insulation resistance between earth and current carrying part	>100 M Ohm
	The luminaire shall be protected against surges and transients (Internal)	>/=5KV
	The luminaire shall be protected against surges and transients of >/=10KV (External)	No
CONSTRUCTIONAL	The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity	Yes
	The luminaire body must be corrosion resistant powder coated	Yes
	All fastners must be of stainless steel	Yes
	Protection of the entire housing (both LED section and driver section) as per IS:10322 (Part 1):1982 latest	IP66
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes
	Luminaries light transparency should be of Toughened glass	Yes
	Toughned transparent glass cover thickness	>/=4 mm
	Toughned Glass shall not get discoloured shall not suffer degration due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	1 No.
	Light Source	SMD LED Chip as per LM 80/IS16106
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	50 cm
MARKING	"Manufactures Name and and brand on the aluminium die cast body "	Engraved/Embossed
	Manufacturer's name, model number, serial number	Yes
	Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box	Yes
	The operation characteristics voltage and power be marked inside of each LED luminaire unit	Yes
	Diameter of pole Luminiare suitable for: (upto 45W Pole OD: shall be 40mm), (>45W<120W Pole OD: Shall be 50 mm), (above 120W: OD shall be 60 mm for which luminiare is suitable	Yes
Reports And Certifications	LED Make	OSRAM / NICHIA / CREE / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish to the buyer / consignee on demand)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer / consignee on demand (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,	Yes
	LM 80 & TM 21 (Ref. IS:16105:2012) Report and Photo biological report for LED report from Central Government Lab /NABL/ILAC accredited lab. Reports shall be furnish to the buyer / consignee on demand (LM-80 report shall have the Pohoto Biological re	Yes
	Availability of test Report from Central Government Lab /NABL/ILAC accredited lab to Indian Standrad IS:10322/part 5/sec-3/2012 and IS 16107 (Part 2/Sec 1) : 2012	Yes
	Seller shall furnish the Type test reports to the buyer / consignee on demand	Yes
	DC or AC supplied electronic control gear for LED Module shall comply as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for road and street lighting shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 3): 2012 as applicable on date	Yes

टिप्पणी|Note: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are

being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

खरीदार परिभाषित अतिरिक्त विशेषता के लिए | Buyer Defined Additional Specification for Unbranded Yes WLed Luminaire Light

विवरण Specification	मूल्य Value
LED BULB 45WATTS	LED BULB 45WATTS

ईपीबीजी विवरण | ePBG Detail

सलाहकार बैंक Advisory Bank :	NA
ईपीबीजी प्रतिशत (%) ePBG Percentage(%):	NA

नियम और शर्तें| Terms and Conditions

1. General Terms and Conditions-

1.1 This contract is governed by the [General Terms and Conditions](#), conditions stipulated to this Product/Service as provided in the Marketplace.

1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

2. Buyer Added Bid Specific Terms and Conditions-

2.1 Generic

OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 25 percent of bid quantity at the time of placement of contract. The purchaser also reserves the right to increase the ordered quantity by up to 25% of the contracted quantity during the currency of the contract at the contracted rates. Bidders are bound to accept the orders accordingly.

2.2 Buyer Added Bid Specific ATC:

Buyer uploaded ATC document [Click here to view the file](#).

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.