अनुबंध|Contract



अनुबंध क्रमांक | Contract No: GEMC-511687720209042

अनुबंध तिथि | Generated Date : 03-Jun-2024

संगठन विवरण|Organisation Details

प्ररूप|Type: Central Government मंत्रालय|Ministry: Ministry of Education

Department of School Education and Literacy विभाग | Department :

संगठन का नाम|Organisation Name : Navodaya Vidyalaya Samiti

कार्यालय क्षेत्र|Office Zone: LUCKNOW

खरीदार विवरण|Buyer Details

पद|Designation: संपर्क नंबर|Contact No. :

ईमेल आईडी|Email ID: pao81.nvs.up@gembuyer.in

जीएसटीआईएन|GSTIN :

JAWAHAR NAVODAYA VIDYALAYA, GAURIGANJ, AMETHI, पता|Address:

Sultanpur, UTTAR PRADESH-227409, India

वित्तीय स्वीकृति विवरण | Financial Approval Detail

आईएफडी सहमित|IFD Concurrence

प्रशासनिक अनुमोदन का पदनाम|

PRINCIPAL, JAWAHAR NAVODAYA VIDYALAYA, GAURI Designation of Administrative GANJ, AMETHI

Approval:

वित्तीय अनुमोदन का पदनाम|

Designation of Financial PRINCIPAL.JNV GAURIGANJ,AMETHI

Approval:

भुगतान प्राधिकरण विवरण | Paying Authority Details

Role: BUYER

भुगतान का तरीका| Offline Payment Mode: पद|Designation : OS

ईमेल आईडी|Email ID : pao81.nvs.up@gembuyer.in

जीएसटीआईएन|GSTIN :

JAWAHAR NAVODAYA VIDYALAYA, GAURIGANJ, AMETHI, पता|Address:

Amethi, UTTAR PRADESH-227409, India

विक्रैता विवरण|Seller Details

जेम विक्रैता आईडी|GeM Seller ID : E009180000114004

SUPER PRINTERS AND TRADERS कंपनी का नाम|Company Name :

संपर्क नंबर|Contact No. : 09335145559

ईमेल आईडी|Email ID : wajahat.riyaz@gmail.com 754, MALVIYA NAGAR,, पता| Address :

ALLAHABAD, UTTAR PRADESH-211003, -

एमएसएमई पंजीकरण संख्या|MSME Registration number :

जीएसटीआईएन|GSTIN: 09AFXPA7748H1ZT (B), (R)

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा|GST / Tax invoice to be raised in the name of - Consignee

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण|Product Details

;	# आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name: Unbranded Polyester Blended with Cotton Woven Track Suits – Sports ब्रांड Brand: NA ब्रांड प्रकार Brand Type: Unbranded कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As: Reseller not verified by OEM श्रेणी का नाम और चतुर्थीश Category Name & Quadrant: Track Suit - Sports (Q3) मॉडल Model: Track Suit एचएसएन कोड HSN Code: HSN not specified by seller	240	pieces	524.95	NA	125,988
ć	कुल ऑर्डर मूल्य Total Order Value (in INR)					

परेषिती विवरण|Consignee Detail

क्र.सं. S.No	परेषिती Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा कब तक करना है Delivery To Be Completed By
1	पद Designation : Primary User ईमेल आईडी Email ID : ppl.amethi@navodaya.nic.in संपर्क Contact : - जीएसटीआईएन GSTIN : 09LKNJ05413C1D4 पता Address : JAWAHAR NAVODAYA VIDYALAYA,GAURIGANJ,AMETHI, Sultanpur, UTTAR PRADESH-227409, India	Unbranded Polyester Blended with Cotton Woven Track Suits – Sports	-	240	03-Jun-2024	18-Jun-2024

Fabric (Composition) Prolyester Blended v Percentage of Blending (in case of Blended Fabric) Polyester 50 % and Mass (gram per square mtrs) Pabric Construction Woven Weave (In case of Woven Fabric) Any other weave as per buyer's requirements (in case weave is other than already mentioned above) Knitting (In case of knitted Fabric) Not Applicable Ends per dm NA Courses per dm NA Courses per dm NA Count of knitting yarn NA Raising at inner side of Main Fabric Upper Lining No Lower Lining No Lining Material Mass of Lining (Gram per Square Meter) Netting mesh No of holes on base & bias within 625 Square millimeter Technical Requirements of Slide Fastener for Upper Closing Slide Fastners are BIS Marked Width of Tape Elastic at Waist of Trouser Width of Tape Elastic at Bottom of Upper	
Fabric (Composition) Percentage of Blending (in case of Blended Fabric) Percentage of Blending (in case of Blended Fabric) Polyester 50 % and Mass (gram per square mtrs) Pabric Construction Weave (in case of Woven Fabric) Plain Any other wave as aper buyer's requirements (in case weave is other than already mentioned Any other wave as aper buyer's requirements (in case weave is other than already mentioned NA Not Applicable Ends per dm NA Picks per dm NA Courses per dm NA Courses per dm NA Raising at inner side of Main Fabric Upper Uning Lower Lining No Not Applicable Not Applicable Technical Requirements of Slide Fastener for Upper Closing Technical Requireme	
Percentage of Blending (in case of Blended Fabric) Mass (gram per square mitrs) 500 gram Fabric Construction Weven Weave (in case of Woven Fabric) Any other weave as per buyer's requirements (in case weave is other than already mentioned above) Kinting (in case of Intitled Fabric) Entitle per din NA Picts per din NA Courses per dim NA Courses per dim NA Courses per dim NA Courses per dim NA Course of knitting yarn Raising at inner side of Main Fabric Upper Lining Lower Lining Lower Lining Lower Lining Lining Material Mess of Lining (Gram per Square Meteor) Netting mesh No of holes on base & bias within 625 Square millimeter Technical Requirements of Silde Fastener for Upper Closing Technical Requirements of Silde Fastener for Pocket Closing (for Pockets with Silde Fastener for Votage) Silde Fasteners are BIS Marked Width of Tape Elastic at Wass of Trouser Width of Tape Elastic at Wass of Trouser Width of Tape Elastic at Wass of Trouser Technical Requirements of Wast Band Wast Draw Cord Ends Braking Srangth of Draw Cord Seeve Ends (Cuff) Upper provided with Piping No Piping Fabric Composition Piping Fabric Carposition Piping Fabric Any other material as per buyer's requirements (Other than mentioned above) NA Piping Fabric Any other material as per buyer's requirements (Other than mentioned above) NA Piping Fabric Carposition Piping Fabric Carposition Piping Fabric Carposition No Not Applicable Enthrosidery Thread Enthrosidery Thread Lower Content of Dack to bottom of sleeve Steeve energy (Gedaum) Steeve English (Form center of back to bottom of sleeve Steeve pening relaxed (Cuff) Width Steeve length (From center of back to bottom of sleeve Steeve pening relaxed (Cuff) Width	onsisting of Upper and Lower
Mass gram per square mers) 300 gram Fabric Construction Woven Woven (In case of Woven Fabric) Pinin Any other weave as per buyer's requirements (in case weave is other than already mentioned above) Kritting (In case of knitted Fabric) Not Applicable Ends per dm NA Picks per dm NA Courses per dm NA Wales per dm NA Course of main Fabric Yes Upper Lining Lower Lining Lower Lining Lower Lining Mass of Lining (Gram per Square Meter) No Applicable MESSIAL M	ed with Cotton
Fabric Construction Woven Weave (In case of Woven Fabric) Plain Any other weave as per buyer's requirements (in case weave is other than already mentioned above) Kritting (In case of knitted Fabric) Not Applicable Ends per dm NA Picks per dm NA Picks per dm NA Courses per dm NA Raising at inner side of Main Fabric Yes Upper Lining No Lower Lining No And Applicable Technical Requirements of Silde Fastener for Upper Closing (For Pockets with Silde Fastener for Pocket Closing) Silde Fastener are BIS Marked Not Applicable Width of Tape Elastic at Watst of Trouser Width of Tape Elastic at Watst of Trouser Width of Tape Elastic at Watst of Trouser Width of Tape Elastic at Watst Band Watst Band Watst Dand Seperate Disperation No Breaking Strength of Drew Cord Proyer Cord Pocket Closing (For Pocket Separate Not Applicable) Breaking Strength of Drew Cord Proyer Cord Polypropylene Cord Polypropylene Cord Proyer Cord Separate Not Polypropylene Cord Polypropylene Cord Proyer Cord Separate Not Polypropylene Cord Polypropylene Cord Polypropylene Cord Proyer Cord Separate Not Piping No Lower provided with Piping No Piping Fabric Composition 100 per resturements (Other than mentioned above) Na Piping Fabric Composition 100 percent Polypet Immunity (Midth Across Chest 25 mm below under arm Middh Across Separate Polypet Serve (Medium) 46 cm (and Cotton 50 %
Weave (In case of Woven Fabric) Any other weave as per buyer's requirements (in case weave is other than already mentioned above) Not Applicable Ends per dm Not Applicable Ends per dm Not Applicable Courses per dm Not Applicable Courses per dm Not Applicable Raising at inner side of Main Fabric Upper Lining Lower Lining Lower Lining Lower Lining Mass of Lining (Gram per Square Meter) Netting mesh No of holes on base & blas within 625 Square millimeter Technical Requirements of Side Fastener for Pocket Closing (For Pockets with Side Fastner for dosing) Side Fastners are BIS Marked Width of Tape Elastic at Nottom of Upper Technical Requirements of Side Fastener for Pocket Closing (For Pockets with Side Fastner for Dyper Closing) Side Fastners are BIS Marked Width of Tape Elastic at Nottom of Upper Technical Requirements of Side Fastener for Pocket Closing (For Pockets with Side Fastner for Dyper Closing) Technical Requirements of Side Fastners for Pocket Closing (For Pockets with Side Fastner for Not applicable) Width of Tape Elastic at Nottom of Upper Technical Requirements of Waist Band Waist Draw Cord Draw Cord finds Breaking Svength of Draw Cord Sieve Ends (Cuff) Upper provided with Piping No Piping Fabric- Composition Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Seeve length (from center of back to bottom of sleeve Seeve length (from center of back to bottom of sleeve Seeve length (from center of back to bottom of sleeve	
Any other weave as per buyer's requirements (in case weave is other than already mentioned above) Kriting (in case of knitted Fabric) Ends per dm NA Picks per dm NA Courses per dm NA Wales per dm Count of knitting yarn Raising a knienr side of Main Fabric Upper Lining Lower Lining Lower Lining Lower Lining Gram per Square Meter) Not Applicable Netting mesh No of holes on base & bias within 625 Square millimeter Not Applicable Technical Requirements of Side Fastener for Pocket Closing (For Pockets with Side Fastener for design) Side Fasteners are BIS Marked Width of Tape Elastic at Walst of Trouser Width of Tape Elastic at Walst of Trouser Width of Tape Elastic at Bottom of Upper Technical Requirements of Walst Band Walst Draw Cord Draw Cord Ends Breaking Strength of Draw Cord Draw Cord Ends Enebroided with Piping Lower provided with Piping No Piping Fabric. Composition Piping Fabric. Composition Piping Fabric. Composition Piping Fabric. Composition Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve Ends (Lift) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve length (from center of back to bottom of sleeve Sleeve length (from center of back to bottom of sleeve Sleeve length (from center of back to bottom of sleeve Sleeve length (from center of back to bottom of sleeve Sleeve length (from center of back to bottom of sleeve Sleeve length (from center of back to bottom of sleeve	
ATERIAL ATE	
Ends per dm Picks per dm NA Picks per dm NA Courses per dm NA Wales per dm NA Count of knitting yarm Raising at inner side of Main Fabric Upper Lining Lower Lining Lower Lining Lower Lining Lining Material Mass of Lining (Gram per Square Meter) Not Applicable Not Applicable Netting mesh No of holes on base & bias within 625 Square millimeter Technical Requirements of Slide Fastener for Upper Closing Technical Requirements of Slide Fastener for Upper Closing Technical Requirements of Slide Fastener for Upper Closing Width of Tape Elastic at Waist of Trouser Waist Draw Cord Polypropylene Cord Draw Cord Ends Reaking Strength of Draw Cord Sleeve Ends (Cuff) Upper provided with Piping No Lower provided with Piping No Piping Fabric. Composition Piping Fabric. Any other material as per buyer's requirements (Other than mentioned above) Rembroidery Thread Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve length (from center of back to bottom of sleeve Sleeve pening relaxed (Cuff) Width	
Picks per dm NA Courses per dm NA Wales per dm NA Wales per dm NA Count of knitting yarn NA Rabing at linner side of Main Fabric Yes Upper Lining No Lower Lining No Lining Material Not Applicable Mess of Uning (Gram per Square Meter) Not Applicable Netting mesh No of holes on base & bias within 625 Square millimeter Not Applicable Technical Requirements of Silde Fastener for Upper Closing (For Pockets with Silde Fastner for closing) Technical Requirements of Silde Fastener for Upper Closing (For Pockets with Silde Fastner for closing) Silde Fastners are BIS Marked Not Applicable Width of Tape Elastic at Walst of Trouser Scm Width of Tape Elastic at Walst of Trouser Scm Width of Tape Elastic at Walst of Trouser Scm Width of Tape Elastic at Walst of Walst Band Walst Draw Cord Polypropylene Cord Draw Cord Ends Fused Breaking Strength of Draw Cord 340 N minimum Sleeve Ends (Cuff) Upper provided with Piping No Piping Fabric- Composition 100 percent Polyest Embroidery Thread Polypers and Polypers ZE Size Medium (M) Width Across Chest 25 mm below under arm Sc2.5 cm (Medium) Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve See (cuff) Uc centimeter	
Courses per dm NA Wales per dm NA Count of Knitting yarn NA Raising at inner side of Main Fabric Yes Upper Lining No Lower Lining No Lower Lining Material Not Applicable Mass of Lining (Gram per Square Meter) Not Applicable Mass of Lining (Gram per Square Meter) Not Applicable Technical Requirements of Side Fastener for Upper Closing Not Applicable Technical Requirements of Side Fastener for Upper Closing (For Pockets with Side Fastner for Outper Closing) Side Fastners are BIS Marked Not Applicable Width of Tape Elastic at Walst of Trouser S cm Width of Tape Elastic at Walst of Trouser S cm Width of Tape Elastic at Bottom of Upper Technical Requirements of Walst Band Walst Draw Cord Polypropylene Cord Draw Cord Ends Breaking Strength of Draw Cord 340 N minimum Sleeve Ends (Cuff) Upper provided with Piping No Lower provided with Piping No Piping Fabric Any other material as per buyer's requirements (Other than mentioned above) Na Piping Fabric Mass (gram per square mtrs) Not Applicable Embroidery Thread Polyester ZE Size Medium (M) Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (Form center of back to bottom of sleeve) Sleeve length (Form center of back to bottom of sleeve) Sleeve length (Form center of back to bottom of sleeve) Sleeve length (Form center of back to bottom of sleeve) Sleeve length (Form center of back to bottom of sleeve) Sleeve length (Form center of back to bottom of sleeve) Sleeve length (Form center of back to bottom of sleeve) Sleeve length (Form center of back to bottom of sleeve)	
Wales per dm Count of knitting yarm Raising at inner side of Main Fabric Upper Lining Lower Lining Lower Lining Lower Lining Lining Material Mass of Lining (Gram per Square Meter) Not Applicable Not Applicable Netting mesh No of holes on base & bias within 625 Square millimeter Not Applicable Technical Requirements of Slide Fastener for Upper Closing Technical Requirements of Slide Fastener for Pocket Closing (For Pockets with Slide Fastener for Closing) Slide Fastners are BIS Marked Not Applicable Width of Tape Elastic at Waist of Trouser Side Fasteners are BIS Marked Waist Draw Cord Technical Requirements of Waist Band Waist Draw Cord Draw Cord Ends Requirements of Waist Band Waist Draw Cord Draw Cord Ends Prace Ends (Cuff) Upper provided with Piping No Depring Fabric Composition Piping Fabric Composition Piping Fabric Composition Piping Fabric Mass (gram per square mtrs) Embroidery Thread Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve lends (Cuff) Width Of Tape Elastic Tope Width Across Bottom Opening (relaxed) Length at front from center of back to bottom of sleeve Sleeve lends (Cuff) Width	
Count of knitting yarm Raising at inner side of Main Fabric Upper Lining Lower Lining Lower Lining Lining Material Mass of Lining (Gram per Square Meter) Not Applicable Mass of Lining (Gram per Square Meter) Not Applicable Netting mesh No of holes on base & bias within 625 Square millimeter Not Applicable Technical Requirements of Slide Fastener for Upper Closing Technical Requirements of Slide Fastener for Upper Closing Technical Requirements of Slide Fastener for Pocket Closing (For Pockets with Slide Fastner for closing) Slide Fastners are BIS Marked Not Applicable Width of Tape Elastic at Waist of Trouser Width of Tape Elastic at Bottom of Upper Technical Requirements of Waist Band Waist Draw Cord Polypropylene Cord Draw Cord Ends Breaking Strength of Draw Cord Sleeve Ends (Cuff) Upper provided with Piping No Lower provided with Piping No Piping Fabric Composition Piping Fabric Composition Piping Fabric Mass (gram per square mtrs) Embroidery Thread Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve Lends (Cuff) Width Sleeve Lends (For Medium) Sleeve Lends (For M	
Raising at inner side of Main Fabric Piper Lining No No Lower Lining Not Applicable Lower Lining Lining Material Not Applicable Mass of Lining (Gram per Square Meter) Not Applicable Netting mesh No of holes on base & bias within 625 Square millimeter Not Applicable Technical Requirements of Slide Fastner for Upper Closing Light Duty as per IS Technical Requirements of Slide Fastner for Pocket Closing (For Pockets with Slide Fastner for closing) Slide Fastners are BIS Marked Not Applicable Width of Tape Elastic at Waist of Trouser Schwicz Schwi	
Upper Lining Lower Lining Lower Lining Lining Material Not Applicable Mass of Lining (Gram per Square Meter) Netting mesh No of holes on base & bias within 625 Square millimeter Not Applicable Technical Requirements of Slide Fastener for Upper Closing Light Duty as per IS Technical Requirements of Slide Fastener for Upper Closing Technical Requirements of Slide Fastener for Pocket Closing (For Pockets with Slide Fastner for closing) Slide Fastners are BIS Marked Not Applicable Width of Tape Elastic at Waist of Trouser Scm Width of Tape Elastic at Bottom of Upper 3.5 cm Technical Requirements of Waist Band Waist Draw Cord Draw Cord Ends Breaking Strength of Draw Cord Sleeve Ends (Cuff) Upper provided with Piping No Lower provided with Piping No Piping Fabric- Composition Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) NA Piping Fabric Mass (gram per square mtrs) Embroidery Thread Polyester Size Medium (M) Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width Sleeve Pening relaxed (Cuff) Width Sleeve opening relaxed (Cuff) Width To centimeter	
Lower Lining Lining Material Mass of Lining (Gram per Square Meter) Not Applicable Mass of Lining (Gram per Square Meter) Not Applicable Netting mesh No of holes on base & bias within 625 Square millimeter Not Applicable Technical Requirements of Slide Fastener for Upper Closing Light Duty as per IS Technical Requirements of Slide Fastener for Pocket Closing (For Pockets with Slide Fastner for closing) Slide Fastners are BIS Marked Not Applicable Width of Tape Elastic at Waist of Trouser Sc m Width of Tape Elastic at Bottom of Upper 3.5 cm Technical Requirements of Waist Band Waist Draw Cord Draw Cord Ends Breaking Strength of Draw Cord Sleeve Ends (Cuff) Upper provided with Piping No Lower provided with Piping No Piping Fabric- Composition Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) NA Piping Fabric Mass (gram per square mtrs) Embroidery Thread Polyester ZE Size Medium (M) Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width Sleeve opening relaxed (Cuff) Width To centimeter	
Lining Material Mass of Lining (Gram per Square Meter) Not Applicable Mass of Lining (Gram per Square Meter) Not Applicable Netting mesh No of holes on base & bias within 625 Square millimeter Technical Requirements of Slide Fastener for Upper Closing Technical Requirements of Slide Fastener for Pocket Closing (For Pockets with Slide Fastener for Closing) Slide Fastners are BIS Marked Not Applicable Width of Tape Elastic at Waist of Trouser Width of Tape Elastic at Bottom of Upper Technical Requirements of Waist Band Waist Draw Cord Technical Requirements of Waist Band Waist Draw Cord Draw Cord Ends Breaking Strength of Draw Cord Sleeve Ends (Cuff) Upper provided with Piping Lower provided with Piping No Piping Fabric-Composition Piping Fabric-Any other material as per buyer's requirements (Other than mentioned above) Embroidery Thread Polyester Size Medium (M) Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (firom center of back to bottom of sleeve Sleeve length (firom center of back to bottom of sleeve Sleeve length (firom center of back to bottom of sleeve Sleeve length (firom center of back to bottom of sleeve Sleeve length (Form center of back to bottom of sleeve)	
Mass of Lining (Gram per Square Meter) Not Applicable Netting mesh No of holes on base & bias within 625 Square millimeter Technical Requirements of Silde Fastener for Upper Closing Technical Requirements of Silde Fastener for Pocket Closing (For Pockets with Silde Fastener for Closing) Not applicable Technical Requirements of Silde Fastener for Pocket Closing (For Pockets with Silde Fastener for Not applicable Width of Tape Elastic at Waist of Trouser Width of Tape Elastic at Bottom of Upper 3.5 cm Technical Requirements of Waist Band Waist Draw Cord Technical Requirements of Waist Band Waist Draw Cord Draw Cord Ends Breaking Strength of Draw Cord Sleeve Ends (Cuff) Upper provided with Piping Lower provided with Piping No Piping Fabric- Composition Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) NA Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) Embroidery Thread Polyester Size Medium (M) Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sievev length (From center of back to bottom of sievev Sieve opening relaxed (Cuff) Width To centimeter	
Netting mesh No of holes on base & bias within 625 Square millimeter Not Applicable Technical Requirements of Slide Fastener for Upper Closing Technical Requirements of Slide Fastener for Pocket Closing (For Pockets with Slide Fastner for Colosing) Slide Fastners are BIS Marked Not Applicable Width of Tape Elastic at Waist of Trouser 5 cm Width of Tape Elastic at Bottom of Upper 3.5 cm Technical Requirements of Waist Band Waist band as per It Waist Darw Cord Polypropylene Cord Praw Cord Ends Fused Breaking Strength of Draw Cord 340 N minimum Sleeve Ends (Cuff) Upper provided with Piping No Lower provided with Piping No Piping Fabric-Composition 100 percent Polyest Piping Fabric-Any other material as per buyer's requirements (Other than mentioned above) NA Piping Fabric-Mass (gram per square mtrs) Not Applicable Embroidery Thread Polyester ZE Size Medium (M) Width Across Chest 25 mm below under arm 5.2.5 cm (Medium) Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom 5leeve 84.5 cm (Medium) Sleeve pening relaxed (Cuff) Width 10 centimeter	
Netting mesh No of holes on base & bias within 625 Square millimeter Not Applicable Technical Requirements of Slide Fastener for Upper Closing Technical Requirements of Slide Fastener for Pocket Closing (For Pockets with Slide Fastner for closing) Slide Fastners are BIS Marked Width of Tape Elastic at Waist of Trouser Width of Tape Elastic at Bottom of Upper Technical Requirements of Waist Band Waist Draw Cord Polypropylene Cord Draw Cord Ends Breaking Strength of Draw Cord Sleeve Ends (Cuff) Upper provided with Piping Lower provided with Piping Piping Fabric-Composition Piping Fabric-Any other material as per buyer's requirements (Other than mentioned above) Polypster TEE Size Medium (M) Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve Dening relaxed (Cuff) Width Technical Requirements of Slide Fastener for Pocket Closing (For Pockets with Slide Fastener for Closing (For Pockets with Slide Fastener	
Technical Requirements of Slide Fastener for Pocket Closing (For Pockets with Slide Fastner for closing) Slide Fastners are BIS Marked Width of Tape Elastic at Waist of Trouser Width of Tape Elastic at Bottom of Upper Technical Requirements of Waist Band Waist band as per It Waist Draw Cord Draw Cord Ends Breaking Strength of Draw Cord Sleeve Ends (Cuff) Lower provided with Piping Lower provided with Piping Piping Fabric- Composition Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) Piping Fabric Mass (gram per square mtrs) Embroidery Thread Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width Scentimeter	
closing) Slide Fastners are BIS Marked Not Applicable Width of Tape Elastic at Waist of Trouser 5 cm Width of Tape Elastic at Bottom of Upper 3.5 cm Technical Requirements of Waist Band Waist band as per It Waist Draw Cord Polypropylene Cord Draw Cord Ends Fused Breaking Strength of Draw Cord 340 N minimum Sleeve Ends (Cuff) Elastic Tape Upper provided with Piping No Lower provided with Piping No Piping Fabric- Composition 100 percent Polyest Piping Fabric-Any other material as per buyer's requirements (Other than mentioned above) NA Piping Fabric Mass (gram per square mtrs) Not Applicable Embroidery Thread Polyester IZE Size Medium (M) Width Across Chest 25 mm below under arm 52.5 cm (Medium) Width Across Softom Opening (relaxed) 46 cm (Medium) Length at front from top of collar to bottom 51eeve 51eeve opening relaxed (Cuff) Width 10 centimeter	er IS 14181 Latest
Width of Tape Elastic at Waist of Trouser Width of Tape Elastic at Bottom of Upper Technical Requirements of Waist Band Waist Draw Cord Polypropylene Cord Draw Cord Ends Breaking Strength of Draw Cord Sleeve Ends (Cuff) Upper provided with Piping Lower provided with Piping Piping Fabric- Composition Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) Piping Fabric Mass (gram per square mtrs) Embroidery Thread Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width 10 centimeter	
Width of Tape Elastic at Bottom of Upper Technical Requirements of Waist Band Waist Draw Cord Polypropylene Cord Draw Cord Ends Breaking Strength of Draw Cord Sleeve Ends (Cuff) Upper provided with Piping No Lower provided with Piping No Piping Fabric- Composition Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) Piping Fabric Mass (gram per square mtrs) Not Applicable Embroidery Thread Polyester Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width Sleeve opening relaxed (Cuff) Width 10 centimeter	
Technical Requirements of Waist Band Waist Draw Cord Polypropylene Cord Draw Cord Ends Fused Breaking Strength of Draw Cord Sleeve Ends (Cuff) Upper provided with Piping No Lower provided with Piping No Piping Fabric- Composition Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) Piping Fabric- Mass (gram per square mtrs) Embroidery Thread Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width 100 centimeter	
Waist Draw Cord Draw Cord Ends Breaking Strength of Draw Cord Sleeve Ends (Cuff) Upper provided with Piping Lower provided with Piping No Piping Fabric- Composition Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) Embroidery Thread Width Across Chest 25 mm below under arm Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width Sleeve opening relaxed (Cuff) Width Polypropylene Cord Fused Fused 340 N minimum No 100 percent Polyest No No No No No No No Not Applicable Polyester Seeve Medium (M) Seeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width Sleeve opening relaxed (Cuff) Width 10 centimeter	
Draw Cord Ends Breaking Strength of Draw Cord 340 N minimum Sleeve Ends (Cuff) Upper provided with Piping No Lower provided with Piping Piping Fabric- Composition Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) Piping Fabric Mass (gram per square mtrs) Embroidery Thread Polyester Size Medium (M) Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width Sleeve opening relaxed (Cuff) Width 10 centimeter	er IS 9686- 1980 latest
Breaking Strength of Draw Cord Sleeve Ends (Cuff) Upper provided with Piping Lower provided with Piping No Piping Fabric- Composition Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) Piping Fabric Mass (gram per square mtrs) Embroidery Thread Size Medium (M) Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width 10 centimeter	Cord of 4mm dia
Sleeve Ends (Cuff) Elastic Tape Upper provided with Piping No Lower provided with Piping No Piping Fabric- Composition 100 percent Polyest Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) NA Piping Fabric Mass (gram per square mtrs) Not Applicable Embroidery Thread Polyester IZE Size Medium (M) Width Across Chest 25 mm below under arm 52.5 cm (Medium) Width Across Bottom Opening (relaxed) 46 cm (Medium) Length at front from top of collar to bottom 5sleeve 84.5 cm (Medium) Sleeve length (from center of back to bottom of sleeve 84.5 cm (Medium) Sleeve opening relaxed (Cuff) Width 10 centimeter	
Upper provided with Piping Lower provided with Piping No Piping Fabric- Composition Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) Piping Fabric Mass (gram per square mtrs) Embroidery Thread Not Applicable Embroidery Thread Polyester Size Medium (M) Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width Sleeve opening relaxed (Cuff) Width 10 centimeter	ı
Lower provided with Piping No Piping Fabric- Composition 100 percent Polyest Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) NA Piping Fabric Mass (gram per square mtrs) Not Applicable Embroidery Thread Polyester IZE Size Medium (M) Width Across Chest 25 mm below under arm 52.5 cm (Medium) Width Across Bottom Opening (relaxed) 46 cm (Medium) Length at front from top of collar to bottom 66 cm (Medium) Sleeve length (from center of back to bottom of sleeve 84.5 cm (Medium) Sleeve opening relaxed (Cuff) Width 10 centimeter	
Piping Fabric- Composition 100 percent Polyest Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) NA Piping Fabric Mass (gram per square mtrs) Not Applicable Embroidery Thread Polyester Size Medium (M) Width Across Chest 25 mm below under arm 52.5 cm (Medium) Width Across Bottom Opening (relaxed) 46 cm (Medium) Length at front from top of collar to bottom 66 cm (Medium) Sleeve length (from center of back to bottom of sleeve 84.5 cm (Medium) Sleeve opening relaxed (Cuff) Width 10 centimeter	
Piping Fabric- Any other material as per buyer's requirements (Other than mentioned above) Piping Fabric Mass (gram per square mtrs) Embroidery Thread Polyester IZE Size Medium (M) Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width 10 centimeter	
Piping Fabric Mass (gram per square mtrs) Embroidery Thread Polyester Size Medium (M) Width Across Chest 25 mm below under arm Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width 10 centimeter	yester
Embroidery Thread Polyester IZE Size Medium (M) Width Across Chest 25 mm below under arm 52.5 cm (Medium) Width Across Bottom Opening (relaxed) 46 cm (Medium) Length at front from top of collar to bottom 66 cm (Medium) Sleeve length (from center of back to bottom of sleeve 84.5 cm (Medium) Sleeve opening relaxed (Cuff) Width 10 centimeter	
IZE Size Medium (M) Width Across Chest 25 mm below under arm 52.5 cm (Medium) Width Across Bottom Opening (relaxed) 46 cm (Medium) Length at front from top of collar to bottom 66 cm (Medium) Sleeve length (from center of back to bottom of sleeve 84.5 cm (Medium) Sleeve opening relaxed (Cuff) Width 10 centimeter	
Width Across Chest 25 mm below under arm 52.5 cm (Medium) Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width 10 centimeter	
Width Across Bottom Opening (relaxed) Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width 10 centimeter	
Length at front from top of collar to bottom Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width 10 centimeter	m)
Sleeve length (from center of back to bottom of sleeve Sleeve opening relaxed (Cuff) Width Sleeve opening relaxed (Cuff) Width)
Sleeve opening relaxed (Cuff) Width 10 centimeter)
Sleeve opening relaxed (Cuff) Width 10 centimeter	m)
Front Neck Dron	
1 5 centimeter	
Back Neck Drop 2 centimeter	

	+	1
	Side Seam Length	104.5 cm (Medium)
	Waist relaxed (Width Across)	43 cm (Medium)
	Waist stretched (Width Across)	52.5 cm (Medium)
	Seat/ Hip (15 cm below waist band)	52.5 cm (Medium)
DIMENSIONS OF	Thigh (at Crotch) (Width Across)	36 cm (Medium)
LOWER	Bottom Opening (Width Across)	24 centimeter
	Front rise including waist band	28 cm (Medium)
	Back rise including waist band	38 cm (Medium)
	Length of Waist Tying Cord	160 centimeter
	Bottom Fold (Hem) with full turn in(cm)	2.0
	Number of Pockets (Upper)	2 Side Pockets
	Size of Side Pockets-Upper (Length X Width) (cm)	17 cm X 18 cm
	Size of Inside Pocket at Chest- Upper	Not Applicable
	Side Pocket opening - Upper	15.0 cm
	Side Pocket Closure with Slide Fastener -Upper	No
POCKETS	Number of Pockets (Lower)	2 Side Pockets
	Size of Side Pockets - Lower (Length X Width) (cm)	17 cm X 18 cm
	Side Pocket Opening- Lower	17.5 centimeter
	Pocket Closure with Slide Fastener - Lower	All Pockets without Slide Fastener
	Material of Pockets	Main Basic Fabric
COLLAR	Collar Type	Stand and Fall Type, Made of two layers of self material
	Collar Reinforcement	With Canvas Reinforcement
SLEEVE	Sleeve Type	Reglan Sleeve
	Position and Dimensions of Piping on Upper	NA
PIPING	Position and Dimensions of Piping on Lower	NA
	Sewing Thread	145 d tex X 3, Polyester
	Raw edges, if any shall be bound by overlock stitching	Yes
	Waist band stitching of Upper	Stitched in single rows with chain stitch on the elastic
	Sleeve Bottom (Cuff) Stitching	Not Applicable
STITCHING	Waist band stitching of Lower	Stitched in single rows with chain stitch on the elastic
	Lining seams	Not Applicable
	Bartack Stitching (Reinforcement Stitching) at stress bearing areas	No
	Tunnel at Waist Band for Lower	Two holes stitched to allow the draw cord with insertion free movement
	Stitches per dm (min)	36
	Colour	Multicolour/ Contrasting Pannels / Any other colou as per buyer's requirements
	Multicolour/ Contrasting Pannels / Any other colour as per buyer's requirements	GREY
	Sublimation Printing (for 100 % polyester only)	Sublimation Print as per buyer's requirements
	Sublimation Print as per buyer's requirements	NA
	Colourfastness to Light (IS 2454)	5
	Colourfastness to Washing (IS/ ISO 105-C10, Test- C (3))	Change in Colour- 4; Staining of Adjacent Fabric- 3
COLOUR/ PRINT	Colourfastness to Rubbing (IS 766)	Dry- 4 / Wet- 3
	Colourfastness to perspiration (IS 971)	4
		1
	Colour of Mesh Lining	Not Applicable

	Colourfastness to Washing (IS/ISO 105-C10, Test- C (3))- Mesh Lining	Not Applicable
	Colourfastness to perspiration (IS 971)- Mesh Lining	Not Applicable
	Colour of Piping Material	Any other colour as per buyer's requirements
	Any other colour as per buyer's requirements	Black
	Pilling Resistant [after 5 hours Test as per IS 10971 (Part 1)], min	4
OTHER REQUIREMENTS	Dimensional stability to washing, Shrinkage or Elongation Percentage, max (IS 2977 latest), in lengthwise and widthwise direction	2
	Logo/ Totem Marking	As per buyer's requirements
	Type of Logo	Printed
LOGO AND MARKING	Number of Logos on Upper	1
	Number of Logos on Lower	1
	Size, Design and Location of Logo as per buyer's requirement	Yes
	Availability of Test Report from designated AHSP/ NABL/ ILAC accredited or Central Government Lab to prove conformity of products to the specification	No
	Test Report No	NA
TEST REPORT	Test Report Date	NA
	Name of the Lab	NA
	Address of the Lab	NA
	Test reports to be furnished to buyer on demand, if claimed to be available	Not applicable
ADVANCE SAMPLE	Agree to provide Advance Sample(s) for buyer's approval before commencement of supply	Not applicable

टिप्पणी | Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

ईपीबीजी विवरण | ePBG Detail

NA

नियम और शर्तें|Terms and Conditions

- 1. General Terms and Conditions-
- 1.1 This contract is governed by the General Terms and Conditions, conditions stipulated to this Product/Service as provided in the Marketplace.
- 1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.