

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687764261736

अनुबंध तिथि | Generated Date : 20-Jun-2024

संगठन विवरण Organisation Details		खरीदार विवरण Buyer Details				
प्ररूप Type :	State Government	पद Designation :	Kamrej Gram Panchayat			
मंत्रालय Ministry :	-	संपर्क नंबर Contact No. :	-			
विभाग Department :	Panchayats and Rural Housing Department Gujarat	ईमेल आईडी Email ID :	buycon506.sdp.gj@gembuyer.in			
संगठन का नाम Organisation Name :	Surat District Panchayat	जीएसटीआईएन GSTIN :	-			
कार्यालय क्षेत्र Office Zone :	Taluka Panchayat Kamrej	पता Address :	Taluka Panchayat Kamrej , Ta.Kamrej , Dist Surat, SURAT, GUJARAT-394185, India			
वित्तीय स्वीकृति विवरण Financial Approval Detail		भुगतान प्राधिकरण विवरण Paying Authority Details				
आईएफडी सहमति IFD Concurrence :	No	Role:	BUYER			
प्रशासनिक अनुमोदन का पदनाम Designation of Administrative Approval:	Shah Kinjal Jignesh	भुगतान का तरीका Payment Mode:	Offline			
वित्तीय अनुमोदन का पदनाम Designation of Financial Approval :	Shah Kinjal Jignesh	पद Designation :	Kamrej Gram Panchayat			
		ईमेल आईडी Email ID :	buycon506.sdp.gj@gembuyer.in			
		जीएसटीआईएन GSTIN :	-			
		पता Address:	Taluka Panchayat Kamrej , Ta.Kamrej , Dist Surat, Surat, GUJARAT-394185, India			
विक्रेता विवरण Seller Details						
जेम विक्रेता आईडी GeM Seller ID :	3B24230009218751					
कंपनी का नाम Company Name :	SAI ENTERPRISE					
संपर्क नंबर Contact No. :	07016626036					
ईमेल आईडी Email ID :	Priyapatel35926@gmail.com					
पता Address :	Plot No.234/1,At Po Kelni,,Kukarmunda,Ta Nizar, Fulwadi, Tapi, Gujarat,, Surat, GUJARAT-394380, -					
एमएसएमई पंजीकरण संख्या MSME Registration number :	UDYAM-GJ-33-0004398					
एमएसई सामाजिक श्रेणी MSE Social Category :	General					
एमएसई लिंग श्रेणी MSE Gender :	Female					
जीएसटीआईएन GSTIN:	24CLWPP4867R1ZP (R)					
*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा GST / Tax invoice to be raised in the name of - Buyer						
वितरण निर्देश Delivery Instructions : NA						
उत्पाद विवरण Product Details						
#	आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : Unbranded 36 W LED Luminaire For Flood Light ब्रांड Brand : NA ब्रांड प्रकार Brand Type : Unbranded कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : LED Luminaire (for Flood Light) as per IS 10322, IS 16107 (Q3) मॉडल Model: UNBRANDED FLOOD LIGHT 35W IP66 एचएसएन कोड HSN Code: HSN not specified by seller	28	pieces	885	NA	24,780
कुल ऑर्डर मूल्य Total Order Value (in INR)						24,780
परोक्षी विवरण Consignee Detail						
क्र.सं. S.No	परोक्षी Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनों के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा कब तक करना है Delivery To Be Completed By
1	पद Designation : Kamrej Gram Panchayat ईमेल आईडी Email ID : buycon506.sdp.gj@gembuyer.in संपर्क Contact : - जीएसटीआईएन GSTIN : -	Unbranded 36 W LED Luminaire For Flood	-	28	20-Jun-2024	05-Jul-2024

Product Specification for Unbranded 36 W LED Luminaire For Flood Light

विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
STANDARDS	LED Luminaire conformity to IS:10322/Part 5/Section 5/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest	Yes
	Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group)	Yes
	Types of LED Luminaire as per the IS: 16107(Part-2/ Sec.-1)/2012	Type B
	Types of LED Modules as per the IS: 16103(Part-2)/2012	Type 3
	LED Rating/System Wattage/Rated Power	36 W
	Luminaire System Efficacy (Lumen/watt)	>= 100 Lm/Watt
	Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest	IP66
	Mounting brackets (included)	Adjustable
	Warranty for free replacement (in Years)	2
ELECTRICAL EFFICIENCY	Input operating Voltage range and frequency	90 to 300 V olts AC at 50 Hz+/-2 Hz
	Automatic Higher Cut off voltage above 300 volt	Yes
	Rated voltage	230 V AC 50 Hz
	AC Power Factor at full load	≥ 0.95
	Driver Efficiency (in %age)	≥85
	Total Harmonics Distortion (in %age)	≤ 10
	"The total circuit power shall not be more than 110 percent of the value declared by the manufacturer"	Yes
OPTICAL	LED chip Efficacy	≥130 Lm/Watt
	Colour temperature (+/-500K)	6000K
	Working life for LED (Minimum 50,000 burning hours as per LM-80 report)	Yes
	Colour Rendering Index(CRI)	≥70
	Beam Angle	≥120
	Optic lense material (UV stabilised) (Write NA for without optic lense supply)	Poly carbonate lense
THERMAL MANAGEMENT	Heat sink should be die-cast aluminium along with sufficient heat sink fins to dissipate heat effectively	Yes
	Capacitor shall be rated for a temperature of 105 deg. celsius or better	Yes
	Junction temperature	< 85 degC
	Operating temperature range	-10 deg C to +50 deg C
	Operating Humidity Range	10 % to 95% RH
PROTECTION	Short circuit Protection	Yes
	Over load protecton	Yes
	Over Voltage protection	Yes
	Reverse polarity	Yes
	High voltage test (1.5 KV for one minute between supply terminals and body of the unit)	Yes
	Insulation resistance between earth and current carrying part	>100 M ohm
	The luminaire shall be protected against surges and transients (Internal)	>=5KV
	The luminaire shall be protected against surges and transients of >=10KV (External)	Yes
	The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity	Yes
	The luminaire body must be corrosion resistant epoxy powder coated	Yes
	All fastners must be of stainless steel	Yes
	The entire housing (both LED section and driver section) shall be dust and water proof having IP 66 protection as per IS:10322 (Part 1):1982 latest	Yes
	Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc.,	Yes
	Luminaries light transparency should be of Toughened glass	Yes

CONSTRUCTIONAL	Toughned transparent glass cover thickness	>=4 mm
	Toughned Glass shall not get discoloured shall not suffer degradation due to heat and ageing within warranty period	Yes
	Number of electronic control gear (power supplies)	1 No.
	Driver components shall be industrial grade or above	Yes
	PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more	Yes
	The Luminaires works on single phase three wires system (Phase, Neutral and Earth)	Yes
	Suitable connector shall be provided for LED connection between driver output and LED	Yes
	Length of ISI marked three core wire (shall be provided along with supply of material)	50 cm
	Light Source	SMD LED Chip as per LM 80/IS16106
	MARKING	"Manufactures Name and and brand on the aluminium die cast body
Manufacturer's name, model number, serial number		Yes
Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box		Yes
The operation characteristics voltage and power be marked inside of each LED luminaire unit		Yes
REPORTS AND CERTIFICATIONS	LED Make	OSRAM / NICHIA/CREE / SAMSUNG / SEOUL / LUMILED / PHILIPS / EDISON / SYSKA / LUMENMAX / EVERLIGHT / BRIDGELUX / NATIONSTAR / REFOND
	System must have EMI/EMC compliance as applicable (Test reports shall be furnish on demand by buyer/consignee)	Yes
	LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government lab/NABL/ILAC accredited lab. Reports shall be furnish on demany by buyer (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc..)	Yes
	LM 80 & TM 21 (Part of LM 80) (Ref. IS:16105:2012) Reports and Photo biological report for LED report from Central Government lab /NABL/ILAC accredited lab. Reports shall be furnish on demany by buyer (LM-80 report shall haveand the Pohoto Biological report of the LED Chip being used in the luminaire)	Yes
	Availability of test Report from Central Government lab/NABL/ILAC accredited lab to Indian Standrad IS:10322/part 5/sec-5/2012 and IS 16107 (Part 2/Sec 1) : 2012	Yes
	Seller has to furnish Type test report on demand by buyer/consignee	Yes
	DC or AC supplied electronic control gear for LED Module shall comply as per IS:15885 (Part 2/Sec.13)	Yes
	LED Luminaire for Flood Light shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 5): 2012 as applicable on the date	Yes
<p>टिप्पणी Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.</p>		
<p>ईपीबीजी विवरण ePBG Detail</p>		
<p>NA</p>		
<p>नियम और शर्तें Terms and Conditions</p>		
<p>1. General Terms and Conditions-</p>		
<p>1.1 This contract is governed by the General Terms and Conditions, conditions stipulated to this Product/Service as provided in the Marketplace.</p>		
<p>1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable</p>		
<p>नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।</p>		
<p>Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.</p>		