

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687740831174

अनुबंध तिथि | Generated Date : 22-Jun-2024

संगठन विवरण Organisation Details		खरीदार विवरण Buyer Details				
प्ररूप Type :	State Autonomous	पद Designation :	Gramsevak			
मंत्रालय Ministry :	-	संपर्क नंबर Contact No. :	-			
विभाग Department :	Department of Panchayati Raj	ईमेल आईडी Email ID :	gpkotamgaon02-mh@panchayat.gov.in			
संगठन का नाम Organisation Name :	NASHIK District Panchayats	जीएसटीआईएन GSTIN :	-			
कार्यालय क्षेत्र Office Zone:	KOTAMGAON 183391	पता Address :	Grampanchayat Office Kotamgaon Tal Dist Nashik, NASHIK, MAHARASHTRA-422105, India			
वित्तीय स्वीकृति विवरण Financial Approval Detail		भुगतान प्राधिकरण विवरण Paying Authority Details				
आईएफडी सहमति IFD Concurrence :	No	Role:	BUYER			
प्रशासनिक अनुमोदन का पदनाम	GRAMSEVAK	भुगतान का तरीका	MOPR			
Designation of Administrative Approval:		Payment Mode:				
वित्तीय अनुमोदन का पदनाम	SACHIV	पद Designation :	Gramsevak			
Designation of Financial Approval :		ईमेल आईडी Email ID :	gpkotamgaon02-mh@panchayat.gov.in			
		जीएसटीआईएन GSTIN :	-			
		पता Address:	Grampanchayat Office Kotamgaon Tal Dist Nashik, Nashik, MAHARASHTRA-422105, India			
विक्रेता विवरण Seller Details						
जेम विक्रेता आईडी GeM Seller ID :	5XIY230010702337					
कंपनी का नाम Company Name :	VAISHNAVI COMPUTERS					
संपर्क नंबर Contact No. :	07057662566					
ईमेल आईडी Email ID :	vcminfotech@gmail.com					
पता Address :	SHOP NO.4, SHAILYATRABAK, NAYGOAN ROAD,SHINDE , NASHIK,SHINDE,NASHIK,NASHIK, Nashik, MAHARASHTRA-422102, -					
एमएसएमई पंजीकरण संख्या MSME Registration number :	UDYAM-MH-23-0077757					
एमएसई सामाजिक श्रेणी MSE Social Category :	SC					
एमएसई लिंग श्रेणी MSE Gender :	Male					
जीएसटीआईएन GSTIN:	27CKWPS5230G1ZM (R)					
*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा GST / Tax invoice to be raised in the name of - Consignee						
वितरण निर्देश Delivery Instructions : NA						
उत्पाद विवरण Product Details						
#	आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : UTL SOLAR can be hung from the ceiling in a stable manner SPV Module:200 Wp, Battery:24V,75Ah Solar Lamps (Solar Based Home Systems - Solar Power Packs - Ac Models ब्रांड Brand : UTL SOLAR ब्रांड प्रकार Brand Type : Registered Brand कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Solar Lamps (Solar Based Home Systems - Solar Power Packs - AC Models) (Q3) मॉडल Model: SPP200WP3 एचएसएन कोड HSN Code: HSN not specified by seller	1	pieces	24,999	NA	24,999
कुल ऑर्डर मूल्य Total Order Value (in INR)						24,999
परेषिती विवरण Consignee Detail						
क्र.सं. S.No	परेषिती Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा कब तक करना है Delivery To Be Completed By
	पद Designation : Gramsevak	UTL SOLAR can be hung from the ceiling in a				

1	ईमेल आईडी Email ID : gpkotamgaon02-mh@panchayat.gov.in संपर्क Contact : - जीएसटीआईएन GSTIN : - पता Address : Grampanchayat Office Kotamgaon Tal Dist Nashik, NASHIK, MAHARASHTRA-422105, India	stable manner SPV Module:200 Wp, Battery:24V,75Ah Solar Lamps (Solar Based Home Systems - Solar Power Packs - Ac Models	-	1	22-Jun-2024	07-Jul-2024
Product Specification for UTL SOLAR can be hung from the ceiling in a stable manner SPV Module:200 Wp, Battery:24V,75Ah Solar Lamps (Solar Based Home Systems - Solar Power Packs - Ac Models						
विनिर्देश Specification		उप-विनिर्देश Sub-Spec			मूल्य Value	
CONSTRUCTIONAL		Corrosion resistant frame structure should be provided to hold the SPV module. PV Module shall supply with Module mounting structure			Yes	
		The frame structure should have provision to adjust its angle of inclination to the horizontal, so that it can be installed at the specified tilt angle			Yes	
		Mounting type of light source as per site requirements.			can be hung from the ceiling in a stable manner	
		A vented plastic/ wooden/ metallic box with acid proof corrosion resistant paint for housing the storage battery indoors should be provided			Yes. provided	
		The system should have two indicators, green (charging under preogress) and red (indicate the battery "Load Cut Off" condition)			Yes	
		Working temperature			0 deg C to 45 deg C	
GENERIC		Power pack model			SPV Module:200 Wp, Battery:24V,75Ah	
		Solar Inverter: 24V /12 V , 300VA, Pure Sine wave (THD<5%)			Yes	
		Load			100 Watt A.C. load for 4-5 Hours/ day for 200 Wp solar power pack	
		Indicative A.C. Loads: 3 Nos. of White Light Emitting Diode (W-LED) Luminaire (max. 3.0 Watts each) for 6 Hrs. / day			Yes. Provided	
		"Indicative A.C. Loads: 2 Nos. of White Light Emitting Diode (W-LED) Luminaire (max. 6.0 Watts each) for 6 Hrs. / day"			Yes. Provided	
		Provision to Power			for One Fan or A TV set for 4-5 Hrs. / day for 200 Wp solar power pack	
		Provision for operating the radio			Yes	
		USB port for mobile Phone Charging			Yes	
		Solar Photovoltaic lighting systems and power packs A. C. Models shall conform to MNRE specification (Off-grid Solar Applications Scheme 2016-17)			Yes	
PV MODULE		Indigenously manufactured PV modules should be used			Yes	
		The PV modules should be made up of crystalline silicon solar cells and must have a certificate of testing conforming to IEC 61215 Edition II / BIS 14286 from an NABL or IECQ accredited Laboratory.			Yes	
		Efficiency for PV Modules			>14%	
		The terminal box on the module should have a provision for opening, for replacing the cable, if required			Yes	
		"There should be a Name Plate fixed inside the module which will give: (a) Name of the Manufacturer or Distinctive Logo. (B) Model Number (c) Serial Number (d) Year of manufacture"			Yes	
		A distinctive serial number starting with NSM will be engraved on the frame of the module or screen printed on the tedlar sheet of the module.			Yes	
BATTERY		The battery should be Lead Acid, Tubular positive plate flooded electrolyte or Gel or VRLA Type. Battery Ah at C/10 rated			Yes	
		75 % of the rated capacity of the battery should be between fully charged & load cut off conditions			Yes	
		Battery should conform to the latest BIS/ International standards			Yes	
LIGHT SOURCE		The luminaries should use white LEDs			Yes	
		Minimum 18 Lux for 3 W LED Luminaire and Minimum 32 LUX for 16W LED Luminaire when measured from a height of 2.5 meter in an area of 2.5 meter diameter			Yes	
		The colour temperature of White-LED(s) used in the system			5500 deg K to 6500 deg K	
		3 Nos. of White Light Emitting Diode (W-LED) Luminaire (max. 3.0 Watts each) .			Yes. Provided	
		The total input power consumption by the luminaire is not more than 3 W/6W as applicable (including the LED driver consumption).			Yes	
		White-LED(s) should not emit ultraviolet light			Yes	
		The light output from the White- LED should be constant throughout the operation of lights			Yes	
		The lamps should be housed in an assembly suitable for indoor use with an appropriate heat sink to dissipate the heat				

	generated by LEDs during operation	Yes
	"The temperature of LED should not increase more than 10o above room temperature. This condition should be complied for 5 hours of operation of the lamp at a stretch while battery operating at any voltage between the loads disconnect and the charge regulation set point"	Yes
	The luminaries must use the optics and diffuser in order to have uniform and glaze free light	Yes
	The make, model number, country of origin and technical characteristics (including IESNA LM-80 report) of white LEDs used in the lighting system must be furnished to the buyer / consignee along with the system	Yes
	All Luminaries should have a built in ON/OFF switch and fuse	Yes
	2 Nos. of White Light Emitting Diode (W-LED) Luminaire (max. 6.0 Watts each).	Yes. Provided
ELECTRONICS	Electronics should operate at 12 / 24 V and should have adequate temperature compensation arrangement for proper charging of the battery throughout the year	Yes
	Total Harmonic Distortion	<5%
	Inverter efficiency	>/=90%
	The system should have separate ports for connecting each load along with a charging port for mobile and laptop	Yes
	The voltage drop from module terminals to the battery terminals should not exceed 1.0 volts including the dropage across the diode and the cable when measured at maximum charging current	Yes
	The idle current i.e. when there is no load (& inverter is switched OFF, in case of A.C. Systems) and no display	</=150 mA
	The PCB containing the electronics should be capable of solder free installation and replacement	Yes
	Necessary lengths of wires/cables, switches suitable for DC use and fuses should be provided	Yes
	Necessary lengths of wires/ cables, switches and fuses should be provided	Yes
	The inverter output AC voltage should not change with the decreased battery voltage in the operating voltage range of the battery	Yes
	No Load protection	Yes
	Battery over charge and deep discharge protection	Yes
	The load reconnect should be provided at 90% of the battery capacity status	Yes
	Battery reverse polarity, Short circuit proection, reverse flow current protection	Yes
WARRANTY	Warranty for Solar home system including Battery from the date of supply	5 Years
	Warranty for PV Modules from the date of supply as per MNRE specn.,	>/=25 Years
	PV modules used in Solar Home Lighting System must be warranted for their output peak watt capacity, which should not be less than 90% at the end of Ten (10) years and 80% at the end of Twenty five (25) years	Yes
	The Warranty Card to be supplied with the system must contain the details of the system. The manufacturers can also provide additional information about the system and conditions of warranty as necessary	Yes
	OPERATION and MAINTENANCE MANUAL shall be furnish to the buyer / consignee as per MNRE (Off-grid Solar Applications Scheme 2016-17) (including IESNA LM-80 report of W-LEDs)	Yes
CERTIFICATION	Availability of Type Test Report from Central Govt./NABL/ILAC accredited lab to prove conformity to specification	Yes
	Storage battery shall comply with Bureau of Indian Standards of CRS as on date as applicable	Yes
	PV Modules shall comply with Bureau of Indian Standards of CRS as on date as applicable	Yes
<p>टिप्पणी Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.</p>		
<p>ईपीबीजी विवरण ePBG Detail</p>		
NA		
<p>नियम और शर्तें Terms and Conditions</p>		
<p>1. General Terms and Conditions-</p>		
<p>1.1 This contract is governed by the General Terms and Conditions, conditions stipulated to this Product/Service as provided in the Marketplace.</p>		
<p>1.2 This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable</p>		

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.