

अनुबंध | Contract



अनुबंध क्रमांक | Contract No: GEMC-511687758861595

अनुबंध तिथि | Generated Date : 11-Jul-2024

बोली/आरए/पीबीपी संख्या | Bid/RA/PBP No.: [GEM/2024/B/5108147](#)

संगठन विवरण Organisation Details	खरीदार विवरण Buyer Details
प्ररूप Type : State Government	पद Designation : mukhiya
मंत्रालय Ministry : -	संपर्क नंबर Contact No. : -
विभाग Department : Rural Development Department Bihar	ईमेल आईडी Email ID : pay11.rdd.bh@gembuyer.in
संगठन का नाम Organisation Name : Rural Development Department	जीएसटीआईएन GSTIN : -
कार्यालय क्षेत्र Office Zone: Block office sarairanjan	पता Address : Gram Panchayat office Harpurbarheta, SAMASTIPUR, BIHAR-848127, India

वित्तीय स्वीकृति विवरण Financial Approval Detail	भुगतान प्राधिकरण विवरण Paying Authority Details
आईएफडी सहमति IFD Concurrence : No	Role: BUYER
प्रशासनिक अनुमोदन का पदनाम Designation of Administrative Approval: GRAM SEVAK	भुगतान का तरीका Payment Mode: Offline
वित्तीय अनुमोदन का पदनाम Designation of Financial Approval: MUKHIYA HARPURBARHETA	पद Designation : mukhiya
	ईमेल आईडी Email ID : pay11.rdd.bh@gembuyer.in
	जीएसटीआईएन GSTIN : -
	पता Address: Gram Panchayat office Harpurbarheta, Samastipur, BIHAR-848127, India

विक्रेता विवरण Seller Details
जेम विक्रेता आईडी GeM Seller ID : GF9N220007171871
कंपनी का नाम Company Name : BABA CONSTRUCTION
संपर्क नंबर Contact No. : 07667371421
ईमेल आईडी Email ID : nikhilsingh.sam@gmail.com
पता Address : 05,Baba Palace,Musrigharari - Jandaha road,Musrigharari, Samastipur, BIHAR-848101, -
एमएसएमई सत्यापित MSME verified : No
एमएसएमई पंजीकरण संख्या MSME Registration number : -
जीएसटीआईएन GSTIN: 10CQIPK3919A2ZE (R)

*जिसके नाम के पक्ष में GST/TAX इनवॉइस पेश किया जाएगा | GST / Tax invoice to be raised in the name of - Buyer

वितरण निर्देश | Delivery Instructions : NA

उत्पाद विवरण Product Details						
#	आइटम विवरण Item Description	आइटम विवरण Ordered Quantity	इकाई Unit	इकाई मूल्य (INR) Unit Price (INR)	कर विभाजन (INR) Tax Bifurcation (INR)	मूल्य (INR में सभी शुल्क और कर सहित) Price (Inclusive of all Duties and Taxes in INR)
1	उत्पाद का नाम Product Name : Unbranded Air Walker/ Stroller Single ब्रांड Brand : NA ब्रांड प्रकार Brand Type : Unbranded कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Air Walker / Stroller - Outdoor Gym Equipment (Q3) मॉडल Model: GB 411 एचएसएन कोड HSN Code: HSN not specified by seller	2	pieces	76,700	जीएसटी GST (18%) : 23,399.695 जीएसटी उपकर 1 GST Cess 1 (0%) : 0 जीएसटी उपकर 2 GST Cess 2 (1 per accounting unit) : 2 जीएसटी पर इनपुट टैक्स क्रेडिट (आईटीसी) Input Tax Credit (ITC) on GST1 : - जीएसटी उपकर पर आईटीसी 1 ITC on GST Cess 1 : - जीएसटी उपकर पर आईटीसी 2 ITC on GST Cess 2 : -	153,400
2	उत्पाद का नाम Product Name : Unbranded Triple Twister (Three Sitting) Twister - Outdoor Gym Equipment ब्रांड Brand : NA ब्रांड प्रकार Brand Type : Unbranded कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Twister - Outdoor Gym Equipment (Q3) मॉडल Model: TWISTER एचएसएन कोड HSN Code: HSN not specified by seller	1	pieces	90,360	जीएसटी GST (18%) : 13,783.576 जीएसटी उपकर 1 GST Cess 1 (0%) : 0 जीएसटी उपकर 2 GST Cess 2 (1 per accounting unit) : 1 जीएसटी पर इनपुट टैक्स क्रेडिट (आईटीसी) Input Tax Credit (ITC) on GST1 : - जीएसटी उपकर पर आईटीसी 1 ITC on GST Cess 1 : - जीएसटी उपकर पर आईटीसी 2 ITC on GST Cess 2 : -	90,360
					जीएसटी GST (18%) : 11,519.847	

3	<p>उत्पाद का नाम Product Name : Unbranded Chest Press Single - Max user weight - 100 kilogram</p> <p>ब्रांड Brand : NA</p> <p>ब्रांड प्रकार Brand Type : Unbranded</p> <p>कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM</p> <p>कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM</p> <p>श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Chest Press - Outdoor Gym Equipments (Q3)</p> <p>मॉडल Model: MS</p> <p>एचएसएन कोड HSN Code: HSN not specified by seller</p>	1	pieces	75,520	<p>जीएसटी उपकर 1 GST Cess 1 (0%) : 0</p> <p>जीएसटी उपकर 2 GST Cess 2 (1 per accounting unit) : 1</p> <p>जीएसटी पर इनपुट टैक्स क्रेडिट (आईटीसी) Input Tax Credit (ITC) on GST1 : -</p> <p>जीएसटी उपकर पर आईटीसी 1 ITC on GST Cess 1 : -</p> <p>जीएसटी उपकर पर आईटीसी 2 ITC on GST Cess 2 : -</p>	75,520
4	<p>उत्पाद का नाम Product Name : Unbranded Leg Press - Outdoor Gym Equipments Leg Press Double</p> <p>ब्रांड Brand : NA</p> <p>ब्रांड प्रकार Brand Type : Unbranded</p> <p>कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM</p> <p>कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM</p> <p>श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Leg Press - Outdoor Gym Equipments (Q3)</p> <p>मॉडल Model: HEVUX LEG PRESS DOU</p> <p>एचएसएन कोड HSN Code: HSN not specified by seller</p>	2	pieces	82,010	<p>जीएसटी GST (18%) : 25,019.695</p> <p>जीएसटी उपकर 1 GST Cess 1 (0%) : 0</p> <p>जीएसटी उपकर 2 GST Cess 2 (1 per accounting unit) : 2</p> <p>जीएसटी पर इनपुट टैक्स क्रेडिट (आईटीसी) Input Tax Credit (ITC) on GST1 : -</p> <p>जीएसटी उपकर पर आईटीसी 1 ITC on GST Cess 1 : -</p> <p>जीएसटी उपकर पर आईटीसी 2 ITC on GST Cess 2 : -</p>	164,020
5	<p>उत्पाद का नाम Product Name : Unbranded 750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm Parallel Bar - Outdoor Gym Equipment</p> <p>ब्रांड Brand : NA</p> <p>ब्रांड प्रकार Brand Type : Unbranded</p> <p>कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM</p> <p>कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM</p> <p>श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Parallel Bar - Outdoor Gym Equipment (Q3)</p> <p>मॉडल Model: BAR-0125</p> <p>एचएसएन कोड HSN Code: HSN not specified by seller</p>	1	pieces	75,520	<p>जीएसटी GST (18%) : 11,519.847</p> <p>जीएसटी उपकर 1 GST Cess 1 (0%) : 0</p> <p>जीएसटी उपकर 2 GST Cess 2 (1 per accounting unit) : 1</p> <p>जीएसटी पर इनपुट टैक्स क्रेडिट (आईटीसी) Input Tax Credit (ITC) on GST1 : -</p> <p>जीएसटी उपकर पर आईटीसी 1 ITC on GST Cess 1 : -</p> <p>जीएसटी उपकर पर आईटीसी 2 ITC on GST Cess 2 : -</p>	75,520
6	<p>उत्पाद का नाम Product Name : Unbranded Two Wheel Shoulder Builder/ Arm Wheel- Outdoor Gym Equipment</p> <p>ब्रांड Brand : NA</p> <p>ब्रांड प्रकार Brand Type : Unbranded</p> <p>कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM</p> <p>कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM</p> <p>श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Shoulder Builder / Arm Wheel - Outdoor Gym Equipment (Q3)</p> <p>मॉडल Model: ARM WHEEL 001</p> <p>एचएसएन कोड HSN Code: HSN not specified by seller</p>	1	pieces	76,700	<p>जीएसटी GST (18%) : 11,699.847</p> <p>जीएसटी उपकर 1 GST Cess 1 (0%) : 0</p> <p>जीएसटी उपकर 2 GST Cess 2 (1 per accounting unit) : 1</p> <p>जीएसटी पर इनपुट टैक्स क्रेडिट (आईटीसी) Input Tax Credit (ITC) on GST1 : -</p> <p>जीएसटी उपकर पर आईटीसी 1 ITC on GST Cess 1 : -</p> <p>जीएसटी उपकर पर आईटीसी 2 ITC on GST Cess 2 : -</p>	76,700
7	<p>उत्पाद का नाम Product Name : Unbranded Sit Up Board Double Station</p> <p>ब्रांड Brand : NA</p> <p>ब्रांड प्रकार Brand Type : Unbranded</p> <p>कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM</p> <p>कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM</p> <p>श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Sit Up Board - Outdoor Gym Equipment (Q3)</p> <p>मॉडल Model: SPE-SIT-006</p> <p>एचएसएन कोड HSN Code: HSN not specified by seller</p>	2	pieces	86,230	<p>जीएसटी GST (18%) : 26,307.153</p> <p>जीएसटी उपकर 1 GST Cess 1 (0%) : 0</p> <p>जीएसटी उपकर 2 GST Cess 2 (1 per accounting unit) : 2</p> <p>जीएसटी पर इनपुट टैक्स क्रेडिट (आईटीसी) Input Tax Credit (ITC) on GST1 : -</p> <p>जीएसटी उपकर पर आईटीसी 1 ITC on GST Cess 1 : -</p> <p>जीएसटी उपकर पर आईटीसी 2 ITC on GST Cess 2 : -</p>	172,460
8	<p>उत्पाद का नाम Product Name : Unbranded Triple Twister (Three Sitting) Twister - Outdoor Gym Equipment</p> <p>ब्रांड Brand : NA</p> <p>ब्रांड प्रकार Brand Type : Unbranded</p> <p>कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM</p> <p>कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM</p> <p>श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Twister - Outdoor Gym Equipment (Q3)</p> <p>मॉडल Model: TWISTER</p> <p>एचएसएन कोड HSN Code: HSN not specified by seller</p>	1	pieces	90,360	<p>जीएसटी GST (18%) : 13,783.576</p> <p>जीएसटी उपकर 1 GST Cess 1 (0%) : 0</p> <p>जीएसटी उपकर 2 GST Cess 2 (1 per accounting unit) : 1</p> <p>जीएसटी पर इनपुट टैक्स क्रेडिट (आईटीसी) Input Tax Credit (ITC) on GST1 : -</p> <p>जीएसटी उपकर पर आईटीसी 1 ITC on GST Cess 1 : -</p> <p>जीएसटी उपकर पर आईटीसी 2 ITC on GST Cess 2 : -</p>	90,360
	<p>उत्पाद का नाम Product Name : Unbranded Two Wheel Shoulder Builder/ Arm Wheel- Outdoor Gym Equipment</p> <p>ब्रांड Brand : NA</p> <p>ब्रांड प्रकार Brand Type : Unbranded</p> <p>कैटलॉग की स्थिति Catalogue Status: Catalogue not verified by OEM</p>				<p>जीएसटी GST (18%) : 11,702.898</p> <p>जीएसटी उपकर 1 GST Cess 1 (0%) : 0</p> <p>जीएसटी उपकर 2 GST Cess 2 (1 per accounting unit) : 1</p> <p>जीएसटी पर इनपुट टैक्स क्रेडिट</p>	

9	कैसे बेचा जा रहा है Selling As : Reseller not verified by OEM श्रेणी का नाम और चतुर्थांश Category Name & Quadrant : Shoulder Builder / Arm Wheel - Outdoor Gym Equipment (Q3) मॉडल Model: ARM WHEEL 001 एचएसएन कोड HSN Code: HSN not specified by seller	1	pieces	76,720	(आईटीसी) Input Tax Credit (ITC) on GST1 : - जीएसटी उपकर पर आईटीसी 1 ITC on GST Cess 1 : - जीएसटी उपकर पर आईटीसी 2 ITC on GST Cess 2 : -	76,720
कुल ऑर्डर मूल्य Total Order Value (in INR)						975,060
परेशिती विवरण Consignee Detail						
क्र.सं. S.No	परेशिती Consignee	वस्तु Item	लॉट नंबर Lot No.	मात्रा Quantity	दिनांक के बाद डिलीवरी शुरू करना है Delivery Start After	वितरण पूरा कब तक करना है Delivery To Be Completed By
1	पद Designation : - ईमेल आईडी Email ID : pay11.rdd.bh@gembuyer.in संपर्क Contact : - जीएसटीआईएन GSTIN : - पता Address : Gram Panchayat office Harpurbarheta, SAMASTIPUR, BIHAR-848127, India	Unbranded Air Walker/ Stroller Single	-	2	11-Jul-2024	26-Jul-2024
		Unbranded Triple Twister (Three Sitting) Twister - Outdoor Gym Equipment	-	1	11-Jul-2024	26-Jul-2024
		Unbranded Chest Press Single - Max user weight - 100 kilogram	-	1	11-Jul-2024	26-Jul-2024
		Unbranded Leg Press - Outdoor Gym Equipments Leg Press Double	-	2	11-Jul-2024	26-Jul-2024
		Unbranded 750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm Parallel Bar - Outdoor Gym Equipment	-	1	11-Jul-2024	26-Jul-2024
		Unbranded Two Wheel Shoulder Builder/ Arm Wheel- Outdoor Gym Equipment	-	1	11-Jul-2024	26-Jul-2024
		Unbranded Sit Up Board Double Station	-	2	11-Jul-2024	26-Jul-2024
		Unbranded Triple Twister (Three Sitting) Twister - Outdoor Gym Equipment	-	1	11-Jul-2024	26-Jul-2024
		Unbranded Two Wheel Shoulder Builder/ Arm Wheel- Outdoor Gym Equipment	-	1	11-Jul-2024	26-Jul-2024
Product Specification for Unbranded Air Walker/ Stroller Single						
विनिर्देश Specification	उप-विनिर्देश Sub-Spec				मूल्य Value	
TYPE	Type				Single	
SIZE/ DIMENSIONS	Length				800 millimeter	
	Width				400 millimeter	
	Height				1200 millimeter	
CAPACITY	Maximum User Weight (Kg)				100 kilogram	
	Governing Specification for GI Pipes				BIS specification No IS 1161:2014, latest	
	All the GI Pipes are ISI marked				Yes	
	Main Frame				80mm Nominal Bore G.I. Pipe	
	Main Frame Pipe, Class as per IS 1239				Heavy	
	Designation of Main Frame Pipe (as per IS 1161)				NA	
	leg movement frame				32mm Nominal Bore G.I. Pipe	

MATERIAL	Leg Movement Frame Pipe, Class as per IS 1239	Heavy
	Designation of Leg movement frame Pipe (as per IS 1161)	NA
	Handle Frame	25mm Nominal bore G.I. pipe
	Handle Frame Pipe, Class as per IS 1239	Heavy
	Designation of Handle Frame Pipe (as per IS 1161) Hint must be declared as per clause 3 of IS 1161 indicating nominal bore, wall thickness and grade (not applicable for pipe as per IS 1239)	NA
	Movement must be supplied with bearings	Yes
	Bearings	Ball Bearing
	Bearings shall be self lubricating and sealed for protection against Rain and dust etc	Yes
	Foot Rest	Aluminum casting material
	MS Foundation Plate Thickness	10 millimeter
	Foundation Pipes with anchoring	500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	80mm
	Foundation Pipe, Class as per IS 1239	Heavy
	Designation of Foundation Pipe (as per IS 1161)	NA
	Galvanization of all Pipes	Zinc coating on the tubes shall be in accordance with IS 4736 latest.
	Nuts and Bolts for Assembly	Stainless Steel
	Closing Caps of open ends of the pipes, bearings, bushes and base	Fibre Reinforced Plastic
	Thickness of closing caps (min)	2 millimeter
	All Plastic Components	U V stabilised, weather resistance
	COLOUR	Colour
Paint// Finish		Powder Coated, UV resistant
Paint Coating Thickness (min)		80 micrometer
OTHER REQUIREMENTS	Ergonomic Design	Yes
	Foot rest shall be antislip/ antiskid	Yes
	Moving (swinging) Scope should be Limited	Yes
	There shall be no crushing or searing points for user between moving and / or stationary parts of equipment during use	Yes
	Equipment shall be free from entrapments and sharp edges	Yes
	Installation Instructions must be provided	Yes
	Installation	Included
	Safety and quality Requirements	European Standard EN 16630: 2015 latest
	Instruction Plate	Stainless Steel, Size 150 X 230 X 0.7mm, with indelible printing
CERTIFICATION	Certification (Safety and Quality Requirements)	As per European Standard EN 16630
	Registration No and Validity of Registration	NA
APPROVAL	Drawing depicting detailed dimensions and foundation details shall be got approved from buyer before installation, if desired by buyer	Yes
WARRANTY	Warranty (years)	2 year
टिप्पणी Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.		
Product Specification for Unbranded Triple Twister (Three Sitting) Twister - Outdoor Gym Equipment		
विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
TYPE	Type	Triple Twister (Three Sitting)
SIZE/ DIMENSIONS	Length	1455 millimeter
	Width	1855 millimeter

	Height	1465 millimeter
CAPACITY	Maximum User Weight (Kg)	110 kilogram
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes
	Main Central Pipe	100mm Nominal Bore G.I. Pipe
	Main Frame Pipe, Class as per IS 1239	Heavy
	Main Central Pipe (As per Clause 3, of IS 1161) Nominal Bore & Wall Thickness	100 mm NB with 3.6 mm Thickness
	Grade Material as per table 2 of IS 1161	YSt 310
	Standing/ Sitting Twister Frame Pipe	32 mm Nominal Bore G.I. Pipe
	Standing/ Sitting Twister Frame Pipe, Class as per IS 1239	Heavy
	Standing/ Sitting Twister Frame Pipe (As per Clause 3, of IS 1161) Nominal Bore & Wall Thickness	40 mm NB with 2.9 mm Thickness
	Grade Material as per table 2 IS 1161	YSt 310
	Rotating Disk Support Pipe at Bottom Pipe	100 mm Nominal Bore G.I. Pipe
	Rotating Disk Support Pipe, Class as per IS 1239	Heavy
	Rotating Disk Support Pipe (as per IS 1161) as per Clause 3, Nominal Bore & Wall Thickness	100 mm NB with 4.5 mm Thickness
	Grade Material (as per table 2 of IS 1161)	YSt 310
	Handle Frame Pipe	32mm Nominal bore G.I. pipe
	Handle Frame Pipe, Class as per IS 1239	Heavy
	Handle Frame Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	32 mm NB with 4 mm Thickness
	Grade Material per table 2 of IS 1161	YSt 310
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	100mm
	Foundation Pipe, Class as per IS 1239	Heavy
	Foundation Pipe Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	100 mm NB with 4.5 mm Thickness
	Grade Material (as per table 2 of IS 1161)	YSt 310
	M S Foundation Plate Thickness	12 millimeter
	Galvanization of all Pipes	Zinc coating on the tubes shall be in accordance with IS 4736 latest.
	Movement must be supplied with bearings	Yes
	Bearings	Tapered Roller Bearing
	Bearings shall be self lubricating and sealed for protection against Rain and dust etc	Yes
	Nuts and Bolts for Assembly	Stainless Steel
	Foot Rest	Fibre Reinforced Plastic
	Closing Caps of open ends of the pipes, bearings, bushes and base	SS 304 Grade Stainless Steel
	Thickness of closing caps (min)	3 millimeter
	All Plastic Components	U V stabilised, weather resistance
COLOUR	Colour	As per buyer's requirements
	Paint// Finish	Powder Coated, UV resistant
	Paint Coating Thickness (min)	100 micrometer
OTHER REQUIREMENTS	Other Requirement	Ergonomic Design, Equipment shall be free from entrapments and sharp edges, Installation Instructions must be provided
	Installation	Not Included
	Safety and quality Requirements	European Standard EN 16630: 2015 latest
	Instruction Plate	Stainless Steel, Size 150 X 230 X 0.7mm, with indelible printing
CERTIFICATION	Certification (Safety and Quality Requirements)	As per European Standard EN 16630
	Registration No and Validity of Registration	QMS-095781602/KGW-20

APPROVAL	Drawing depicting detailed dimensions and foundation details shall be got approved from buyer before installation, if desired by buyer	Yes
WARRANTY	Warranty (years)	4 year
<p>टिप्पणी Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.</p>		
<p>Product Specification for Unbranded Chest Press Single - Max user weight - 100 kilogram</p>		
विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
TYPE	Type	Chest Press Single
SIZE	Length	1000 millimeter
	Width	710 millimeter
	Height	2150 millimeter
CAPACITY	Maximum User Weight (Kg)	100 kilogram
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes
	Main Central Pipe	100mm Nominal Bore G.I. Pipe
	Main Central Pipe, Class as per IS 1239	Heavy
	Designation of Main Central Pipe (as per IS 1161)	100 MM OD GI PIPE
	Handle Frame	32mm Nominal bore G.I. pipe
	Handle Frame Pipe, Class as per IS 1239	Heavy
	Designation of Handle Frame Pipe (as per IS 1161)	32MM OD GI PIPE
	Seat Frame	32mm Nominal Bore G.I. Pipe
	Seat Frame Pipe, Class as per IS 1239	Heavy
	Designation of Seat Frame Pipe (as per IS 1161)	25 MM GI PIPE
	Connecting Links	25mm Nominal Bore G.I. Pipe
	Connecting Links Pipe, Class as per IS 1239	Heavy
	Designation of connecting link Pipe (as per IS 1161)	25 MM GI PIPE
	Foot Rest Pipe	25mm Nominal Bore G.I. Pipe
	Foot Rest Pipe, Class as per IS 1239	Heavy
	Designation of Foot Rest Pipe (as per IS 1161)	25 MM GI PIPE
	MS Foundation Plate Thickness	10 millimeter
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	80mm
	Foundation Pipe, Class as per IS 1239	Heavy
	Designation of Foundation Pipe (as per IS 1161)	80 MM GI PIPE
	Galvanization of all Pipes	Zinc coating on the tubes shall be in accordance with IS 4736 latest.
	Seat and Back Rest	2mm Thick G.I. Seat with uniform bending radius to avoid sharp edges
	Hand Grips	Rubber
	Nuts and Bolts for Assembly	G.I.
	Movement must be supplied with bearings	Yes
	Bearings	Ball Bearing
	Bearings shall be self lubricating and sealed for protection against Rain and dust etc	Yes
	Closing Caps of open ends of the pipes, bearings, bushes and base	Fibre Reinforced Plastic
	Thickness of closing caps (min)	2 millimeter
	All Plastic Components	U V stabilised, weather resistance

COLOUR	Colour	As per buyer's requirements
	Paint// Finish	Powder Coated, UV resistant
	Paint Coating Thickness (min)	80 micrometer
OTHER REQUIREMENTS	Ergonomic Design	Yes
	Moving Scope should be Limited	Yes
	There shall be no crushing or searing points for user between moving and / or stationary parts of equipment during use	Yes
	Equipment shall be free from entrapments and sharp edges	Yes
	Installation Instructions must be provided	Yes
	Installation	Included
	Safety and quality Requirements	European Standard EN 16630: 2015 latest
	Instruction Plate	Stainless Steel, Size 150 X 230 X 0.7mm, with indelible printing
CERTIFICATION	Certification (Safety and Quality Requirements)	As per European Standard EN 16630
	Registration No and Validity of Registration	91/Q/8545 17/05/2021
APPROVAL	Drawing depicting detailed dimensions and foundation details shall be got approved from buyer before installation, if desired by buyer	Yes
WARRANTY	Warranty (years)	2 year
टिप्पणी Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.		
Product Specification for Unbranded Leg Press - Outdoor Gym Equipments Leg Press Double		
विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
TYPE	Type	Leg Press Double
SIZE	Length	1700 millimeter
	Width	700 millimeter
	Height	2000 millimeter
CAPACITY	Maximum User Weight (Kg)	120 kilogram
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1239 (Part 1)- 2004, latest
	All the GI Pipes are ISI marked	Yes
	Main Central Pipe	80mm Nominal Bore G.I. Pipe
	Main Central Pipe, Class as per IS 1239	Heavy
	Designation of Main Central Pipe (as per IS 1161)	125 MM NB G. I. PIPE
	Moving Frame Pipe	40mm Nominal bore G.I. pipe
	Moving Frame Pipe, Class as per IS 1239	Heavy
	Designation of Moving Frame Pipe (as per IS 1161)	40 MM GI PIPE
	Foot Rest Frame/ Foot Rest Hinging Pipe	32mm Nominal Bore G.I. Pipe
	Foot Rest Frame Pipe, Class as per IS 1239	Heavy
	Designation of Foot Rest Frame Pipe (as per IS 1161)	40 MM BORE GI PIPE
	Connecting Links	12mm thick MS plates
	Connecting Links Pipe, Class as per IS 1239	Heavy
	Designation of connecting link Pipe (as per IS 1161)	40 MM N BORE GI PIPE
	MS Foundation Plate Thickness	12 millimeter
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	150mm
	Foundation Pipe, Class as per IS 1239	Heavy
	Designation of Foundation Pipe (as per IS 1161)	Dia 125 mm G. I Pipe

	Galvanization of all Pipes	Zinc coating on the tubes shall be in accordance with IS 4736 latest.
	Nuts and Bolts for Assembly	G.I.
	Movement must be supplied with bearings	Yes
	Bearings	Tapered Roller Bearing
	Bearings shall be self lubricating and sealed for protection against Rain and dust etc	Yes
	Seat and Back Rest	6mm thick, Fibre Reinforced plastic with uniform bending radius to avoid sharp edges
	Foot Rest	HDPE
	Closing Caps of open ends of the pipes, bearings, bushes and base	HDPE
	Thickness of closing caps (min)	3 millimeter
	All Plastic Components	U V stabilised, weather resistance
COLOUR	Colour	As per buyer's requirements
	Paint// Finish	Powder Coated, UV resistant
	Paint Coating Thickness (min)	80 micrometer
OTHER REQUIREMENTS	Ergonomic Design	Yes
	Foot rest shall be antislip/ antiskid	Yes
	Moving Scope should be Limited	Yes
	There shall be no crushing or searing points for user between moving and / or stationary parts of equipment during use	Yes
	Equipment shall be free from entrapments and sharp edges	Yes
	Installation Instructions must be provided	Yes
	Installation	Included
	Safety and quality Requirements	European Standard EN 16630: 2015 latest
	Instruction Plate	Stainless Steel, Size 150 X 230 X 0.7mm, with indelible printing
CERTIFICATION	Certification (Safety and Quality Requirements)	No
	Registration No and Validity of Registration	NA
APPROVAL	Drawing depicting detailed dimensions and foundation details shall be got approved from buyer before installation, if desired by buyer	Yes
WARRANTY	Warranty (years)	2 year
टिप्पणी Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.		
Product Specification for Unbranded 750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm Parallel Bar - Outdoor Gym Equipment		
विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
Size/ Dimensions	Length	1600 millimeter
	Height	1800 millimeter
Type	Type	Parallel Bar / Double Bar consisting of two frames with each frame consisting of one Horizontal bar and two vertical bars.
	Governing Specification for GI Pipes	BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes
	Vertical / Standing Pipes	80 mm Nominal Bore G.I. Pipe
	Vertical/ Standing Pipes, Class as per IS 1239	Heavy
	Vertical / Standing Pipe (as per Clause 3 of IS 1161) , Nominal Bore & Wall Thickness	80 mm NB with 4.8 mm Thickness
	Horizontal Pipe	40 mm Nominal Bore G.I. Pipe
	Horizontal Pipe, Class as per IS 1239	Heavy
	Horizontal Pipe (As per Clause 3, of IS 1161) Nominal Bore & Wall Thickness	40 mm NB with 4 mm Thickness

Material	Grade Material as per table 2 of IS 1161	YSt 310
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	80 mm
	Foundation Pipe, Class as per IS 1239	Heavy
	Foundation Pipe Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	40 mm NB with 4 mm Thickness
	M S Foundation Plate Thickness	12 millimeter
	Galvanization of all Pipes	Zinc coating on the tubes shall be in accordance with IS 4736 latest.
	Movement must be supplied with bearings	Yes
	Bearings	Ball Bearing
	Bearings shall be self lubricating and sealed for protection against Rain and dust etc	Yes
	Nuts and Bolts for Assembly	G.I.
	Foot Rest	C.I.
	Closing Caps of open ends of the pipes, bearings, bushes and base	Fibre Reinforced Plastic
	Thickness of closing caps (min)	3 millimeter
	All Plastic Components	U V stabilised, weather resistance
Colour	Colour	As per buyer's requirements
	Paint// Finish	Powder Coated, UV resistant
	Paint Coating Thickness (min)	100 micrometer
Other Requirements	Other Requirement	Equipment shall be free from entrapments and sharp edges
	Installation	Included
	Safety and quality Requirements	European Standard EN 16630: 2015 latest
	Instruction Plate	Stainless Steel, Size 150 X 230 X 0.7mm, with indelible printing
Certification	Certification (Safety and Quality Requirements)	As per European Standard EN 16630
	Registration No and Validity of Registration	NA
Approval	Drawing depicting detailed dimensions and foundation details shall be got approved from buyer before installation, if desired by buyer	Yes
Warranty	Warranty (years)	2 year
<p>टिप्पणी Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.</p>		
<p>Product Specification for Unbranded Two Wheel Shoulder Builder/ Arm Wheel- Outdoor Gym Equipment</p>		
विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
TYPE	Type	Two Wheel
DIMENSIONS	Height of Main Central Pole from ground	1600 millimeter
	Outside Diameter of first wheel	750 millimeter
	Outside Diameter of second wheel	750 millimeter
	Outside Diameter of third wheel	850 millimeter
	Height of first wheel from ground	1150 millimeter
	Height of second wheel from ground	1000 millimeter
	Height of third wheel from ground	1200 millimeter
	Governing Specification for GI Pipes	BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes
	Main Central Pipe construction	125 mm Nominal Bore G.I. Pipe
	Main Central Pipe, Class as per IS 1239	Medium
	Designation of Main Central Pipe (as per IS 1161)	YES
	Ring (Wheel)	32mm Nominal Bore G.I. Pipe

MATERIAL	Ring (Wheel) Pipe, Class as per IS 1239	Medium
	Designation of Ring (Wheel) Pipe (as per IS 1161)	YES
	Pipe of Spokes of Wheel	20mm Nominal bore G.I. pipe
	Pipe of Spoke of Wheel , Class as per IS 1239	Medium
	Designation of Pipe of Spoke of Wheel (as per IS 1161)	YES
	Number of Spokes in Wheel	5
	Connector Pipe (between Main Central Pipe and Wheel)	50 mm Nominal bore G.I. pipe
	Connector Pipe, Class as per IS 1239	Medium
	Designation of connecting pipe (as per IS 1161)	YES
	MS Foundation Plate Thickness	12 millimeter
	Foundation Pipes with anchoring	500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	150mm
	Foundation Pipe, Class as per IS 1239	Medium
	Designation of Foundation Pipe (as per IS 1161)	YES
	Galvanization of all Pipes	Zinc coating on the tubes shall be in accordance with IS 4736 latest.
	Nuts and Bolts for Assembly	Stainless Steel
	Knobs on the Wheel for Gripping	Rubber
	Movement must be supplied with bearings	Yes
	Bearings	Tapered Roller Bearing
	Bearings shall be self lubricating and sealed for protection against Rain and dust etc	Yes
COLOUR	Closing Caps of open ends of the pipes, bearings, bushes and base	Fibre Reinforced Plastic
	Thickness of closing caps (min)	3 millimeter
	All Plastic Components	U V stabilised, weather resistance
OTHER REQUIREMENTS	Colour	Blue
	Paint// Finish	Poly Urethane Paint, UV Resistant
	Paint Coating Thickness (min)	100 micrometer
CERTIFICATION	Ergonomic Design	Yes
	There shall be no crushing or searing points for user between moving and / or stationary parts of equipment during use	Yes
	Equipment shall be free from entrapments and sharp edges	Yes
	Installation Instructions must be provided	Yes
	Installation	Included
	Safety and quality Requirements	European Standard EN 16630: 2015 latest
	Instruction Plate	Stainless Steel, Size 150 X 230 X 0.7mm, with indelible printing
APPROVAL	Certification (Safety and Quality Requirements)	As per European Standard EN 16630
	Registration No and Validity of Registration	NA
WARRANTY	Warranty (years)	2 year
<p>टिप्पणी Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.</p>		
<p>Product Specification for Unbranded Sit Up Board Double Station</p>		
विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
TYPE	Name of the product	Sit Up Board

	Type	Double Station
SIZE/ DIMENSIONS	Length	1390 millimeter
	Width	1390 millimeter
	Height	1000 millimeter
MATERIAL	Type of Back Rest	Set of Rectangular Flat Pipes
	Material of Back Rest	Mild Steel Plate
	Thickness of Back Rest	5 millimeter
	Governing Specification for GI Pipes	BIS specification No IS 1239 (Part 1)- 2004, latest
	All the GI Pipes are ISI marked	Yes
	Main Frame/Central Pipe	125mm Nominal Bore G.I. Pipe
	Main Frame/Central Pipe, Class as per IS 1239	Heavy
	Main Frame/Central Pipe (As per Clause 3, of IS 1161) Nominal Bore & Wall Thickness	100 mm NB with 3.6 mm Thickness
	Grade of Material as per table 2 of IS 1161	Not Applicable
	Foot Rest Pipe	50mm Nominal Bore G.I. Pipe
	Foot Rest Pipe , Class as per IS 1239	Heavy
	Foot Rest Pipe (As per as per Clause 3, of IS 1161) , Nominal Bore & Wall Thickness	40 mm NB with 2.9 mm Thickness
	Grade of Material as per table 2 IS 1161	Not Applicable
	Back Rest Frame Pipe and Connecting Links	40 mm Nominal Bore G.I. Pipe
	Back Rest Frame Pipe and Connecting Links, Class as per IS 1239	Heavy
	Back Rest Frame Pipe and Connecting Links (As per Clause 3, of IS 1161) Nominal Wall & Thickness	32 mm NB with 2.6 mm Thickness
	Grade of Material (as per table 2 of IS 1161)	Not Applicable
	Leg Support Pipe	50mm Nominal bore G.I. pipe
	Leg Support Pipe , Class as per IS 1239	Heavy
	Leg Support Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	40 mm NB with 2.9 mm Thickness
	Grade of Material per table 2 of IS 1161	Not Applicable
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	150mm
	Foundation Pipe, Class as per IS 1239	Heavy
	Foundation Pipe Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	100 mm NB with 3.6 mm Thickness
	Grade of Material (as per table 2 of IS 1161)	Not Applicable
	M S Foundation Plate Thickness	10 millimeter
	Galvanization of all Pipes	Zinc coating on the tubes shall be in accordance with IS 4736 latest.
	Nuts and Bolts for Assembly	G.I.
	Closing Caps of open ends of the pipes, bearings, bushes and base	Fibre Reinforced Plastic
	Thickness of closing caps (min)	3 millimeter
	All Plastic Components	U V stabilised, weather resistance
COLOUR	Colour	As per buyer's requirements
	Paint// Finish	Poly Urethane Paint, UV Resistant
	Paint Coating Thickness (min)	100 micrometer
OTHER REQUIREMENTS	Other Requirement	Ergonomic Design, Equipment shall be free from entrapments and sharp edges, Installation Instructions must be provided
	Installation	Not Included
	Safety and quality Requirements	European Standard EN 16630: 2015 latest
	Instruction Plate	Stainless Steel, Size 150 X 230 X 0.7mm, with indelible printing
CERTIFICATION	Certification (Safety and Quality Requirements)	No
	Registration No and Validity of Registration	UQ-2021012544

APPROVAL	Drawing depicting detailed dimensions and foundation details shall be got approved from buyer before installation, if desired by buyer	Yes
WARRANTY	Warranty (years)	2 year
<p>टिप्पणी Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.</p>		
<p>Product Specification for Unbranded Triple Twister (Three Sitting) Twister - Outdoor Gym Equipment</p>		
विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
TYPE	Type	Triple Twister (Three Sitting)
SIZE/ DIMENSIONS	Length	1455 millimeter
	Width	1855 millimeter
	Height	1465 millimeter
CAPACITY	Maximum User Weight (Kg)	110 kilogram
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes
	Main Central Pipe	100mm Nominal Bore G.I. Pipe
	Main Frame Pipe, Class as per IS 1239	Heavy
	Main Central Pipe (As per Clause 3, of IS 1161) Nominal Bore & Wall Thickness	100 mm NB with 3.6 mm Thickness
	Grade Material as per table 2 of IS 1161	YSt 310
	Standing/ Sitting Twister Frame Pipe	32 mm Nominal Bore G.I. Pipe
	Standing/ Sitting Twister Frame Pipe, Class as per IS 1239	Heavy
	Standing/ Sitting Twister Frame Pipe (As per Clause 3, of IS 1161) Nominal Bore & Wall Thickness	40 mm NB with 2.9 mm Thickness
	Grade Material as per table 2 IS 1161	YSt 310
	Rotating Disk Support Pipe at Bottom Pipe	100 mm Nominal Bore G.I. Pipe
	Rotating Disk Support Pipe, Class as per IS 1239	Heavy
	Rotating Disk Support Pipe (as per IS 1161) as per Clause 3, Nominal Bore & Wall Thickness	100 mm NB with 4.5 mm Thickness
	Grade Material (as per table 2 of IS 1161)	YSt 310
	Handle Frame Pipe	32mm Nominal bore G.I. pipe
	Handle Frame Pipe, Class as per IS 1239	Heavy
	Handle Frame Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	32 mm NB with 4 mm Thickness
	Grade Material per table 2 of IS 1161	YSt 310
	Foundation Pipes with anchoring	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	100mm
	Foundation Pipe, Class as per IS 1239	Heavy
	Foundation Pipe Pipe (as per IS 1161) as per clause 3, Nominal Wall & Thickness	100 mm NB with 4.5 mm Thickness
	Grade Material (as per table 2 of IS 1161)	YSt 310
	M S Foundation Plate Thickness	12 millimeter
	Galvanization of all Pipes	Zinc coating on the tubes shall be in accordance with IS 4736 latest.
	Movement must be supplied with bearings	Yes
	Bearings	Tapered Roller Bearing
	Bearings shall be self lubricating and sealed for protection against Rain and dust etc	Yes
	Nuts and Bolts for Assembly	Stainless Steel
	Foot Rest	Fibre Reinforced Plastic
	Closing Caps of open ends of the pipes, bearings, bushes and base	SS 304 Grade Stainless Steel

	Thickness of closing caps (min)	3 millimeter
	All Plastic Components	U V stabilised, weather resistance
COLOUR	Colour	As per buyer's requirements
	Paint// Finish	Powder Coated, UV resistant
	Paint Coating Thickness (min)	100 micrometer
OTHER REQUIREMENTS	Other Requirement	Ergronomic Design, Equipment shall be free from entrapments and sharp edges, Installation Instructions must be provided
	Installation	Not Included
	Safety and quality Requirements	European Standard EN 16630: 2015 latest
	Instruction Plate	Stainless Steel, Size 150 X 230 X 0.7mm, with indelible printing
CERTIFICATION	Certification (Safety and Quality Requirements)	As per European Standard EN 16630
	Registration No and Validity of Registration	QMS-095781602/KGW-20
APPROVAL	Drawing depicting detailed dimensions and foundation details shall be got approved from buyer before installation, if desired by buyer	Yes
WARRANTY	Warranty (years)	4 year
टिप्पणी Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.		
Product Specification for Unbranded Two Wheel Shoulder Builder/ Arm Wheel- Outdoor Gym Equipment		
विनिर्देश Specification	उप-विनिर्देश Sub-Spec	मूल्य Value
TYPE	Type	Two Wheel
DIMENSIONS	Height of Main Central Pole from ground	1600 millimeter
	Outside Diameter of first wheel	750 millimeter
	Outside Diameter of second wheel	750 millimeter
	Outside Diameter of third wheel	850 millimeter
	Height of first wheel from ground	1150 millimeter
	Height of second wheel from ground	1000 millimeter
	Height of third wheel from ground	1200 millimeter
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes
	Main Central Pipe construction	125 mm Nominal Bore G.I. Pipe
	Main Central Pipe, Class as per IS 1239	Medium
	Designation of Main Central Pipe (as per IS 1161)	YES
	Ring (Wheel)	32mm Nominal Bore G.I. Pipe
	Ring (Wheel) Pipe, Class as per IS 1239	Medium
	Designation of Ring (Wheel) Pipe (as per IS 1161)	YES
	Pipe of Spokes of Wheel	20mm Nominal bore G.I. pipe
	Pipe of Spoke of Wheel , Class as per IS 1239	Medium
	Designation of Pipe of Spoke of Wheel (as per IS 1161)	YES
	Number of Spokes in Wheel	5
	Connector Pipe (between Main Central Pipe and Wheel)	50 mm Nominal bore G.I. pipe
	Connector Pipe, Class as per IS 1239	Medium
	Designation of connecting pipe (as per IS 1161)	YES
	MS Foundation Plate Thickness	12 millimeter
	Foundation Pipes with anchoring	500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	Nominal Bore of Foundation Pipe	150mm
	Foundation Pipe, Class as per IS 1239	Medium

	Designation of Foundation Pipe (as per IS 1161)	YES
	Galvanization of all Pipes	Zinc coating on the tubes shall be in accordance with IS 4736 latest.
	Nuts and Bolts for Assembly	Stainless Steel
	Knobs on the Wheel for Gripping	Rubber
	Movement must be supplied with bearings	Yes
	Bearings	Tapered Roller Bearing
	Bearings shall be self lubricating and sealed for protection against Rain and dust etc	Yes
	Closing Caps of open ends of the pipes, bearings, bushes and base	Fibre Reinforced Plastic
	Thickness of closing caps (min)	3 millimeter
	All Plastic Components	U V stabilised, weather resistance
COLOUR	Colour	Blue
	Paint// Finish	Poly Urethane Paint, UV Resistant
	Paint Coating Thickness (min)	100 micrometer
OTHER REQUIREMENTS	Ergonomic Design	Yes
	There shall be no crushing or searing points for user between moving and / or stationary parts of equipment during use	Yes
	Equipment shall be free from entrapments and sharp edges	Yes
	Installation Instructions must be provided	Yes
	Installation	Included
	Safety and quality Requirements	European Standard EN 16630: 2015 latest
	Instruction Plate	Stainless Steel, Size 150 X 230 X 0.7mm, with indelible printing
CERTIFICATION	Certification (Safety and Quality Requirements)	As per European Standard EN 16630
	Registration No and Validity of Registration	NA
APPROVAL	Drawing depicting detailed dimensions and foundation details shall be got approved from buyer before installation, if desired by buyer	Yes
WARRANTY	Warranty (years)	2 year

टिप्पणी | Note:: Seller has given an undertaking that it has made arrangements for getting the stores from an authorized distributor / dealer / channel partner of the OEM of the offered product. At the time of delivery of goods, Seller will provide necessary chain documents (in the form of GST Invoice) to prove that the supplied goods are genuine and are being sourced from an authorized distributor / dealer / channel partner of the OEM. In case of any complaint about genuineness of the supplied products, Seller shall be responsible for providing genuine replacement supplies.

ईपीबीजी विवरण | ePBG Detail

सलाहकार बैंक Advisory Bank :	NA
ईपीबीजी प्रतिशत (%) ePBG Percentage(%):	NA

आरसीएम/एफसीएम के संबंध में सामान्य खंड | General Clauses w.r.t RCM/FCM

- Where ever RCM is applicable, for sellers (Regular GST registered seller who opted out of FCM as per notifications of GST like GTA , unregistered seller), Buyer have liability of paying the GST and GST cess to the government on the specified rate mentioned by them in this contract. Seller will invoice buyer with Zero GST and GST cess.
- For Registered sellers as per FCM, rates will be inclusive of prescribed rate of GST and GST cess. ITC available to buyer as shown in the bid document have been applied while evaluating the bids. Seller has liability of paying the GST and GST cess to the govt and same will be charged from buyer while invoice.
- For Registered sellers who opted for RCM while quoting for specified category under section 9(3) like GTA rates will be exclusive of GST and GST cess. GST and GST cess as indicated by the buyer in the bid document payment of GST and GST Cess will be the liability of buyer.
- For Unregistered sellers Liability of payment of GST and GST cess is in Buyers scope. GST and GST cess as indicated by the buyer in the bid document will be the liability of buyer . Unregistered seller will invoice buyer with zero GST and Zero GST cess.
- For sellers under Composition Scheme: There is no liability of payment of GST and GST cess in Buyers cope. Seller will invoice Zero GST and GST cess in the invoice to buyer.

नियम और शर्तें | Terms and Conditions

1. General Terms and Conditions-

- This contract is governed by the [General Terms and Conditions](#), conditions stipulated to this Product/Service as provided in the Marketplace.
- This Contract between the Seller and the Buyer, is for the supply of the Goods and/ or Services, detailed in the schedule above, in accordance with the General Terms and

Conditions (GTC) unless otherwise superseded by Goods / Services specific Special Terms and Conditions (STC) and/ or BID/Reverse Auction Additional Terms and Conditions (ATC), as applicable

2. Buyer Added Bid Specific Terms and Conditions-

2.1 *Generic*:

OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 25 percent of bid quantity at the time of placement of contract. The purchaser also reserves the right to increase the ordered quantity by up to 25% of the contracted quantity during the currency of the contract at the contracted rates. Bidders are bound to accept the orders accordingly.

नोट: यह सिस्टम जनरेटेड फाइल है। कोई हस्ताक्षर की आवश्यकता नहीं है। इस दस्तावेज़ का प्रिंट आउट भुगतान/लेनदेन उद्देश्य के लिए मान्य नहीं है।

Note: This is system generated file. No signature is required. Print out of this document is not valid for payment/ transaction purpose.